

# PC8374K

## Desktop SuperI/O with Glue Functions

### General Description

The Winbond PC8374K Advanced I/O product is a member of the PC837x SuperI/O family. All PC837x devices are highly integrated and are pin and software compatible, thus providing drop-in interchangeability and enabling a variety of assembly options using only a single motherboard and BIOS.

PC8374K integration allows for a smaller system board size and saves on total system cost.

The PC8374K includes legacy SuperI/O functions, system glue functions, fan monitoring and control, commonly used functions such as GPIO, and ACPI-compliant Power Management support.

The PC8374K integrates miscellaneous analog and digital system glue functions to reduce the number of discrete components required. The host communicates with the functions integrated in the PC8374K device through an LPC Bus Interface.


The PC8374K extended wake-up support complements the ACPI controller in the chipset. The System Wake-Up Control (SWC) module, powered by  $V_{SB3}$ , supports a flexible wake-up mechanism.

The PC8374K supports both I/O and memory mapping of module registers and enables building legacy-free systems.

### Outstanding Features

- Fan monitor and control
- Glue functions to complement the South Bridge functionality
- $V_{SB3}$ -powered Power Management with 19 wake-up sources
- Controls three LED indicators
- 16 GPIO ports with a variety of wake-up options
- I/O-mapped and memory-mapped registers
- Legacy modules: Parallel Port, Floppy Disk Controller (FDC), two Serial Ports, Slow InfraRed Port and a Keyboard and Mouse Controller (KBC)
- LPC interface, based on Intel's *LPC Interface Specification Revision 1.1, August 2002*
- *PC2001 Revision 1.0* and *Advanced Configuration and Power Interface (ACPI) Specification Revision 3.0* compliant
- 128-pin PQFP package

### Block Diagram



## Features

### Glue Functions

- System Health support
  - Three PWM-based fan controls
  - Four 16-bit resolution tachometer inputs
- Generates the power-related signals:
  - Main Power good
  - Power distribution control (for switching between Main and Standby regulators)
  - Resume reset (Master Reset) according to the 5V standby supply status
  - Main power supply turn on ( $\overline{PS\_ON}$ )
- Voltage translation between 2.5V or 3.3V levels (DDC) and 5V levels (VGA) for the SMBus serial clock and data signals
- Isolation circuitry for the SMBus serial clock and data signals
- Buffers  $\overline{PCI\_RESET}$  to generate two reset output signals
- Buffers  $\overline{PCI\_RESET}$  to generate IDE reset output.
- Generates “highest active supply” reference voltage
  - Based on 3.3V and 5V Main supplies
  - Based on 3.3V and 5V Standby supplies
- High-current LED driver control for Hard Disk Drive activity indication
- Software selectable alternative functionality, through pin multiplexing

### General-Purpose I/O (GPIO) Ports

- All 16 GPIO ports powered by  $V_{SB3}$
- Each pin individually configured as input or output
- Programmable features for each output pin:
  - Drive type (open-drain, push-pull or TRI-STATE<sup>®</sup>)
  - TRI-STATE on detection of falling  $V_{DD3}$  for  $V_{SB3}$ -powered pins driving  $V_{DD}$ -supplied devices
- Programmable option for internal pull-up resistor on each input pin (some with internal pull-down resistor option)
- Lock option for the configuration and data of each output pin
- 15 GPIO ports generate  $IRQ/\overline{SIOPME}$  for wake-up events; each GPIO has separate:
  - Enable control of event status routing to IRQ
  - Enable control of event status routing to  $\overline{SIOPME}$  (via SWC)
  - Polarity and edge/level selection
    - Programmable debouncing

### Power Management

- Supports *ACPI Specification Revision 3.0, Sep 2, 2004*
- System Wake-Up Control (SWC)
  - Optional routing of events to generate SCI ( $\overline{SIOPME}$ ) on detection of:
    - Keyboard or Mouse events
    - Ring Indication  $\overline{RI}$  on each of the two serial ports
    - General-Purpose Input Events from 15 GPIO pins
    - IRQs of the Keyboard and Mouse Controller
    - IRQs of the other internal modules

- Optional routing of the SCI ( $\overline{SIOPME}$ ) to generate IRQ (SERIRQ)
- Implements the GPE1\_BLK of the ACPI General Purpose (Generic) Register blocks with “child” events
- $V_{SB3}$ -powered event detection and event-logic configuration

- Enhanced Power Management (PM), including:
  - Special configuration registers for power down
  - Low-leakage pins
  - Low-power CMOS technology
  - Ability to disable all modules
  - High-current LED drivers control (two LEDs) for power status indication with:
    - Standard blinking, controlled by software
    - Advanced blinking, controlled by power supply status, sleep state or software
    - Special blinking, controlled by power supply status, sleep state and software bit
  - $V_{BAT}$ -powered indication of the Main power supply state before an AC power failure
- Keyboard Events
  - Wake-up on any key
  - Supports programmable 8-byte sequence “Password” or “Special Keys” for Power Management
  - Simultaneous recognition of three programmable keys (sequences): “Power”, “Sleep” and “Resume”
  - Wake-up on mouse movement and/or button click

### Bus Interface

- LPC Bus Interface
  - Based on Intel’s *LPC Interface Specification Revision 1.1, August 2002*
  - I/O, Memory and 8-bit Firmware Memory read and write cycles
  - Up to four 8-bit DMA channels
  - Serial IRQ (SERIRQ)
  - Supports registers memory and I/O mapping
- Configuration Control
  - PnP Configuration Register structure
  - *PC01 Specification Revision 1.0, 1999-2000* compliant
  - Base Address strap ( $\overline{BADDR}$ ) to setup the address of the Index-Data register pair (defaults to 2Eh/2Fh)
  - Flexible resource allocation for all logical devices:
    - Relocatable base address
    - 15 IRQ routing options to serial IRQ
    - Up to four optional 8-bit DMA channels
  - Configurable feature sets:
    - Software selectable
    - $V_{SB3}$ -powered pin multiplexing

## Features (Continued)

### Legacy Modules


- Serial Ports 1 and 2
  - Software-compatible with the NS16550A and NS16450
  - Support shadow register for write-only bit monitoring
  - Data rates up to 1.5 Mbaud
- Serial Infrared Port (SIR)
  - Software compatible with the 16550A and the 16450
  - Shadow register support for write-only bit monitoring
  - HP-SIR
  - ASK-IR option of SHARP-IR
  - DASK-IR option of SHARP-IR
  - Consumer Remote Control supports RC-5, RC-6, NEC, RCA and RECS 80
- IEEE 1284-compliant Parallel Port
  - ECP, with Level 2 (14 mA sink and source output buffers)
  - Software or hardware control
  - Enhanced Parallel Port (EPP) compatible with EPP 1.7 and EPP 1.9
  - Supports EPP as mode 4 of the Extended Control Register (ECR)
  - Selection of internal pull-up or pull-down resistor for Paper End (PE) pin
  - Supports a demand DMA mode mechanism and a DMA fairness mechanism for improved bus utilization
  - Protection circuit that prevents damage to the parallel port when a printer connected to it is powered up or is operated at high voltages (in both cases, even if the PC8374K is in power-down state)
- Floppy Disk Controller (FDC)
  - Software compatible with the PC8477 (the PC8477 contains a superset of the FDC functions in the  $\mu$ DP8473, NEC  $\mu$ PD765A/B and N82077 devices)
  - Error-free handling of data overrun and underrun
  - Programmable write protect
  - Supports FM and MFM modes
  - Supports Enhanced mode command for three-mode Floppy Disk Drive (FDD)
  - Perpendicular recording drive support for 2.88 MBytes
  - Burst (16-byte FIFO) and Non-Burst modes
  - Full support for IBM Tape Drive Register (TDR) implementation of AT and PS/2 drive types
  - High-performance digital separator
  - Supports fast tape drives (2 Mbps) and standard tape drives (1 Mbps, 500 Kbps and 250 Kbps)
- Keyboard and Mouse Controller (KBC)
  - 8-bit microcontroller, software compatible with 8042AH and PC87911
  - Standard interface (60h, 64h, IRQ1 and IRQ12)
  - Supports two external swappable PS/2 interfaces for keyboard and mouse
  - Programmable, dedicated quasi-bidirectional I/O lines (GA20/P21, KBRST/P20)

### Clocking, Supply, and Package Information

- Clocks
  - LPC (PCI) clock input (up to 33 MHz)
  - On-chip Clock Generator:
    - Generates 48 MHz clock
    - Generates 32.768 KHz internal clock
    - $V_{SB3}$  powered
    - Based on the 14.31818 MHz clock input
- Protection
  - All pins are 5V tolerant and back-drive protected (except LPC bus pins)
  - High ESD protection of all the pins
  - Pin multiplexing selection lock
  - Configuration register lock
- Testability
  - XOR tree structure
    - Includes all the pins (except supply, analog and not connected pins)
    - Selected at power-up by strap input ( $\overline{\text{TEST}}$ )
  - TRI-STATE pins, selected at power-up by strap input ( $\overline{\text{TRIS}}$ )
- Power Supply
  - 3.3V supply operation
  - Separate pin pairs for main ( $V_{DD3}$ ) and standby ( $V_{SB3}$ ) power supplies
  - Backup battery input ( $V_{BAT}$ ) for SWC indications
  - Low standby power consumption
  - Very low power consumption from backup battery (less than 0.5  $\mu$ A)
- Package
  - 128-pin PQFP

## Physical Dimensions

All dimensions are in millimeters



Plastic Quad Flatpack (PQFP), JEDEC  
Order Number: 8374F2-x/xx

### Important Notice

Winbond products are not designed, intended, authorized or warranted for use as components in systems or equipment intended for surgical implantation, atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, or for other applications intended to support or sustain life. Furthermore, Winbond products are not intended for applications wherein failure of Winbond products could result or lead to a situation wherein personal injury, death or severe property or environmental damage could occur.

Winbond customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Winbond for any damages resulting from such improper use or sales.



#### Headquarters

No. 4, Creation Rd. III,  
Science-Based Industrial Park,  
Hsinchu, Taiwan  
TEL: 886-3-5770066  
FAX: 886-3-5665577  
<http://www.winbond.com.tw/>

#### Taipei Office

9F, No.480, Rueiguang Rd.,  
Neihu District, Taipei, 114,  
Taiwan, R.O.C.  
TEL: 886-2-8177-7168  
FAX: 886-2-8751-3579

#### Winbond Electronics Corporation America

2727 North First Street, San Jose,  
CA 95134, U.S.A.  
TEL: 1-408-9436666  
FAX: 1-408-5441798

#### Winbond Electronics Corporation Japan

7F Daini-ueno BLDG, 3-7-18  
Shinyokohama Kohoku-ku,  
Yokohama, 222-0033  
TEL: 81-45-4781881  
FAX: 81-45-4781800

#### Winbond Electronics (Shanghai) Ltd.

27F, 2299 Yan An W. Rd. Shanghai,  
200336 China  
TEL: 86-21-62365999  
FAX: 86-21-62365998

#### Winbond Electronics (H.K.) Ltd.

Unit 9-15, 22F, Millennium City,  
No. 378 Kwun Tong Rd.,  
Kowloon, Hong Kong  
TEL: 852-27513100  
FAX: 852-27552064

For Advanced PC Product Line information contact: [APC.Support@winbond.com](mailto:APC.Support@winbond.com)

Please note that all data and specifications are subject to change without notice.

All the trademarks of products and companies mentioned in this datasheet belong to their respective owners