



ACS-7630 RAID Kit

SPECIFICATIONS

Features

PATA Host Interface Disk Interface 3 x PATA

RAID Level 0 and 5 Form factor Two 5.25 inch half height

> - Automatic on-line rebuilding - Hot swappable drives

> > - Can be configured as master or slave

- OS independent

- LED indicators for disk operation status

- Alert notification

- No sharing host resource

- User friendly GUI

ENVIRONMENT CHARACTERISTICS

40°F to 115°F Operating Temperature

- Non-condensing humidity (%) 5°C to 46°C

5% to 85%

Non-Operating Temperature -13°F to 140°F

- Non-condensing humidity (%) -25°C to 60°C

5% to 95%

POWER REQUIREMENT

Input voltage (DC) Nominal voltage & margin 5V(5%) and 12V(8%)

EXPECTED RELIABILITY

MTBF >3000,000 POH

PHYSICAL CHARACTERISTICS

Dimension-inches (mm) Width 5.75(146.2) Length 8.84(224.6)

3.35(85.1) Height Weight-pounds (kg) 3.96(1.8)

WARRANTY

1 Year

NOTE: Specifications subject to change without notice. © 2004 ACCUSYS, Inc. V 1.0 All brand names and products are trademarks or registered trademarks of their respective holders.







8F-3, No.47, Lane 2, Sec. 2, Guangfu Rd., Hsinchu, Taiwan, R.O.C.

Tel: 886-3-575-0668 Fax: 886-3-575-0866

http://www.accusys.com.tw E-mail: sales@accusys.com.tw

- Accusys U.S.A., Inc.
- Accusys Korea, Ltd.
- Accusys China.
- Accusys EU B.V

sales@accusysusa.com

sales@accusys.co.kr sales@accusys.com.cn

sales@accusyseu.com