



SPECIFICATIONS

Operation System

CPU

SCSI I/O Processor

RAID level

Cache Memory

SCSI Channel to Host

Fibre Channel to Host

EIDE Channel to Device

Data Transfer Rate

Tagged Command Queuing

Stripe Size

Write Option

Hot Swap

On Line expansion

Hot Spare

Remote Management

Remote Alerts

Local Alerts

OS independent and Host Transparent

Intel i80303 64-bit RISI microprocessor

LSI 53C1010R

0, 1, 3, 5, 0+1

Up to 512MB

2(Max) Ultra 160 SCSI LVD

2(Max) Optional for 2Gb FC upgrade

16(Max)EIDE with Ultra DMA-100/133

Up to 160MB

Yes, up to 256 Commands

Variable

Write through or Write Back

Yes

Yes

Yes(rebuild Transparrently & Automatically)

RS-232 terminal emulation for configuration and monitoring

Fax, Pager

Built-in buzzer

NOTE: Specifications subject to change without notice. © 2004 ACCUSYS, Inc. V 1.0 All brand names and products are trademarks or registered trademarks of their respective holders.







8F-3, No.47, Lane 2, Sec. 2, Guangfu Rd., Hsinchu, Taiwan, R.O.C.

Tel: 886-3-575-0668 Fax: 886-3-575-0866

http://www.accusys.com.tw E-mail: sales@accusys.com.tw

- Accusys U.S.A., Inc.
- Accusys Korea, Ltd.
- Accusys China.
- Accusys EU B.V

sales@accusysusa.com sales@accusys.co.kr

sales@accusys.com.cn sales@accusyseu.com