



SPECIFICATIONS

Operation System

CPU

SCSI I/O Processor

RAID Level

RAID Architecture

Cache Memory

Dual Controller Capability

Battery Backup

SCSI Architecture

SCSI Channel to Host

SCSI Channel to Device

Data Transfer Rate

Devices support per Channel

Disk Drives

Tagged Command Queuing

Stripe Size

Write Option

Hot Swap

Hot Spare

SAF-TE Support

On Line Expansion

User Friendly GUI man

Remote Management

Remote Alerts Local Alerts

NOTE: Specifications subject to change without notice. © 2002 ACCUSYS, Inc.

All brand names and products are trademarks or registered trademarks of their respective holders.

OS Independent and Host Transparent

Intel 80303 64-bit RISC microprocessor

LSI 53C1010 Ultra 160

0,1,3,5,0+1

Multiple Array

Up to 512MB SDRAM with ECC on board

Yes (option)

Yes (option)

Multiple ID & Multiple LUN

2(Max) Ultra 160 LVD

3(Max) Ultra 160 LVD

Up to 160MB/s

Up to 45 drives (1 Host & 3 SCSI Channels)

Yes, up to 256 Commands

Variable

Write Through or Write Back

Yes

Rebuild Transparently & Automatically

Yes

Yes

Yes

RS-232 terminal emulation support

Fax, Pager

Built-in buzzer







8F, No.47, Lane 2, Sec. 2, Kuang Fu Rd., Hsinchu, Taiwan, R.O.C.

Tel: 886-3-575-0668 Fax: 886-3-575-0866

http://www.accusys.com.tw E-mail: sales@accusys.com.tw

- · Accusys U.S.A., Inc.
- Accusys Central Europe(Germany)
- Accusys Europe, Ltd.(UK)
- Accusys Korea, Ltd.

sales@accusysusa.com

sales@accusys.de

sales@accusys.co.uk

sales@accusys.co.kr