

Today's personal computers and LANs have the same power that mainframe computer systems had just a few years ago. Now PCs run multiuser applications, networks, large database programs and applications for operation and control that used to be possible only on much larger computers. What has been missing up to now is a high-performance storage subsystem that can keep pace with these advanced applications.

The PhD from Amcodyne is a true high-performance storage subsystem with a significant advantage—removable disk cartridges.

Because of its removable cartridges and the PhD's advanced performance features, you can also completely eliminate the need for tape backup systems.

The PhD sets a new standard of convenience and performance for serious R&D, business and engineering applications.

## Superior File Access Speeds

It's not just access time, but real mainframe-level features like our 16 Kbyte full-track buffer, 8.5 msec rotational latency and 1 to 1 interleaving that make the PhD the fastest and most efficient storage product available for PCs.


## Backup That's Convenient, Fast and Efficient

Removable 20.5 megabyte cartridges offer the ability to backup or store data without having to buy additional backup peripherals. That means you realize significant advantages in speed, performance and convenience. For example, by using the PhD's direct internal copy feature users can **copy or backup a full 20.5 megabytes in just 90 seconds!** And, your backup can be back on-line simply by reinserting the cartridge.

## Mainframe System Reliability

Amcodyne's patented Dynamic Head Loading system adds a new dimension to disk reliability. In fact, the PhD is so rugged, it is used in mobile military applications where traditional drives cannot survive the shock, vibration and humidity conditions. So, if you are entrusting more and more valuable data to your system, the PhD will provide you with truly superior durability and reliability.

Optimize your valuable computer-intensive time and increase your productivity. Contact your Amcodyne representative today and ask for a demonstration of the **PhD**.





THE
REMOVABLE CARTRIDGE
IS THE KEY
TO EXPANDABILITY
AND SECURITY

Fast, Convenient and User Friendly

File management, transfer of data and data backup procedures are easy and fast with the PhD. DOS, for example, treats each 20.5 megabyte disk as a matched, separate disk volume. And, since our cartridges are matched in performance as well as size, that means PC's can take full advantage of the spectacular access speed of the PhD. You can transfer data directly from fixed disk to cartridge and back, quickly and simply, making this one of the fastest and easiest to use storage subsystem on the market today. No matter where data is stored—on cartridges off-line, or on the fixed disks, you can get to it fast.

Most importantly, the PhD lets you decide how and when to manage your data. **Backups or transfers of a full 20.5 megabyte cartridge can be accomplished through a single SCSI command in 90 seconds**—a fraction of the time it takes to copy the same data through memory or onto tape.

The PhD makes PCs easier to use and increases system availability through unsurpassed speed, convenience and reliability.

#### FLEXIBILITY

Keep customer files on removable cartridges while applications programs and working files are maintained on the fixed disks.

#### SECURITY

Confidential databases such as financial spreadsheets and analytical files can be kept on cartridges, completely removed and externally secured as required per application.

## CONVENIENCE


Engineers can keep their project data on cartridges while CAE/CAD/CAM programs that are shared can be stored in the fixed area.

## EXPANDABILITY

Increase your storage capacity without limitation by simply adding cartridges. You can get on-line fast with the PhD.

# S U M M A R Y S P E C I F I C A T I O N S

CAPACITY	Per Drive Fixed Disks Cartridge	82.2 Mbytes formatted 61.7 Mbytes formatted 20.5 Mbytes formatted	POWER REQUIREMENTS	AC DC	None +24 Vdc; -12 Vdc; +5 Vdc; -5 Vdc
CONFIGURATION	Disks Data Heads Servo Recording Density Recording Method Track Density Tracks per Drive	3 fixed/1 removable 8 Embedded 10,986 bpi 2 of 7 RLLC 555 tpi 3864 fixed/1288 removable	ENVIRONMENTAL	Power Dissipation Temperature Humidity	98 watts (read/write), 180 watts (seek)  50°F to 104°F operating (10°C to 40°C), —40°F to 140°F storage (—40°C to 60°C)  20% to 80% RH operating (non- condensing), 5% to 95% RH storage (non-condensing)
PERFORMANCE RELIABILITY AND	Rotation Speed Average Latency Access Time Data Transfer Rate Error Rate	3522.9 rpm 8.5 msec 25 msec average 1.229 Mbytes/sec 1 in 10 <sup>10</sup> bits recoverable.		Altitude Shock Vibration	To 10,000 feet (3,048 m) operating to 40,000 feet (12,192m) storage Non-operating 30 G max. Operating 0.25 G max. (10-2000 Hz), non-operating 1.0 G max. (10-500 Hz)
MAINTAINABILITY	MTBF MTTR PM Service Life	1 in 1012 bits non-recoverable, 1 in 106 seeks >20,000 hours 30 minutes None 5 years	PHYSICAL	Drive Cartridge	Height 6.25 in. (158.8 mm) Width 8.50 in. (215.9mm) Depth 20.0 in. (508.0mm) Weight 36.5 lbs. (16.6 kg) ANSI standard



Headquarters
Century Data Systems, Inc.
2055 Gateway Place
Suite 650
San Jose, California 95110

(408) 298-5756

Operations
Amcodyne Division
1301 South Sunset Street
Longmont, Colorado 80501
(303) 772-2601
TLX: 384373 (AMCO)

Specifications subject to change without notice.
© Copyright 1986 Century Data Systems
Printed in U.S.A. 11/86
IBM & PC-AT are trademarks of International Business Machines Corporation;
Apple & Macintosh are trademarks of Apple Computer, Inc.
PhD is a trademark of Century Data Systems, Inc.

GSA No. GSOOK86AGS5286