

Hewlett-Packard HP 3000 Series

MANAGEMENT SUMMARY

Hewlett-Packard continues to enhance the HP 3000 family of computers with the addition of new peripherals. Two more laser page printers have been introduced, each capable of printing up to 12 pages per minute. The Desktop Laser page printer interfaces to an RS-232-C port. The second model, the Laser page printer, is packaged with a controller in a floor-standing unit and when used with HP's word processing and graphics software, it becomes a document generation device capable of printing charts, graphs and diagrams. Both forms and data may be printed simultaneously to generate documents such as purchase orders. A variety of word processing fonts in multiple pitch and point sizes are also available with this model.

New terminals introduced include a Dual-System Display Terminal which can be simultaneously connected to an HP system and to an IBM or IBM-compatible system. HP data entry features are on Port 1 and IBM 3276 features are on Port 2. The user can switch from one mode to the other by simply pressing a function key, but both modes remain active at all times, allowing tasks to be run concurrently on both hosts. Port 1 supports a wide variety of HP data communications protocols and Port 2 supports IBM bi-synch. Options available with this terminal add graphics features or word processing capabilities. A second terminal has been introduced for word processing under control of HP 3000 HPWord software. The terminal can also be used ➤



The Series 68, the top-of-the-line Series 3000, performs at the one-million-instructions-per-second level. The system offers many advantages of a 32-bit machine—a 32-bit data path, a 32-bit memory word, and dual arithmetic logic units—while maintaining full compatibility with existing HP software. The system shown here includes multiple disk units, an additional I/O bay, and HP's laser printer.

Hewlett-Packard continues to enhance the HP 3000 Series with the addition of many new peripherals and capabilities. These additions include two laser printers, one a desktop model, a word processing terminal, dual-system display terminal and tape drive. Continuing their commitment to networking, HP has also announced X.25 and PBX data communications capabilities.

MODELS: Series 39, Series 42, Series 48 and Series 68.

MEMORY: 512K bytes to 8 megabytes.

DISK CAPACITY: 28 megabytes to 9.7 gigabytes.

WORKSTATIONS: Up to 92 on the Series 39 and Series 42; up to 152 on the Series 48; and up to 400 on the Series 68.

PRICE: \$33,200 to \$186,100.

CHARACTERISTICS

MANUFACTURER: Hewlett-Packard Company, Computer Systems Division, 19447 Pruneridge Avenue, Cupertino, California 95014. Telephone (408) 725-8111.

CANADIAN SALES OFFICE: Hewlett-Packard (Canada Ltd.), 6877 Goreway Drive, Mississauga, Ontario L4V 1M8. Telephone (416) 678-9430.

Hewlett-Packard Company is a major designer and manufacturer of precision electronic equipment for measurement, analysis and computation. HP makes more than 5000 products for application in the fields of science, engineering, business, industry, medicine, and education. The company's principal product categories include computers and computer systems, handheld calculators, and computer/calculator peripheral products; test and measuring instrumentation and solid-state components; medical electronic equipment; and instrumentation for chemical analysis.

Hewlett-Packard products are sold and serviced by over 300 sales offices and distributorships in 70 countries, and are manufactured by approximately 33 domestic divisions and 17 overseas divisions. The company now employs over 69,000 people worldwide.

DATA FORMATS

BASIC UNIT: 16-bit word or eight-bit byte.

FIXED-POINT OPERANDS: 16-bit operands can be used by logical or fixed-point arithmetic instructions to represent unsigned 16-bit integers from 0 to 65,535 or signed 15-bit integers from -32,768 to +32,767. Double-integer fixed-point formats provide 32 bits of representation of values from -2 billion to +2 billion. Bit 0 for the most significant word is the sign bit. Logical operands are represented in positive integer format, while fixed-point operands are represented in two's-complement format. Also provided is 28-bit packed decimal arithmetic in hardware.

FLOATING-POINT OPERANDS: Includes single-precision 32-bit (2-word) operands with signed 9-bit exponent ➤

Hewlett-Packard HP 3000 Series

CHART A. SYSTEM COMPARISON

	Series 39	Series 42	Series 48	Series 68
SYSTEM CHARACTERISTICS				
Date of introduction	February 1983	June 1983	June 1983	June 1983
Date of first delivery	April 1983	December 1983	December 1983	December 1983
Operating systems	MPE-V	MPE-V	MPE-V	MPE-V
Upgradable from	—	Series 40	Series 44	Series 64
Upgradable to	—	—	—	—
MIPS	not available	not available	not available	not available
Relative performance (based on a rating of the Series 39 at 1.0)	1.0	1.25	1.25	3.0
MEMORY				
Minimum capacity, bytes	512K	1M	1M	3M
Maximum capacity, bytes	3M	3M	4M	8M
Type	NMOS	NMOS	NMOS	NMOS
Cache memory	none	none	none	8KB
Cycle time, nanoseconds	430	430	430	134
Bytes fetched per cycle	—	—	—	—
INPUT/OUTPUT CONTROL				
Number of channels	2	2	5	15
High-speed buses/channels	up to 2	up to 2	up to 2	up to 6
Low-speed buses/channels	up to 2	up to 2	3-5	9-15
MINIMUM DISK STORAGE	28MB	28MB	28MB	50MB
MAXIMUM DISK STORAGE	3.2GB	3.2GB	4.2GB	9.7GB
NUMBER OF WORKSTATIONS	92	92	152	400
COMMUNICATIONS PROTOCOLS	Bisynch, HDLC/SDLC, RS-232-C, RS-422, X.25	Bisynch, HDLC/SDLC, RS-232-C, RS-422, X.25	Bisynch, HDLC/SDLC, RS-232-C, RS-422, X.25	Bisynch, HDLC/SDLC, RS-232-C, RS-422, X.25

▷ as a data entry terminal with six pages of alphanumeric memory and VPlus/3000 support so that HP block mode screen oriented applications can be run. A graphics option is also available with the Word Processing Terminal.

More enhancements include additional data communications capabilities, the newest of which is the Distributed Systems Network/Private Branch Exchange (DSN/PBX). DSN/PBX provides HP 3000 users with the ability to utilize their PBX telephone systems for data transmission between the host HP 3000 and HP terminals and personal computers. Hewlett-Packard has certified three PBX manufacturers' equipment for connection to HP computer systems. Those certified are: Northern Telecom's SL-1 PABX line, ROLM Corporation's CBX line, and Intecom's S/40 IBX. Hewlett-Packard guarantees full support of its products when using these connections. The HP 3000 now supports a Fiber Optic Multiplexer to allow the interconnection of up to eight RS-232-C devices at distances up to 3280 feet (1000 meters). And, finally, X.25 hardware and software communications products have been added to provide communications between HP computer systems and terminals over X.25 Packet Switched Networks. Three main communications capabilities are provided: system-to-system communications; system-to-dial-up terminal communications; and system-to-leased-line communications. Also, an X.25 Cluster Controller is available, allowing a group of up to 16 remote terminals and printers to communicate with a host computer which can be an HP 3000, HP 1000 or non-HP computer.

And finally, a new 1/2-inch streaming tape drive has been added to the line of peripherals supported on the HP 3000. The tape drive can operate in either start/stop (50 ips) or streaming (100 ips) modes with a capacity of 1600 phase-▷

▷ and 22-bit positive fraction and extended-precision 64-bit (4-word) operands with signed 9-bit exponent and 55-bit positive fraction. In both single- and extended-precision formats, the exponent can range between -256 and +255, while an assumed "one" is placed to the left of the binary point in the fraction. (The "one" is disregarded for floating-point zero.) All floating-point numbers are by definition normalized. The binary point is assumed to be between the exponent and fraction. Bit 0 of the first word is the sign bit; the exponent in bits 1 through 9 is biased by +256.

INSTRUCTIONS: The HP 3000 Series has an unusually rich and varied complement of instructions; all, except the stack operation instruction, are one-word types with 23 distinct formats for 13 different instruction groups. The 65 stack instructions can be packed two per word. In general, each instruction has a number of basic fields. The first field is always four bits long and is used to define a specific operation code (for memory reference or loop control instructions) or one of four sub-opcode groups. All sub-opcode type instructions have an operation code extension field whose length and position in the instruction vary depending upon which of the four sub-opcode groups is specified. In some cases, a third operation code field (mini-opcode or special opcode) is used to extend the basic operation code. The rest of the 16-bit instruction is used for a variety of functions (count fields, bit positions, index specification, immediate operand, etc.) and is called the argument.

INTERNAL CODE: ASCII.

MAIN STORAGE

TYPE: NMOS utilizing 64K RAMs.

CYCLE TIME: The Series 39, 42, and 48 each have a cycle time of 430 nanoseconds for a 16-bit fetch and a read access time of 300 nanoseconds. The Series 68 includes an 8K byte cache memory to provide an average memory access time of 134 nanoseconds. The cycle time of 840 nanoseconds is for an 8-word block. ▶

Hewlett-Packard HP 3000 Series

- encoded characters per inch. Optional support for nonreturn to zero inverted (NRZI) 800 characters per inch double-density tape formats is also available.

The HP 3000 Series consists of four models, the Series 39, Series 42, Series 48 and Series 68. These systems represent enhanced versions of the earlier Series 40SX, 40, 44 and 64, respectively. All of the current models support an upgraded version of the operating system, MPE V, and all offer a disk caching feature to speed I/O transfers (optional on the Series 39, standard on the other three models).

The Series 68 is the most powerful HP 3000 to date with a performance level of one-million-instructions-per-second. This system offers many 32-bit advantages—a 32-bit data bus, a 32-bit memory word, and dual arithmetic logic units capable of performing 32-bit arithmetic in a single cycle. The Series 68 comes with three megabytes of main memory and can be expanded to eight megabytes. The system will support up to 24 data communication lines, 9.7 gigabytes of disk storage, eight tape drives, and up to eight line printers. The Series 68 supports 400 terminals, 336 of which may be connected point-to-point. This system comes standard with the HP Advanced Terminal Processor (ATP). The ATP provides communications capabilities while reducing system overhead via the ATP's own microprocessors.

The Series 48 is one of Hewlett-Packard's two 16-bit, mid-range systems. This system comes standard with two megabytes of main memory, and is expandable to four megabytes. Up to seven data communication lines, 4.2 gigabytes of disk storage, two line printers and eight tape drives are supported. The Series 48 has the ability to support a total of 152 terminals, 104 of those may be connected point-to-point. HP's Advanced Terminal Processor (ATP) is also available on the Series 48.

The other 16-bit, mid-range system is the Series 42. The Series 42 comes standard with one megabyte of main memory, expandable to three megabytes, and supports up to three data communications lines, 3.2 gigabytes of disk storage, two line printers and four tape drives. In addition, the Series 42 supports up to 92 terminals, 32 of which may be connected point-to-point.

The Series 39—utilizing a 16-bit microcoded processor—is the low-cost, entry level member of the HP 3000 family. The Series 39 comes standard with 512K bytes of main memory, with expansion capability to three megabytes, and is packaged with an integral cartridge tape and a 28-, 65-, or 132-megabyte Winchester disk. The Series 39 will support up to three data communication lines, 3.2 gigabytes of disk storage, two line printers and four tape drives. A maximum of 92 terminals is supported, 32 of which may be connected point-to-point.

Even though the Series 68, 48, 42, and 39 use MPE V, a new operating system with expanded capabilities, these systems are fully compatible with the entire HP 3000 installed base. The Multiprogramming Executive (MPE) operating system allows transaction processing on-line program develop-

- **CAPACITY:** The HP 3000 Series 39 and 42 support a minimum of 512K bytes of main memory. Additional memory is available in increments of 256K bytes or one megabyte, up to a maximum of three megabytes. The memory capacity of the Series 48 ranges from one megabyte to four megabytes in increments of 512K bytes or one megabyte. The Series 68 supports a minimum of two megabytes and a maximum of eight megabytes. Additional memory is available in one-megabyte increments.

CHECKING: Automatic fault detection and correction memory is used in all current HP 3000 models. The word length transmitted over the intermodule bus is 16 bits. In the memory modules the word length is expanded to 39 bits; 32 data bits and 7 bits for the automatic fault detection and correction logic. This provides the system with the capability of detecting single bit and double bit errors and correcting single bit errors.

STORAGE PROTECTION: Upper and lower address boundaries, provided by certain registers, define the limits of authorized program access in main memory. The microprogram routinely checks for bounds violation during execution (overlapped with operand fetch) and generates an interrupt if an unauthorized memory access attempt is made. Bounds violations may be classified under program transfer or reference, data reference, and stack overflow or underflow.

RESERVED STORAGE: The first 11 main memory locations are reserved for global system pointers used in the firmware implementation of virtual memory and variable-length program segmentation. Following this is a device reference table containing a set of four-word entries (one per controller, maximum 119 entries on the Series 39, 42, and 48, and 485 maximum on the Series 68) containing device interrupt vectors and the identity of the drives for each device.

CACHE MEMORY: The Series 68 has 8K bytes of cache memory and is the only HP 3000 system to support cache memory.

CENTRAL PROCESSOR

GENERAL: The HP 3000 Series processors include a firmware-implemented instruction set; firmware-implemented repetitive functions such as subroutine linkage, string processing, and buffer transfers; firmware-assisted software; bus control clock; and crystal clock dedicated to process execution measurements. The hardware processors consist of an arithmetic-logic unit, shifting network, and on the Series 39, 42, and 48, 72 specific-purpose registers, 18 of which are user-accessible. The Series 68 CPU also contains 72 specific-purpose registers with 21 of those instructions user-accessible.

Auto restart after power failure is standard. When the line voltage falls below 90 percent, a power-fail warning is issued. All register contents are moved to memory, system activities are completed, and then the system shuts itself down. All models include a rechargeable battery pack to maintain memory data during power failure. A minimum of 15 minutes is provided with the total amount of backup time dependent on memory size and battery condition (age and level of charge). When voltages reach 90 percent of their values, all registers are automatically restored and processing resumes.

The Series 39, 42, and 48 feature a Hewlett-Packard designed, microcoded, 16-bit processor using Schottky TTL technology. This technique provides high speed execution of instructions while maintaining machine instruction set flexibility. Each system is based on a modular design to allow independent elements to be interconnected through a central

Hewlett-Packard HP 3000 Series

CHART B. MASS STORAGE

Model	7911P	7912	7914P/7914TD	7920 M/S*
Type	Winchester built-in	Winchester built-in	Winchester built-in	Pack built-in
Controller model	one	one	one	8
Drives per subsystem/controller	28	65.6	132	50Mb
Formatted capacity per drive, megabytes	1.5	3.5	3.5	5
Number of usable surfaces	1,444 tracks	1,144 tracks	2,328 tracks	823 tracks
Number of sectors or tracks per surface	256/sector	256/sector	256/sector	256/sector
Bytes per sector or track	26.7 ms	26.7 ms	27.7 ms	25 ms
Average seek time	8.3 ms	8.3 ms	8.3 ms	8.3 ms
Average rotational/relay time	35 ms	35 ms	36 ms	33.3 ms
Average access time	983 kbs	983 kbs	983 kbs	740 kbs
Data transfer rate	all models	all models	all models	all models
Supported by system models	includes built-in 1/4", 67Mb cartridge tape drive	includes built-in 1/4", 67Mb cartridge tape	includes built-in 1/4", 67Mb cartridge tape; 7914 TD includes 1/2", 1600 bpi tape drive	
Comments				

*79xxM = MAC Master Disk including controller. Up to 7 slave disks can be connected to the master.
79xxS = MAC Slave Disk.

Chart B (Continued) MASS STORAGE

MODEL	7925 M/S/T	7933 H/G	7935H	9895A
Type	Pack	fixed	Pack	dual 8-inch flexible disk
Controller model	built-in	built-in	built-in	•
Drives per subsystem/controller	8	one	one	two
Formatted capacity per drive, megabytes	120	404	404	23
Number of usable surfaces	9	13	13	2
Number of sectors or tracks per surface	823	1,321 tracks	1,321 tracks	77 tracks
Bytes per sector or track	256/sector	256/sectors	256/sector	256/sector
Average seek time	25 ms	24 ms	24 ms	—
Average rotational/relay time	11.1 ms	11.1 ms	11.1 ms	—
Average access time	36.1 ms	35.1 ms	35.1 ms	179 ms
Data transfer rate	740 kbs	1.2Mb/sec.	1.2Mb/sec.	23 kbs
Supported by system models	all models	all models	all models	all models
Comments	7925T is an add-on unit providing 240Mb of disk storage	7933 is an add-on unit providing 1.2 gigabytes of disk storage	7935G is an add-on unit providing 1.2 gigabytes of disk storage	opt. 010-single drive

➤ ments, data communications and batch processing. An on-line HELP command is one illustration of HP's user friendly software approach. The full complement of language processors available include Basic, Cobol, Fortran, Pascal, Transact, RPG, and SPL.

Disk caching increases response time and provides higher throughput by caching information from disk in main memory. This feature anticipates code and data likely to be needed by working applications, stores it in main memory (as space is available), and checks memory before accessing the disk for information. The more I/O intensive the operation and the larger the size of memory, the more the user benefits from the caching feature. Disk caching is an optional feature on the Series 39, but is standard on the other HP 3000 models.

The HP 3000 uses a stack architecture to provide a number of system advantages. Storage allocation is dynamic and temporary storage of intermediate values is automatically provided. Compilers, then, do not need to save and restore registers for intermediate results. Code compression is possible by the omission of operands in many of the ➤

➤ system bus structure. The independent elements consist of a CPU which controls memory via a memory controller, general I/O channels, DSN/Asynchronous Data Communication Controllers, and the bus system to allow communication between the I/O devices. The system also includes a console and a Control and Maintenance Processor (CMP).

The Series 68 CPU is a Hewlett-Packard designed, micro-coded processor using high speed Emitter Coupled Logic (ECL) technology and a dual arithmetic logic unit (ALU). This provides the highest performance level achieved in an HP 3000, one-million-instructions-per-second. The modular Series 68 includes the following components: CPU with dual arithmetic logic units (ALUs), cache memory, main memory, Writable Control Store, I/O Adapters, General I/O channels, and DSN/Advanced Terminal Processors. Communications between modules is accomplished using a high speed Central System Bus and up to three Intermodule Busses. The Series 68 also includes a system console, system display panel, and a Diagnostic Control Unit (DCU).

Program code and data are maintained in strictly separate domains and cannot be intermixed except in "immediate" type data present in program instructions. This design was chosen so that all program code would be protected from alteration, thus permitting the development of reentrant programs for multithread operation. ➤

Hewlett-Packard HP 3000 Series

▷ instructions. The HP 3000 includes a separate code area and data stack. Added to the fact that code is not modifiable while active in the system, this allows code to be shared among several users. HP code is reentrant which when combined with stack processing makes possible subprogram recursion—a subprogram calling itself. This combination is essential for efficient compilers and system software.

All of the HP 3000s utilize 64K RAM memory chips to provide maximum memory with a minimum of boards. The Series 68 also adds an 8K byte cache memory to speed processing. Hewlett-Packard claims the cache memory has a 95 percent effective hit rate for memory accesses.

The Series 39, 42, and 48 models include an Intermodule Bus (IMB) to handle communications between the CPU, memory, and I/O modules. The CPU only releases control of the IMB upon request. The Series 68 has a Central System Bus (CSB) to perform the same general functions. The CSB features a 56 megabyte-per-second bandwidth and allows each module independent control of bus transfers. The Advanced Terminal Processor (ATP) is one of the independent microprocessor-based modules accessing the CSB.

Hewlett-Packard set several design goals for the 3000 Series product line. They included a common operating system and object code compatibility, a broad range of price and performance options, a clear growth path, friendly software, and full networking capabilities. A performance comparison of these newest HP 3000 models with the earlier systems is as follows:

Model	Performance Level
Series 30	Base-line
Series III	1.5 to 2 times Series 30
Series 39	3 times Series 30
Series 42	3.5 times Series 30
Series 48	4 times Series 30
Series 68	9 times Series 30

Hewlett-Packard offers a wide range of peripherals, personal computers and mass storage devices for use on the HP 3000. Disk storage is available in sizes ranging from 28 megabytes to 404 megabytes per drive. One magnetic tape model features a 6250 bits per inch, group-encoded unit for burst-speed backup operations. Printers vary from a 40 character per second letter quality printer to 45 pages per second Laser Page Printing Systems. The wide range of terminals available can allow the user to tailor each workstation according to its task. Hewlett-Packard also offers a broad range of personal computers which have the ability to communicate with an HP 3000 system as terminal emulators or standalone processors.

Internationally accepted, standard protocols are planned as the fundamental basis for the HP Distributed Systems Network (HP-DSN) Communications architecture. HP ▷

▶ Firmware-assisted software includes the interrupt handler, cold-start loader, power-failure data-saving routines, automatic restart routines, and front panel-initiated diagnostics. The basic microprogramming architecture is asynchronous and designed to facilitate a multiprogrammed, variable-length, code-segmentation, virtual-memory and mode of operation with extensive stack processing.

CONTROL STORAGE: Bipolar Read-only Memory (ROM) consists of 12K 48-bit words for the Series 39, 42, and 48. The Series 68 utilizes 64K bytes of Random-access Memory (RAM) as its control storage. All of this control storage is utilized and is not directly accessible to the end user. Microinstruction cycle time is 105 nanoseconds for the Series 39, 42, and 48. The Series 68 microinstruction cycle time is 75 nanoseconds.

REGISTERS: There are 72 hardware registers on the HP 3000. Eighteen are accessible to the programmer on the Series 39, 42, and 48; twenty-one registers are available for programmer use on the Series 68. Those dedicated to system use are mostly 16-bit registers. These include the current and next instruction registers; scratch pad, flag, and interrupt registers; I/O registers; memory address and data registers; and firmware address registers. The Series 68 adds four cache operand registers, a performance register, and four ALU registers to those provided on the other systems.

Registers accessible to the programmer include the four code segment pointers, seven stack pointers, four top of stack registers (eight in the Series 68), and the Index and Status registers.

The code segment group consists of the Program Base register (PB), which defines the program base of the code segment being executed; the Program Counter (P), which contains the 16-bit absolute address of the instruction being executed; the Program Limit register (PL), which defines the limit of the code segment being executed; and the Program Bank register (PBNK), which defines the bank of 64K words where the code segment resides (Series 39, 42, and 48). The Series 68, instead of the PBNK register, includes a BNKP register which performs the same function.

The stack pointer group is divided into the data segment group and the stack pointers. The data segment group includes the Data Base register (DB), used to define the data base of the current user's stack; the Q register, utilized to define the current stack master in the current data segment; the Data Limit register (DL), where the data limit of the current data segment is defined; and the Data Base Bank register (DBNK) which contains the location of the bank in which the stack or split stacks reside. DBNK is used in the Series 39, 42, and 48 machines. The Series 68 uses the BNKD register to perform this function. The stack pointers include the SM register, which defines the number of top-of-stack elements that are in CPU Stack registers; the Z register, whose function is to define the stack limit of the current user's stack; and the Stack Bank register (SBNK), used to define the 64K word bank in which the stack resides (Series 39, 42, and 48). The Series 68 uses the BNKS register to perform this function.

The Status register indicates the current status of the computer hardware, including whether the system is in user or privileged mode. The Switch register (SWCH) is a 16-bit register representing front panel switches used for bootstrapping and fault diagnosis on the Series 39, 42, and 48. A performance register (PERF) in the Series 68 is used by Hewlett-Packard to make electrical measurements to monitor performance.

ADDRESSING: Only privileged instructions may use absolute addressing. All other addressing is performed using one ▶

Hewlett-Packard HP 3000 Series

CHART C: TERMINALS

DEVICE	DESCRIPTION
INTERACTIVE DISPLAYS	
2382A/2622A	Interactive Display; inverse video, underline, half-bright, blinking, 8 standard user-definable soft keys, 128 Roman Character set, block or character mode, 48 lines of memory, 9600 bps
2621B/2623A	Interactive Display; inverse video, underline, half-bright (2623A only), blinking (2623A only), 8 standard user-definable soft keys, 128 Roman Character set, block (2623A only) or character mode, 48 lines of memory, 9600 bps
2624B	Interactive Display; inverse video, underline, half-bright, blinking, 8 standard user-definable soft keys, 128 Roman Character set, block or character mode, up to 32K bytes of memory, 9600 bps
2625A	Dual system display terminal can simultaneously be connected to an HP system and an IBM compatible system. Features include: optional graphics mode, wide choice of data communications options, ergonomic design
2626A/W	Interactive Display; inverse video, underline and blinking, 8 standard user-definable soft keys, 128 Roman Character set, block or character mode, 119 lines of memory, 9600 bps
2627A	Interactive Display; inverse video, underline, half-bright, blinking, 8 standard user-definable soft keys, 128 Roman character set, block or character mode, 48 lines of alpha memory, 9600 bps
2628A	Word processing terminal; can be used in data entry mode. Features include optional graphics mode, up to 6 pages of display memory, 19,200 bps, and printer port
2641/2645A	Interactive Display; inverse video, underline, half-bright, and blinking standard for 2641A-2645A requires 13231A display option; 8 standard user-definable soft keys, 64 Roman and 128 APL character set for 2641A (APL 3000 is available only on HP 3000 Series III), 128 Roman character set for 2645A, block or character mode, 4 to 12K bytes of memory, 9600 bps
2647F	Interactive Display; inverse video, underline, half-bright, blinking, 8 standard user-definable soft keys, 128 Roman character set, block or character mode, up to 115 lines of alpha memory, 9600 bps
2648A	Interactive Display; inverse video, requires 13231A display option for underline, half-bright, and blinking 8 standard user-definable soft keys, 128 Roman character set, block or character mode, 8-12K bytes of memory, 9600 bps
2703A	Interactive Display; inverse video, underline, half-bright, blinking, 8 standard user-definable soft keys, 128 Roman character set, block or character mode, up to 32K bytes of alpha memory, 19,200 bps

➤ recognized and addressed the communications needs for workstation to HP system transmission, for an HP system to an HP system environment, for HP to an IBM distributed system arrangement. A variety of communications products allow the user to customize the system to his or her needs.

Software available for the HP 3000 includes HP's data base management system (Image/3000 plus Query/3000). Image/3000 allows information to be related logically between data sets (files), minimizing data redundancy and facilitating information retrieval. Its companion package, QUERY/3000, allows both programmers and nonprogrammers to access an Image data base with simple, English-like commands.

The close parallels between the Fortran and Basic language used on the HP 1000 Series computers and their counterparts on the HP 3000 systems make it possible for users with the HP 1000 to upgrade easily to the HP 3000. (Even though conversion will be required, the standard portions of the languages will be unchanged, and only the discrepancies in language extensions and data format expressions will need to be resolved.)

The Fundamental Operating Software is included with all HP 3000 models and includes the operating system, MPE V, Edit/3000, FCopy/3000, Sort-Merge/3000, Image/3000, Query/3000, KSAM/3000, and HP VPlus/3000. ➤

➤ of the six allowable relative techniques. Two techniques apply to code, while four apply to data. Except for privileged instructions (including I/O), all word addressing is direct, direct-indexed, indirect or indirect-indexed. Both word and byte addressing is relative to the Q-register (plus or minus), the DB-register (plus only) or the S-register (minus only). The S-register is a logical addition of the contents of the SM and SR-registers. In addition, word addressing is relative to the P-register (plus or minus). Indirect addressing and indexing are both provided, individually or in combination. Up to 32K words (addresses) can be referenced by a memory reference instruction.

Double-word indexing is provided for two memory address instructions that automatically cause the index register contents to be incremented by two during development of the effective address.

INTERRUPTS: The interrupt system provides for up to 105 external interrupts. There are 16 levels of interrupt masking, and each device is initially assigned to one of the 16 levels to fix priorities and permit masking under software control. Under microprogram control, context switching for an interrupt is performed in an average time of 21 microseconds (minimum 18; maximum 24.5). The interrupt routines operate on a common interrupt control stack to permit nesting of interrupt routines for multiple interrupts; context switching time is reduced by about two microseconds should nested interrupts occur. Twenty internal interrupts for user errors, system violations, hardware faults, and power fail/restart are also provided, plus 14 traps for arithmetic errors and illegal use of instructions or privileged mode.

The priority assigned to external devices is determined by the device's logical proximity to the I/O processor (IOP) on ➤

Hewlett-Packard HP 3000 Series

CHART D. PRINTERS

Model	2601A	2602A	2608S	2611A	2619A	2563A
Type	letter-quality	letter quality	dot matrix impact	chain	Drum	dot matrix
Speed	40 cps	25 cps	400 lpm	600 lpm	1000/750 lpm	300 lpm
Bi-directional printing	yes	yes	no	no	no	no
Paper size	up to 15 inches	up to 15 inches	up to 16 inches	up to 19½ x 15 inches	up to 19 inches	up to 16.7 inches
Character formation	full-formed	fully-formed	varies	chain full-font	chain	varies
Horizontal Character spacing (char/line)	10 or 12	10 or 12		10	10	5/10/16.7
Vertical line spacing (lines/inch)	6 or 8	6 or 8	6 or 8	6 or 8	6 or 8	6 or 8
Character set	88/92/96	98	128	64/96	64/96	256
Buffer	2KB	2KB	1KB	2 lines	2 lines	1KB
Controller/Interface	RS-232-C	RS-232-C;	HP-IB	Parallel-Differential	Parallel-Differential	HP-IB or RS-232-C
No. of printers per Controller/interface	one	one	two/four	two	four	two/four
Printer dimensions (h x w x d) inches	9¼ x 24¼ x 18¾	9¼ x 24¼ x 17¾	40 x 27 x 22	42¾ x 36½ x 26	42¾ x 36½ x 26	10¾ x 23.6 x 17¾
Graphics capacity	no	no	yes	no	no	yes

HP is concentrating its applications development efforts on the HP 3000 Family in four major areas: manufacturing, distribution, administration, and office automation. Materials Management/3000 and Production Management/3000 are manufacturing packages intended for manufacturers of products assembled from discrete components. HP provides complete solutions for the wholesale distribution market with two products—SFD/3000 (System for Distributors) and OM/3000 (Order Management). These products are used for order processing, inventory management, and associated accounting functions. HP also provides a complete set of financial, cost, asset, and planning applications. Currently, eight interactive financial software packages are included under the umbrella name HP Financial Accounting. These eight packages are: General Ledger, Accounts Payable, Accounts Receivable, Dual Ledger, Allocator, Report Facility, Interface Facility, and General Accounting. Office Systems products provide a system-wide solution to individual employee word processing and decision support needs. A series of programming aids, including Rapid/3000, is available to provide an improvement of two to ten times in programming productivity.

Customer services for the HP 3000 Series include pre-installation site planning, installation, several levels of training (given both at users' sites and at HP training centers), several levels of on-site hardware and software service, consulting, reference manual updates, information newsletters, and a users' group.

The HP 3000 family is an integral part of Hewlett-Packard's Manufacturer's Productivity Network. HP-MPN includes integrated systems, applications software and communications facilities for use in four major application centers: administrative and office services; factory and plant automation; operational planning and control systems; and computer-aided engineering.

Hewlett-Packard has initiated a System Re-Marketing Operation to sell or rent refurbished and rewarranted HP 3000

the interrupt poll line. Masking is permissible through the 16-bit mask word, which will enable or disable an interrupt request according to the bit pattern of the word.

OPERATING ENVIRONMENT: The Series 39 and 42 System Processing Units (SPU) are housed in identical standalone cabinets, the Series 48 is housed in a desk-style cabinet, and the Series 68 is contained in a larger standalone cabinet. The dimensions for each are given below in inches:

	Series 39	Series 42	Series 48	Series 68
Height (inches)	40	40	28.5	48
Width	24	24	72.25	69
Depth	22.4	22.4	31.25	26
Weight (pounds)	190	190	240	1200

With the optional I/O bag, the SPU measures 48 inches (121.92 cm) by 105 inches (266.70 cm) by 26 inches (60.04 cm) and weighs 1500 pounds (681.8 kg).

The Series 39 and 42 require a line voltage of 120 VAC at 60 Hz or 220 VAC at 50 Hz and a line current 8.5A at 60 Hz or 4.5A at 50 Hz. Heat dissipation is 3000 BTUs per hour. The Series 48 requires a line voltage of 210 VAC at 60 Hz or 220 VAC at 50 Hz with a line current of 13.1A at 60 Hz or 12.4A at 50 Hz. The system dissipates 7380 BTUs per hour. The Series 68 requires a line voltage of 200 VAC, 3 phase at 60 Hz, or 380 VAC, 3 phase at 50 Hz with a line current of 24A at 60 Hz or 13A at 50 Hz. Heat dissipation is 12,000 BTUs per hour.

All HP 3000 models have a recommended operating temperature of 20° C to 25.5° C or 68° F to 78° F. The recommended operating relative humidity is 40 to 60 percent non-condensing.

INPUT/OUTPUT CONTROL

The Series 39, 42, and 48 utilize an Intermodule Bus (IMB) to handle communications between the CPU, memory, and I/O modules. The CPU generates over 90 percent of the bus activity and has continuous access to the bus. The CPU relinquishes control to the I/O channels only on request.

Hewlett-Packard HP 3000 Series

CHART D. PRINTERS

Model	2932A	2933A	2934A	2680A	2687A	2688A
Type	dot matrix	dot matrix	dot matrix	Laser	Laser	Laser
Speed	200 cps	200 cps	40/67/ 200 cps	45 pages/ minute	12 pages/ minute	12 pages/ minute
Bi-directional printing	yes	yes	yes	not applicable	not applicable	not applicable
Paper size	up to 15¾ inches	up to 15¾ inches	up to 15¾ inches	8½ x 11 inches	8½ x 11 inches	8½ x 11 inches
Character formation	9 x 12 dot matrix	9 x 12 dot matrix	9 x 12 or 36 x 24	varies	300 x 300 dots/inch	6 lines/inch
Horizontal Character spacing (char/line)	5/10/16.7	5/10/16.36	5/10/12/163	varies with character set	10/12/15 cpi	15 cpi
Vertical line spacing (lines/inch)	up to 12	up to 12	up to 12	varies with character set	6 or 8 lines/ inch	6 lines/inch
Character set	varies	varies	varie	over 100 different sets	127	182
Buffer	2KB	2KB	2KB	Standard with 256KB memory, expandable to 2MB	256 bytes	2MB memory standard
Controller/Interface	RS-232-C	RS-232-C	RS-232-C	HP-IB	RS-232-C	HP-IB controller included
No. of printers per controller/interface	—	—	—	two	one	one
Printer dimensions (h x w x d) inches	7.28 x 23.85 x 14.37	7.28 x 23.85 x 14.37	7.28 x 23.85 x 14.37	48 x 64.5 x 26.4	11 x 20 x 19.5	11 x 20 x 19.5 plus 29 x 37 x 28- controller yes
Graphics capacity	yes	yes	yes	yes	no	yes

models. Sales channels for these systems will be the same as for new products. Standard HP 3000 quantity discounts apply to the remarketed models. User upgrades, lease returns, and internal capital equipment are the sources for the equipment. These models are, of course, software and peripheral compatible with the new systems.

ADVANTAGES AND RESTRICTIONS

Hewlett-Packard has continually updated the HP 3000 family of computers by introducing new models approximately every two years. All models share a common operating environment, however, providing a growth path to the user which ensures that application programs can be moved without conversion or recompilation from one model to another. Every HP 3000, from the first model released, is upgradable to the more powerful systems currently in the product line.

Another advantage is the wide selection of software available for the HP 3000 from both HP and third parties. The specific areas HP has targeted are particularly well represented with software. Thirdly, the networking capabilities of the system are varied and continually enhanced. Hewlett-Packard not only provides a wide range of data communications services to link their own systems together (both HP 3000 to HP 3000 and HP 3000 to other Hewlett-Packard systems), but also provides many choices utilizing industry standards for the multivendor user.

One drawback to the HP 3000 remains the absence of a growth path to a true 32-bit computer system. Once a user has reached the Series 68, there is no larger system to upgrade to.

► The IMB has separate address and data paths, each with handshake controls operating in a master/slave mode to transfer data. Any channel request will cause the CPU to relinquish control of the IMB so the request can be serviced.

The Series 68 Central System Bus (CSB) is the communication link between the CPU module, main memory module, and the I/O adapter modules. The CSB has a 56 megabyte per second overall bandwidth to allow support of multiple IMBs. No module has implied control of the CSB; each operates independently except when it is necessary to transfer data or send commands. The initiating module asks for and receives control of the CSB. All transfers to and from memory are in eight-word blocks.

The I/O adapter modules (IOA) are an interface between the Central System Bus and the Intermodule Busses to allow communication between the I/O system, main memory, and the CPU. Up to three Intermodule Busses are supported on the Series 68. The IOA synchronizes the slow speeds of the IMB to the Central System Bus. A 1024 byte buffer cache memory is included in each IOA to handle communications between the 16-bit IMB and the 32-bit CSB. To devices on the IMB, the IOA appears as memory responding to IMB requests generated by I/O controllers.

I/O CHANNELS: The General I/O Channel (GIC) is the primary channel for communications to I/O devices other than terminals. Each GIC controls a Hewlett-Packard Interface Bus (HP-IB) and translates I/O commands into the proper HP-IB protocol. Nearly all I/O transactions are accomplished without software interrupts. The GIC contains Direct Memory Access (DMA) hardware to allow large data records to be transferred at the maximum HP-IB speed of 1 megabyte per second.

CONFIGURATION RULES

GENERAL: As is true with most minicomputers, the complement of peripheral equipment for HP 3000 systems is restricted only by the number of slots available in the CPU ►

Hewlett-Packard HP 3000 Series

CHART E. MAGNETIC TAPE EQUIPMENT

	7970E	7976A	7974A
MAGNETIC TAPE EQUIPMENT			
Type	reel-to-reel	reel-to-reel	reel-to-reel
FORMAT			
Number of tracks	9	9	9
Recording density	1600 bpi	1600 or 6250 bpi	800/1600 bpi
Recording mode	PE	PE or GCR	PE/NRZI
CHARACTERISTICS			
Controller model	30215A	included	included
Drives per controller	four	one	one
Max. storage capacity, bytes	40MB	140M	20MB NRZI 40MB PE
Tape speed, inches/second	45 ips	75 ips	100
Data Transfer Rate, bps	72 kbs	120 or 468 kbs	160 kbs—streaming 80—start/stop
Streaming Technology	no	yes	yes
Start/Stop mode, speed	—	—	50 ips
Switch selectable	no	yes	no
Comments		Auto. load and auto. thread	Auto. thread and load

➤ COMPETITIVE POSITION

Because of the emphasis in the manufacturing/distribution areas, competition for the HP 3000 centers around other vendors who have application programs for these same areas such as IBM, Burroughs and DEC. Specifically, Hewlett-Packard positions their systems against the competition as follows: the Series 39 with the IBM System 34 and System 38 Model 4, DEC VAX-11/730 and Burroughs B1955 and B1985; the Series 42 with the IBM System 38 Model 5 and Model 7, DEC VAX-11/750, and Burroughs B1985; the Series 48 with the IBM 4341-9, 4341-10, and System 38 Model 8 and the DEC VAX-11/750; and the Series 68 with the IBM 4341-1, 4341-2, 4341-11, DEC VAX-11/780 and the Burroughs B5920. More competition can be found in the Data General MV/4000 and Perkin-Elmer 3205 and 3210.

Even though the HP 3000 is a 16-bit system, Hewlett-Packard claims the systems are competitive in the 32-bit marketplace because of the HP 3000's fast cycle times (134 nanoseconds for the Series 68) and strong support for large numbers of terminals in interactive environments.

USER REACTION

The HP 3000 was well represented in the 1983 Datapro Computer Users Survey, with 183 users responding. These users represented 235 systems with an average installation time of 36 months. The majority of the users (135) purchased their systems, while 19 are leasing the system from the manufacturer and 26 are leasing from a third party.

Memory capacity on the systems ranged from between 64K bytes and 128K bytes to over 8000K bytes. The largest number of users (76) reported memory sizes of between one million and two million bytes. Total disk storage capacity ranged from 256K bytes to over 1200M bytes with 76 users reporting disk capacity of between 200M and 600M bytes and another 60 users reporting between 600M and 1200M bytes of disk storage. ➤

➤ chassis or its extensions, by software restrictions, by controller limitations, and by marketing considerations.

Maximum configuration parameters for an HP 3000 Series system are as follows:

- Up to eight megabytes of main memory.
- Up to 9.7 billion bytes of on-line disk storage.
- Up to 400 multipoint terminals.
- Up to eight magnetic tape drives.
- Up to eight line printers.
- Up to two laser printer systems.

WORKSTATIONS: Up to 92 terminals may be configured on each Series 39 and 42 system and up to 91 of these may be multipoint terminals; all may operate at 9600 baud. The Series 48 increases the maximum number of terminals to 152, and 151 of these units may operate in a multipoint environment. The Series 68 is physically capable of configuring 400 multipoint terminals but software dictates that only 200 may be simultaneously active.

DISK STORAGE: The Series 39 includes either a 28-, 65-, or 132-megabyte Integrated Storage Unit with an integral Cartridge Tape Drive. A total of eight disk drives, including the unit packaged with each system, is supported on the Series 39. The Series 42 does not include any prepacked disk unit as part of the basic configuration but, like the 39, does support a maximum of eight disk drives. The Series 48 and 68 increase the maximum number of disk drives supported per system to 16 and 24, respectively. All of the HP 3000s support only one Integrated Storage Unit per system. A second controller must be ordered to support the integral cartridge tape to prevent user-lockout during tape back-up operations. The disk units interface to the GIC; a dedicated GIC is required to support the integral cartridge tape unit on the Integrated Storage Unit.

MAGNETIC TAPE UNITS: The cartridge tape drive included with the Integrated Storage Unit is required as a system backup and for software updates on the Series 39. The cartridge tape is designed as a backup device for a maximum of 132 megabytes of disk capacity. When mass storage capacity exceeds 132 megabytes, additional magnetic tape drives must be added as the primary system backup. ➤

Hewlett-Packard HP 3000 Series

➤ The majority of the users (160) reported their systems being used in central processing sites, with 37 of these systems having from one to three distributed processing nodes, eight having from four to nine nodes, and 13 having 10 or more nodes. The remaining 23 users locate their systems in distributed processing sites. One user reported having no local workstations; the most users (73) reported between six and fifteen local workstations, and another 57 users reported between 16 and 30 workstations. Seventy users reported from one to five remote workstations and 12 users have over 60 remote workstations.

Predominate applications used on the systems include: accounting/billing (135 users; payroll/personnel and order processing/inventory (86 users); manufacturing applications (61 users); sales/distribution (58 users); and purchasing (55 users). The majority of the users (155) developed their programs in-house, 81 users have proprietary software, 70 users purchased packaged programs from the manufacturer, and 68 use contract programming. The most common programming language employed was Cobol (123 users), with another 17 using Fortran and 16 using Basic. Almost all of the users (170) use a Data Base Management System and 160 of these respondents use the manufacturer's package. Another 68 users have a communications monitor and 56 of these users have the manufacturer's package.

As the ratings indicate, respondents were well-satisfied with their systems. Specifically, users identified these advantages of the HP 3000: 157 stated that the system was easy to expand/reconfigure; 144 said that the data base language was efficient and effective; 114 were happy with the response time; 85 found that HP's productivity aids helped to keep programming costs down; 62 mentioned that programs/data carried over from other systems were compatible (as the vendor promised); and 54 added that the system was power/energy efficient.

On the opposite side, users experienced the following problems with their systems: costs (for hardware, vendor-supplied software, and support) exceeded the expected total (17 users); vendor enhancements/changes to hardware/software were hard to keep up with (14 users); installation of the equipment was late (13 users); and the computer proposed by the vendor was too small (12 users).

The ratings given to the HP 3000 are shown in the following table:

	Excellent	Good	Fair	Poor	WA*
Ease of operation	116	61	4	0	3.6
Reliability of mainframe	147	34	2	0	3.8
Reliability of peripherals	113	66	3	0	3.6
Maintenance service:					
Responsiveness	88	82	10	3	3.4
Effectiveness	91	76	11	1	3.4
Technical support:					
Trouble-shooting	50	94	32	4	3.1
Education	43	108	28	1	3.1
Documentation	36	103	32	10	2.9
Manufacturers software:					
Operating system	98	74	8	1	3.5
Compiler & assemblers	79	87	13	1	3.4
Application programs	27	83	22	3	3.0
Ease of programming	70	92	11	3	3.3
Ease of conversion	59	66	20	4	3.2
Overall satisfaction	91	85	4	2	3.5

*Weighted Average on a scale of 4.0 for Excellent.

➤ Each system can support both the HP 7970E 1600 bpi drive and the HP 7976A 1600/6250 drive. The Series 39 and 42 systems can have a maximum of four tape drives with two HP 7976s allowed. The Series 48 and 68 each handle up to eight magnetic tape drives with two HP 7976s supported on both the Series 48 and the Series 68. The magnetic tape drives interface through the GIC.

PRINTERS: The HP 3000 supports up to two printers on the Series 39 and 42, four printers on the Series 48, and eight printers on the Series 68. Each HP 3000 system also supports a maximum of two 2680A Intelligent Page Printers. All printers interface through the GIC.

COMMUNICATIONS: The maximum synchronous communication lines supported for each of the four HP 3000 Series is as follows: Series 39—three lines, Series 42—three lines, Series 48—seven lines, and Series 68—24 lines.

MASS STORAGE

Refer to CHART B.

INPUT/OUTPUT UNITS

Refer to CHART C for terminals, CHART D for printers and CHART E for magnetic tape units. Other peripherals supported on the HP 3000 Series are described below.

PLOTTERS: Hewlett-Packard's plotters offer a range of choices in paper size, pens and interfacing.

The *HP 7470A and HP 7475A Graphics Plotters* are desktop units utilizing 2-pen and 6-pen plotting, respectively and A-size paper (8½ x 11 inches). Multicolor plotting is possible on the 2-pen plotter by halting a program through front panel or program control, installing new pens and then resuming plotting. The two-pen plotter offers five character sets, while the six-pen plotter uses 19 character sets. A choice of two interface options is offered: RS-232-C/CCITT V.24 or HP-IB (IEEE 488-1978). With RS-232-C, a dual input/output cable is available allowing connection of the plotter to a terminal.

8-pen Plotters are offered in six models. Single sheet plotting is available in the C models and automatic paper advance is offered on the T models. These plotters use B-size paper (11 x 17 inches) and a choice of fiber tip or drafting pens.

Drafting Plotters utilize micro-grip technology to provide D/E size plots from a device only 42.8 inches wide by 21.9 inches deep. Features of these plotters include: six character sets contained in two fonts; 8-pen capability; three types of pens, fiber tip, drafting and roller ball; 0.003mm mechanical resolution; and D-size paper (24.5 x 48.5 inches) on the Model 7580B or E-size paper (36.5 x 48.5 inches) on the Model 7585B.

GRAPHICS TABLETS: *Model 9111A* is a self-contained unit offering single or continuous line mode, 16 softkeys and resolution to 0.100mm (.00394 inches). *Model 17623* is supported by the Model 2627A color graphics terminal or the Model 2623A monochrome graphics terminal. This tablet also offers single or continuous line mode and resolution to 0.100mm.

DATA COLLECTION TERMINALS: *Model 3075A* is a desktop data capture terminal supported in point-to-point or asynchronous multipoint configurations, with a 15 position numerical display, protected data fields, 17 user-defined prompting lights, and 10 special function keys. *Model 3076A* is a wall mount version of this same device with an inverted keyboard and display. Any two (but only one of each) of the following options are supported with either of these terminals: bar code reader, magnetic stripe reader,

Hewlett-Packard HP 3000 Series

► Four of the respondents were further interviewed to obtain additional comments on their experiences with the HP 3000. The first user interviewed represented an energy company in a Rocky Mountain state. The system has been installed since late 1981 and the user is very happy with it. Initial problems experienced with the system were aggravated by the fact that the system configuration proposed by the vendor was too small. HP corrected the problems however, at no extra cost to the user. According to the user, HP has been "very, very cooperative."

The second user, a manufacturer in the South, is "generally happy" with the system but considers the reliability of their HP 3000 only fair. Consequently, they feel the maintenance service received is only fair also.

The third user represented a service bureau in the Southwest that installed the system in late 1981. Although this company is over 100 miles from an HP office, they still feel that they receive "pretty good maintenance service." This service bureau has been using HP equipment for many years and think HP has "a good product—there is no question about the quality of the HP 3000."

Representing a retail business in the South, the fourth user installed the HP 3000 in the summer of 1982. This firm experienced many problems initially, but the user said HP has made "monumental strides" in solving these problems during the last 12 months. "They still have a way to go, but we are pleased with the system." The firm is planning to upgrade to a Series 68 sometime during 1984.

In summary, 172 of the respondents stated that the computer performed as expected, with only five claiming it did not (the other six were undecided). When asked if they would recommend the HP 3000 to another user, 174 said yes, three said no, and six were undecided. □

- multifunction reader (reads punched cards, marked cards and type III badges), Type V badge reader, printer, serial I/O card or HP-IB card.

Model 3077A is a time and attendance terminal with an internal clock and a time display for mounting on a wall. A Type V badge reader is standard; options include a multifunction reader or magnetic stripe reader.

COMMUNICATIONS CONTROL

DSN/ASYNCHRONOUS DATA COMMUNICATIONS CONTROLLER (ADCC): The ADCC is used in the Series 39, 42, and 48 to provide direct connect and modem connections for terminals or as an alternate way to direct connect terminals. One ADCC is required to connect the Control and Maintenance Processor. The channel performs for terminals essentially the same functions as the GIC. Data is transferred from memory to the ADCC in parallel form and then is converted to a serial bit stream for transmission over RS-232-C lines.

The ADCC does not have DMA facilities and so cannot control the IMB or memory. Terminals on the ADCC do not respond to a parallel poll. The ADCC must be directly controlled by the CPU through channel programs. Circuitry on the ADCC decodes address information and selects the proper device for each operation. Four full-duplex ports are

provided on each Main ADCC, the Extender ADCC boards increase the capacity to eight full-duplex ports. Multiple ADCC are supported on each system but, as the Main ADCC includes specific control circuitry, each Extender ADCC requires a Main ADCC to function. The Main ADCC supports full duplex operation only via Bell type 103, 212, and 202T modems; Extender ADCCs are required for European half-duplex support.

DSN/ADVANCED TERMINAL PROCESSOR (ATP): The ATP provides an intelligent interface between terminals and the CPU for the Series 48 and 68 systems. The ATP supports data transfer rates up to 19,200 bits per second, handles character processing to eliminate CPU interrupts, and provides direct memory access of user data. RS-232-C and RS-422 support is provided for local terminal hook-ups, with distances to 50 or 4000 feet respectively. The Series 68 ATP adds full-duplex asynchronous modem support (Bell type 103, 202T, 212A, and CCITT V.24) to the list of features.

An ATP is composed of one System Interface Board (SIB) and supports up to eight port controllers. The SIB provides a hardware interface to the Intermodule Bus (IMB) and performs byte packing/unpacking and direct memory access of user data. Port Controllers provide the hardware interface to the terminal/workstation devices. The Port Controller handles all handshaking between the system and the terminal, all character echoing, speed sensing, and input character buffering. The ATP supports character or block transmission.

CLUSTER CONTROLLER: The cluster controller allows from four to 16 RS-232-C computer peripherals to communicate with one or two HP 3000s. When two computers are connected, any device in the cluster can address or be addressed by either computer. Also, the two lines can be used for redundant connections to a single computer to prevent line loss. Speed of transmission from the cluster controller to the system is up to 19,000 bits per second (bps). Speed of transmission from the controller to the peripherals is up to 9600 bps. The cluster controller combined with enhanced HP 3000 DSN/Multipoint terminal software provides error-checking and retransmission of data if errors are found.

INTELLIGENT NETWORK PROCESSOR (INP): The INP allows HP 3000 computers to be linked to other computers in a distributed data processing environment and to support multipoint terminals. The INP uses a 16-bit silicon-on-sapphire (SOS) microprocessor to perform all of the data link protocol support, including serialization, protocol management, frame/block management, and data buffering, effectively reducing CPU utilization to free it for other tasks. The INP provides direct memory access for data. Data rates are up to 19,200 bps using modems or up to 56,000 bps hardwired.

Throughput is increased by overlapping data transfer with data processing and buffering from the communications channel. The protocol driver may be dynamically changed to allow the INP to be reconfigured from one data link protocol to another. This allows several subsystems to use a single INP. The INP is Bisync and HDLC/SDLC protocol compatible. RS-232-C, RS-422, CCITT V.24 and V.35 interfacing is available, as is full- and half-duplex asynchronous modem support. An autocal capability allows dial-up remote connections to be completed without human intervention.

DSN/DATA LINK: The Data Link is a data communications capability used to interface an HP 3000 (the primary station) and several widely distributed devices (the secondary stations). Terminals are connected in parallel and can be connected anywhere along the same link, with no restriction ►

Hewlett-Packard HP 3000 Series

► on the distance between terminals, at up to 2.5 miles (4000 meters) from the computer. The use of floating, differential signal lines (balanced voltages) and optical isolators in the link drivers/receivers ensures a high level of noise immunity and enables the DSN/Data Link to be operated in electrically noisy environments. The HP 3000 and all devices on the link communicate at the same speed. Thus the data transmission rate is set by the slowest device on the link.

FIBER OPTIC MULTIPLEXER: The Fiber Optic Multiplexer, connected with fiber optic cable, allows the interconnection of a remote cluster of up to eight RS-232-C devices at distances up to 3280 feet (1000 meters). Each of eight full channels can accommodate asynchronous data at rates up to 9600 bps. The multiplexer is compatible with all HP 3000 family point-to-point EIA RS-232-C/CCITT V.24 interfaces. Any HP 3000 supported point-to-point EIA RS-232-C/CCITT V.24 terminal, printer or plotter device may be connected to the multiplexer.

DSN/ADVANCED TERMINAL PROCESSOR: The Advanced Terminal Processor has been added to accommodate installation of junction panels on the Add-on I/O bay for the Series 68.

DSN/PBX: The PBX data communications interface provides HP 3000 systems with the opportunity to utilize their PBX telephone systems for data transmission between the host HP 3000 and HP terminals and personal computers. The PBX manufacturers that have data communications capability and are certified for connection to HP computer systems are: Northern Telecom's SL-1 PABX line, ROLM Corp.'s CBX line, and InteCom's S/40 IBX. HP does not supply the PBX equipment needed to interface with the HP 3000. And while HP guarantees the proper operation of HP systems and applications, support for the actual PBX and its associated equipment remains the responsibility of the customer and its PBX supplier.

DSN/X.25 CLUSTER CONTROLLER: The X.25 Cluster Controller is designed to connect asynchronous devices to an X.25 Packet Switched Network (PSN). It permits up to 16 terminals and printers to communicate with a host computer system (HP 3000, HP 1000 or non-HP). The Cluster Controller uses a four-port interface card which supports asynchronous RS-232-C point-to-point devices at up to 9600 bps full duplex. Up to four terminal interface cards (with no modem control) can be installed in the controller, allowing up to 16 terminals to be connected.

The Cluster Controller supports the November 1980 version of CCITT X.3/X.28/X.29 recommendations which allow the controller to act as a private Packet Assembler Disassembler (PAD). The standard 18 parameters defined in the X.3 recommendation are supported, plus additional HP defined local parameters are available for enhanced functionality with HP devices.

SOFTWARE

OPERATING SYSTEM: The Multiprogramming Executive (MPE) operating system enables the HP 3000 to perform transaction processing, on-line program development, data communications and batch processing concurrently. System resources can be accessed simultaneously by multiple users. An on-line HELP facility guides the user through the MPE command set. MPE monitors and controls program input, compilation, execution, and output, arranges the order in which programs are executed and dynamically allocates hardware and software resources as required.

The major components of the MPE operating system are: Configurator, Initiator, System Console Manager, Command Interpreter, File Management System, Input/Output System, Virtual Memory Manager, Disk Space Manager,

Disk Cache Manager, Private Volumes Facility, Serial Disk Interface, Tape Labels Facility, Spooling Facility, Job/Session Scheduler, Process Dispatcher, Segmenter, Loader, User Trap Manager, Utility Intrinsic, Accounting Facility, Logging Facility, Backup/Restore Facility, and Power Fail/Auto Restart. Support is provided for Basic, Cobol II, Fortran, Pascal, RPG, and SPL (Systems Programming Language).

According to HP, the latest version of the MPE operating system provides a marked improvement in performance over earlier MPE systems. In addition, internal system data structure expansions now support up to 400 concurrent sessions. Virtual memory can be spread across multiple system domain disks so that more and larger applications can run simultaneously on one system. This reduces I/O contention on the system domain disk and improves system I/O performance. The disk caching facility further improves I/O performance by using excess main memory to buffer reads and writes to disk subsystems. Internal file system management has been enhanced to make internal control block handling more efficient and all changes to the file system are transparent to the user. The dispatcher-scheduler gives users more control over system workload. Disk access is queued on a priority basis to insure better access to disk and memory resources. A TUNE command allows users to filter out long transactions, such as batch operations, to improve on-line performance during periods of heavy interactive load.

Under virtual memory allocation, each program can be segmented into as many as 63 segments. Each code segment can be up to 32K bytes in length, and each data segment up to 64K bytes. The principle of memory allocation dictates that only the essential segments be in memory at any particular time. Program execution for a particular user (called a process by HP) then proceeds until additional segments are needed. The operating system remembers all segments brought into memory under a concept called segment trapping. The goal is to keep as much as possible of a program's working set—the code, data, and system data segments used most recently—in memory. This is accomplished by the use of an HP-developed algorithm called the segment trap frequency algorithm. The algorithm remembers the frequency of use of each segment of each working set and overlays only the least-used segment of a low-priority work set.

Features also include a local compression algorithm, memory allocation manager, and program dispatcher. The local compression algorithm functions to keep user segments tight together by executing large block moves within memory whenever necessary so that the need for frequent overlays is reduced. The memory allocation manager uses the segment trap frequency and local compression algorithms to optimize system throughput as much as possible. The program dispatcher schedules processes for execution by using an algorithm which handles three concurrently existing queues, the new crystal process clock, and instruction set enhancements for privileged operations.

Disk Caching manages retrieval and replacement of disk "domains" in excess main memory. It locates and replaces these disk domains so that a significant portion of the references to disk storage can be resolved before actually having to physically access the disk. Disk Caching policies are integrated into the MPE kernel, file system, and I/O system. The operator will be able to use external commands to activate and deactivate caching on a disk by disk basis and to display general caching statistics.

Disk Caching will use the MPE Kernel resource management mechanisms and strategies. These mechanisms are extended to handle cached disk "domains" in the same manner as segments. These cached disk domains can be of ►

Hewlett-Packard HP 3000 Series

▶ variable size, fetched in parallel with other segments or cached domains, garbage collected, and replaced in the same strategies as stacks, data segments, and code segments. The relative use of main memory between stacks, data and code segments, and cached disk domain objects is dynamic.

The MPE file system is a collection of routines in the system segmented library (SL). A user may open a file, obtain status information, read or write data, perform control functions, and close the file. File security is provided either through the use of passwords to limit access or through file access modes and user restrictions. File access modes are: Reading, Appending, Writing, Executing, Locking, or Save Files. User types are: Any user, Account member, Account Librarian, Group users, Group Librarian, and Creator. This combination allows files to be controlled at several levels ranging from unrestricted access to file access limited to its creator only.

Under MPE, all I/O is handled by the file system; thus, programs are essentially device-independent. The IOP allows for file manipulation without extensive JCL. In any access mode, whether sequential or direct, security is maintained for users, groups, accounts, and individual files.

The MPE Accounting Facility insures that information such as CPU time, connect time, and disk file space is kept by user, group, and account. A REPORT command allows extraction of this information for each log-on group.

Other features of MPE include utilization of the machine's hardware-implemented stack architecture, recursive/reentrant code, spooling from both terminal and batch devices, and remote processing via terminals.

Recommended disk space allocation for MPE, the subsystems, and virtual memory is somewhat over seven million bytes. MPE is disk-resident, with less than one percent (approximately 50K bytes) resident in memory at any one time.

DATA BASE MANAGEMENT SYSTEM: IMAGE/3000, the data base management system for the HP 3000 Series, is oriented toward general purpose data base management and operates in both interactive and batch environments.

IMAGE consists of three parts: a data base definition subsystem (DBDS), a data base management subsystem (DBMS), and a data base utility subsystem (DBUS). Typically, a data base manager would use DBDS to define the data base and DBUS to create and maintain the data base. The applications programmer, in writing his/her programs, would use the data base management language (DBML), which operates on the data base using DBMS.

IMAGE uses a network data structure as its data base organization. Data entry selection is made utilizing one of four access methods: serial, chained, directed, and calculated.

In serial access, IMAGE starts at the most recently accessed data record and searches all adjacent records sequentially until the desired entry (if it exists) is found. In directed access, the calling program specifies the record address of the data entry where the requested data items should be located. In calculated access, master entries are retrieved by calculating an address based on a key.

In chained access, entries having a common search item (key) value are linked together through pointers forming a doubly linked chain. A doubly-linked chain allows for fast forward and backward searches. Access to data is accomplished by identifying the proper chain and searching the chain until the desired entry (if it exists) is found.

Security is provided at the data base, data set, and data item levels using a class type scheme with 63 levels. The scheme is such that a user with a level 10 security does not have access to level 9 data.

Eight different access modes are available for IMAGE users. Multiple users may access a data base concurrently. Restructuring of the data base is accomplished by using DBUS. The restructuring can be through a changed data item or data set name, changed security provisions, changed data set relationships, and increased data set capacities. Inverted data sets are not supported.

Limiting parameters for IMAGE/3000 include the following. In each data base there can be a maximum of 255 data item names and 99 data sets; a single set cannot exceed the capacity of a disk drive. There may be up to 16 characters per item or data set name. In each data entry there may be up to 127 data items. The maximum size of a data entry is 4094 bytes. A maximum of 16 keys per detail data set and 16 detail data sets per master data set is permitted. Each chain may have up to 65,535 entries. Up to 16 different pointer pairs can be maintained for each data item; this permits each data item to be a member of 16 different chains or access paths. There may be six characters per data base name, eight characters per password, and 8,388,607 entries per data set.

IMAGE allows 32 data extents; the capability for data sets to cross volume boundaries; the intrinsic DBEXPLAIN, which explains the result of a CALL to the data base; and the intrinsic DBERROR, which supplies an English-language message for an error code.

QUERY/3000 uses such commands as FIND, REPORT, and UPDATE to locate, report, and update values in an IMAGE/3000 data base. Reporting of retrieved data can be formatted to include page titles, column headings, group subtotals, etc., if desired. All security provisions invoked through IMAGE are adhered to in QUERY. A command file can be utilized to store complex or often-used command sets on disk. For display purposes, nine data types may be converted and error-checked.

For the HP 3000 Series, QUERY/3000 has been enhanced with computation power for crossfooting. Ten registers have been implemented for this purpose, using GROUP and TOTAL.

KSAM/3000: The Keyed Sequential Access Method subsystem extends the file system by allowing files to have one primary and up to 15 alternate keys, with retrieval based on the value of the data. KSAM also supports key access by physical or logical record numbers or by chronological order.

LANGUAGES: All of the HP 3000 computers are multilingual systems that support six programming languages plus a data base management system. All implemented languages have the ability to call a subroutine written in another language. Of equal importance is the facility provided by the file system for all languages to utilize a common file structure, therefore, providing uniform access to disk and tape.

Basic is implemented as an interpreter and a compiler. The interpreter offers an effective way to debug programs interactively, while the compiler yields more efficient code with average program execution speeds 10 to 30 times faster for CPU-bound programs and one to four times faster for I/O-bound programs. Four numeric data types are possible: real, integer, complex, and extended precision.

Basic also provides the following HP extensions. Mixed-mode arithmetic and program chaining with common storage are provided, along with a built-in debugging system. ▶

Hewlett-Packard HP 3000 Series

► External routine calls, strings, and string arrays, and multiple-line statements and functions are all permitted. Picture output formats can be implemented, and the programmer can use timed input by way of the ENTER statement. Both direct and sequential access to files are allowed. File creation and purging are under program control, while file security is user-definable with passwords.

Cobol II is the primary commercial language for the HP 3000s. Cobol II conforms to the Level-2 implementation (except the RERUN option for I/O) of nine of the 12 modules defined by the ANSI Cobol X3.23-1974 specifications. The nine modules, all implemented at the highest level, are Nucleus, Table Handling, Sequential I/O, Relative I/O, Indexed I/O, SORT-MERGE, Segmentation, Library, and Inter-program Communication.

Language extensions implemented by HP include microcoded instructions, pre-processor functions (provides statements which allow the programmer to equate a particular section of code or a file to an identifier), program debugging aids, access to subprograms, access to all MPE System Intrinsic, ACCEPT FREE option (allows a free format for low-volume data entry), file locking capability, special registers, packed decimal, and multiple entry points to subprograms. Cobol II provides access to both sequential MPE and indexed sequential (KSAM) files through the use of ANSI Standard Cobol Input and Output operations and to IMAGE/3000, HP's data base management package, through the use of procedure libraries.

Fortran is based on American National Standard Fortran, X3.9-1966, and is a full implementation of that standard. Described below are some of the Fortran language extensions implemented by HP.

Source programs may be written in a free-field as well as in a fixed-field format. Symbolic names may consist of up to 15 characters instead of the usual six. Character type data may be used to facilitate string manipulation. Up to 99 files may be used during execution of a Fortran program. Arrays may have up to 255 dimensions instead of the standard three. A label may be used as an actual argument in a CALL statement to allow alternative return points following execution of the subroutine referenced by CALL. Support is provided for user-written error-handling routines called in trap conditions, and a parameter statement is available for giving constants symbolic names. Seven data types can be processed: integer, double integer, logical, real, double precision, complex, and character. Subroutines and functions may have secondary entry points. A built-in cross-reference facility is available as a compile-time option. Undefined variables are detected at compute time, and generic functions are recognized.

Pascal/3000 is an implementation of the Hewlett-Packard Standard Pascal, which is in turn a superset of the ANSI/IEEE 770 X3.97-1983 specification.

HP Standard Pascal, which was defined to provide portability between HP computer systems, includes extensions such as a string data type and associated string functions and procedures, direct access I/O, structured constants, and the ability to read and write enumerated types. Implementations of HP Standard Pascal are available on the HP 1000, HP 9000, HP 9826, and HP 9836.

Pascal/3000 also includes extensions beyond the HP Standard Pascal to allow calls to HP 3000 subsystems such as IMAGE/3000, and VPLUS/3000, to HP 3000 system intrinsic, and to external procedures written in Fortran, Cobol or SPL, as well as Pascal. The compiler has numerous compiler options which include flagging all extensions beyond the ANSI standard or the HP Standard. It also supports separate compilation of sources; debugging aids

such as a cross reference facility, load maps, mnemonic code listings and break point information; and optimization of storage and arithmetic.

RPG is compatible to a high degree with RPG and RPG II as developed by IBM. Language extensions implemented by HP include parameters for external subroutine calls, an interface to the data base management system, three methods for run-time error options, a cross-reference error option, EBCDIC/ASCII automatic translation, input/output terminal files, and no requirements for calculation indicator repetition for duplicate conditioning indicators. Data can be processed in binary, packed and unpacked decimal, unpacked decimal with leading or trailing sign, and alphanumeric formats. RPG/3000 also provides automatic 2K- to 8K-byte program segmentation for a virtually unlimited-size RPG program.

SPL is the Systems Programming Language for the HP 3000 Series. It is ALGOL-like, but is machine-dependent (direct register references, bit extraction, etc). It supports one-dimensional arrays and CALLs from any other language available to the system. SPL is free-form in structure and includes other features such as recursive procedures, high-level statements with unlimited nesting, and arithmetic and logical expressions. HP states that MPE and all compilers are written in SPL.

COMMUNICATIONS: The Distributed Systems Network (DSN) software provides capabilities in three broad areas: 1) workstation to HP system communication, 2) HP system to HP system communications, and 3) HP system to IBM mainframe communications.

Each HP 3000 system can support point-to-point terminal capabilities. The DSN/Multipoint Terminal Software (DSN/MTS) provides half-duplex data transmission over a single communications line between an HP 3000 system and up to 32 multidropped terminals. In both interactive and page modes, data can be entered, edited, and transmitted at up to 9600 bps.

DSN/DISTRIBUTED SYSTEMS (DSN/DS) is a communications facility that makes it possible to interconnect HP 3000 Series computer systems in distributed processing networks. The DSN/DS software allows multiple interactive or batch users of a 3000 Series system to communicate concurrently with a remote 3000 Series system in a full multiprogramming environment. According to HP, network operation with DSN/DS makes remote processing as easy as processing on a local 3000; the only special programming needed to interact with a remote processor is the placement of a single word in some commands.

Although multiple users can share the same communications line, one user can command exclusive use of the line when necessary for increased volume of data transfer. A variety of processes can be in progress at the same time, including local and remote batch operations, local and remote transaction processing, interactive problem solving, remote job entry, and intersystem program-to-program communication. One HP 3000 can store, modify, or retrieve data in IMAGE/3000 data bases in other 3000s in the network. The HP file copier can be used to copy whole files from one system to another.

HP states that when existing 3000 Series computers are networked with DSN/DN, the user's investment in application software will be protected. Similarly, DSN/DS has been implemented with a "layered" architecture, with the intent that user-created software shall not be affected by future changes that may occur in communications link protocols or in electrical interfaces. A network accounting structure and file security measures provide protection against unauthorized use, and multilevel security schemes can be implemented. ►

Hewlett-Packard HP 3000 Series

► DSN/DS offers remote command processing, remote file access, program-to-program communications through the use of nine intrinsics, virtual terminal capability (terminals physically connected to one system operate logically as if they were connected to one another), simultaneous local and remote processing, remote data base access, intersystem data transfer, bidirectional interleaving of applications from either end of the communications line, and peripheral sharing.

HP has also implemented distributed system software on the HP 1000, thus allowing these systems to become a part of an intercomputer communications network. For example, an HP 1000 system supports its own interactive terminals, which then can also function as terminals to any HP 3000 in the network.

The 37230A Short Haul Modem provides synchronous transmission of data at rates of 2.4K, 4.8K, 9.6K, and 19.2K bps over short distances (from four to 22 miles) and is designed for half-duplex, full-duplex, and operation over local circuits. Using intelligent microprocessor-based interface cards, line speeds of up to 56,000 bps can be achieved over RS-449 direct connections or RS-232-C connections to common carriers. DSN/DS supports connections via either switched or leased lines, X.25 Public Data Networks, or Digital Dataphone service.

DSN/RJE and DSN/MRJE: Both DSN/Remote Job Entry (RJE) and DSN/Multileaving RJE (MRJE) are software subsystems that provide a means for 3000 users to submit batch jobs to, or receive output from, an IBM or IBM plug-compatible host mainframe.

- DSN/RJE is compatible with host systems that support standard 2780/3780 devices.
- DSN/MRJE is compatible with hosts that support HASPII, ASP, JES2 or JES3 job entry systems.

DSN/IMF: DSN/Interactive Mainframe Facility (IMF) allows programs on the HP 3000 to access host program products such as CILS, IMS, CMS and TSO through a set of 21 high-level intrinsics. In addition, user terminals connected to the HP 3000 may use DSN/IMF to send and receive data to the host. DSN/IMF supports both BSC and SDLC protocols.

UTILITIES: Several major utilities are included with each HP 3000.

Edit/3000 is the HP text editor used to create, manipulate, and store files of upper and lower case alphanumerics in the form of lines, strings, or individual characters. *Sort-Merge/3000* allows the user to order records in a file and merge sorted files. *FCopy/3000* performs general file copying tasks.

VPLUS/3000 is a data entry and forms management software product to help users implement straight forward interactive data entry tasks and to facilitate development of more complex applications through the use of a high-level program interface. *VPLUS/3000* may be used as a stand-alone source data entry facility or as a front-end to transaction processing applications. Features include a Forms Design Facility, a Source Data Entry Facility, a Data Reformatting Facility, and a Program Interface.

The *Text and Document Processor/3000 (TDP/3000)* is a text editing and document formatting system. Its features include text editing, document formatting, mathematical expression handling, table creation, built-in calculator, command files, form letters, automatic hyphenation, security, and MPE command execution. The only other software required is the MPE operating system. Certain MPE commands can be executed without exiting TDP/3000.

The *On-Line Performance Tool/3000 (OPT/3000)* is an interactive performance measurement package for the system analyst. The user can isolate bottlenecks and improve performance by tracking CPU utilization, memory management activity, I/O traffic, program and process activity, and system table usage. Performance data is regularly updated and may be presented in the form of charts, graphic displays, or summary reports. HP offers a System Performance Training Course to teach users how to use the performance related data from OPT/3000. This training is required for each initial OPT/3000 installation.

Flexible Diskcopy/3000 allows conversion of IBM 3741 format flexible disk data set files to HP 3000 disk files while translating EBCDIC code to ASCII. It can operate in either an interactive environment or in batch mode, and can convert either single or multiple data sets and volumes. A complete error, warning, and status message file is included to provide the user messages about program status, user prompts, and error conditions.

PROGRAMMING AIDS: HP offers the following programming aids—RAPID/3000, HP Toolset, and APS/3000 Application Program Sampler. RAPID/3000 is a family of software programming tools consisting of four individual but integrated products. These are Dictionary/3000, Transact/3000, Report/3000, and Inform/3000. HP states that improvements of two to 10 times in programming speed have been demonstrated with RAPID/3000.

Dictionary/3000 is a relational data dictionary and data directory facility to control and coordinate all HP data files. The data dictionary consists of an IMAGE data base, a high-level user interface, and maintenance utilities. The dictionary contains information about a company's data processing and user environment. This includes data definitions, data structures, files, programs, security rules, and locations. The user-world is separated from the system environment with relational user views of the data. The data dictionary interface, in interactive mode, accepts commands and then prompts the user through entry, update, deletion, and reporting operations. Minimum memory required for the dictionary is 256K bytes, although the customer's actual job mix may necessitate more. Both character and block mode terminals are supported.

Transact/3000 is a high-level programming language specifically designed for transaction processing; one Transact/3000 instruction is equal to many instructions in a traditional language. The ability to do prototyping is also an inherent part of the product. Transact/3000 is designed to work in conjunction with HP's system-wide data dictionary, Dictionary/3000. Together with Dictionary/3000, Transact/3000 speeds up the development of applications and reduces maintenance costs.

Transact/3000 is designed to provide a balance between a high-level language and control of the operating environment (something most high-level languages require the user to forego). Programmers are not forced to give up the control they need to do an effective job. The user has a range of options, from using all the defaults that are built into Transact/3000 up to specifically controlling the run-time environment.

Report/3000 is a command driven, non-procedural report writer for use with HP Dictionary/3000. Report/3000 provides extensive layout, heading and editing capabilities. Since Report/3000 operates with Dictionary/3000, programmers are freed from data definitions and physical structure when accessing data for reporting. The dictionary provides for element resolution, definition and physical access. Access is available for IMAGE, KSAM and MPE sequential files through the data dictionary, with only specification of the element name. Report/3000 is self-contained, no procedure calls are required and no intrinsic calls need to

Hewlett-Packard HP 3000 Series

► be made for report generation. Quick reports can be generated utilizing the default headings and edit masks in conjunction with prompts from the system. More complex reports cover the entire range of formatting.

HP Inform/3000 is an interactive inquiry and report generator for nonprogrammers. A series of menus guide the user through the specification process. The more experienced user can bypass lower-level menus by stacking responses. With proper passwords the user can access logically related groups of data through *Dictionary/3000*. The user selects the individual data elements to be included in the report; *Inform/3000* formats the report with no user specification required. Detail information including subtotals, grand totals, break-points and sort order are user specified. Reports can be displayed on the terminal or sent to the line printer. Commands can be stored for future execution.

HPToolset is a productivity aid which includes a workspace manager, a full-screen editor, and HP Cobol II symbolic debugging. This combination eliminates the need to manage files while promoting an information sharing environment for programmers. The workspace manager manages all source files, versions of source files, INCLUDE files, USL files, and program files and listings. Since source files may be shared, individual and team programming efforts are simplified. The full-screen editor provides direct editing of text to simplify source-code entry and modifications. The Cobol II interface program key set consists of function keys which permit the user to compile, prepare, and run programs. The Cobol II symbolic debug locates run-time errors by using actual program variable and paragraph names rather than primitive-level memory locations and code addresses. The programmer can set breakpoints, trace/retrace execution, and display and modify data-item values.

The *APS/3000 Application Program Sampler* identifies procedures consuming a large proportion of CPU time. On-line histograms display CPU time spent directly in user code or indirectly in system services. Samples may be stored onto a disk file for later analysis. The *APS/3000* typically uses two to three percent of the available CPU time as overhead when using the default sampling rate. The sampling rate is adjustable by the user. The samples can be run on any HP terminal supported by an HP 3000 system using a current MPE IV operating system.

OFFICE AUTOMATION: The Office Systems products include several classes of products: document management, decision support, and organizational communications.

HPWord is HP's full-feature word processor for general business needs such as memos, lists, and reports. The large disk storage capabilities provide for more than a million pages of *HPWord* documents to be stored on-line. *HPWord* uses the 2626W Word Processing Station with its internal microprocessor and 128K-byte memory. Editing commands are entered through specially-labeled keys; additional functions are added via the screen-labeled keys. The 2626W is a full-function, multi-screen intelligent data-entry station when not being used in *HPWord* applications.

HPsLlate is a commandless, text processor with a menu-driven set of functions used to enter, format, revise, print, and save shorter documents. It is intended for use by professionals who occasionally need such features. *HPsLlate* utilizes screen-labeled function keys to perform the various editing tasks.

HPDeskmanager operates from any terminal connected to an HP 3000. Working within HP's DSN capabilities, *HPDeskmanager* manages to provide electronic mail, electronic filing of mail, word processing for composing memos, and an electronic time and calendar manager. Users only specify the name of their intended recipient; actual routing

paths are invisible to the user. A general delivery feature provides a way to route messages to a number of locations for manual distribution.

HPDeskmanager includes a HELP facility to quickly answer any questions. If a sender requests acknowledgement of a message, it is sent automatically after the message is read. Users can send messages to offices that are closed, the electronic In Tray continues to receive messages for delivery as soon as the recipient signs on. An Out Tray and Pending Tray function is also provided. Other features include:

- **Work Areas**—allows composing and editing of longer messages and for assembling packages of information files including graphics.
- **File Cabinet**—stores messages and documents.
- **Distribution directory**—provides the ability to construct, use, and store standard distribution lists.
- **Administrative Area**—allows the user to tailor the *HPDeskmanager* environment with passwords, auto forward instructions, auto-answer messages, and the choice of an alternate to handle mail on a user's behalf.

To reduce on-line storage requirements, *HPDeskmanager* uses the *IMAGE/3000* data base for document storage and local distribution. Documents are stored only once on each system in a network, with pointers for each intended recipient.

The *Text and Document Processor/3000 (TDP)/3000* has extensive formatting features used in the creation of manuals, contracts, and lengthy proposals.

APPLICATIONS SOFTWARE: HP's application software is grouped into several major categories: manufacturing, distribution, administration, as well as HP Plus for third-party software.

The products included in the manufacturing area are the *Materials Management/3000* and *Production Management/3000*. Each is an interactive system that can work separately or together, on single systems or distributed networks. *Materials Management/3000* allows the user to manage materials planning and control functions for a manufacturing operation. *Production Management/3000* adds production planning and control. Each consists of software modules using the techniques of Material Requirements Planning (MRP) and Capacity Requirements Planning (CRP).

Materials Management/3000 includes the following modules:

- Master Production Scheduling
- Rough Cut Resource Planning
- Parts and Bills of Materials
- Routings and Wordcenters
- Material Issues and Receipts
- Inventory Balance Management
- Work Order Control
- Purchase Order Tracking
- Material Requirements Planning
- Standard Product Costing

Production Management/3000 includes these modules:

- Routing and Workcenters
- Work In-Process Control
- Work Order Scheduling
- Shop Floor Dispatching
- Work Order Tracking
- Capacity Requirements Planning

Hewlett-Packard HP 3000 Series

▶ HP's manufacturing packages provide a customizable user interface and data base. Menus, data entry and retrieval screens, hard-copy reports; and IMAGE/3000 data base are all available for user's modifications. Query/3000 may be used to meet the need for adhoc reports. HP states that these applications packages are designed for manufacturers who build in batches or lots with a variety of products and processes. HP offers full support and training for their manufacturing application software.

SFD/3000 (System for Distributors) and OM/3000 (Order Management) are HP's two products for wholesale distribution. The SFD/3000 application software consists of the following modules:

- Sales Order Processing
- Purchase Order Processing
- Inventory Control
- Sales Analysis
- Accounts Receivable
- Accounts Payable
- General Ledger

The OM/3000 package is a subset of SFD/3000 geared specifically toward sales. OM/3000 consists of the following modules:

- Sales Order Processing
- Inventory Control
- Sales Analysis
- Accounts Receivable

HP Financial Accounting is an on-line, interactive, totally integrated software package comprised of the following eight modules:

- General Ledger
- Accounts Payable
- Accounts Receivable
- Dual Ledger
- Allocator
- Report Facility
- Interface Facility
- General Accounting

The *Scientific Library* is a collection of routines that perform the most often-used scientific functions. The routines may be utilized by all implemented languages except RPG.

SIS/3000 (Student Information System) and CIS/3000 (College Information System) are two software packages that handle either school or college data via an integrated data base. The packages handle such area as grading, attendance, and registration.

A *General Accounting/3000* software system includes three standard programs: General Ledger, Accounts Payable, and Accounts Receivable. Each module may be used separately or together as an integrated system. These packages link with the Materials Management/3000 software to provide increased capabilities for the manufacturer.

The *HP Decision Support Graphics/3000 (DSG/3000)* is an interactive graphics software package which allows non-technical users to create and save fully-annotated line graphs, horizontal and vertical bar charts, pie charts, and scattergrams. The package includes a set of high-level procedure calls that can be used by any of the HP 3000 languages. Access is menu-driven with screen prompts. Charts created DSG/3000 can be displayed on the HP graphics terminal or printed on any of HP's digital plotters, plotter/printers, or graphics printer. An interactive option allows multicolor graphs.

HPMenu is a menu-building software facility that makes it easier for users to call up HP Interactive Office products. These products include word processing, electronic mail, graphics, and other applications. With HPMenu, users no longer need to type in operating-system commands. Instead, they can see the choices available, and make a selection by pressing screen-labeled function keys. Menu choices can include other menus in a tree structure.

The HP 3000 *Business Graphics Package* includes HPEasychart, HPDraw, and an enhanced Decision Support Graphics/3000 (DSG/3000). The entire package may be purchased at a discount, or individual products may be purchased separately.

HPEasychart is designed for office users to produce quick charts. Small examples of pie charts, bar charts, line charts, or scattergrams are displayed. Up to six variables, each with as many as 70 values, may be entered. Plotting is done at the press of the Draw button.

HPDraw provides presentation text and figure design multi-color output on paper and overhead-transparency slides. Users perform high-quality visual-aid design, production, and revision through the use of menus keyed to their appropriate experience level (beginner, regular, or expert). HPDraw provides a choice of fonts, basic geometric shapes, symbols, and simple figures.

Additional graphics software packages are *AUTO PLOT*, *WORD*, and *FORMS*. *AUTO PLOT* enables users to produce pie, bar, and linear charts and text slides. *WORD* allows users to perform text processing functions through a combination of menu and command keys. Page formatting offers automatic page breaks, footing, headings, and file merging. Included with *WORD* is *FORMS*, to design forms for data entry or documentation.

HP Plus is a marketing program which finds software written by independent software suppliers, qualifies the packages, and then merchandises them with the software suppliers. The HP Plus program currently offers 580 packages. Contact the local HP sales office for a current and complete listing of these packages.

PRICING

POLICY: The HP 3000 Series systems are available on a purchase or lease basis. The U.S. list price includes freight charges. Individual models are offered as a system processor unit, SPU (processor and selected software), with extensive separately priced peripheral and software options. Standard on each HP 3000 system is the Fundamental Operating Software which includes MPE-operating system, Edit/3000 text editor, FCopy/3000 file copying utility. Sort-Merge/3000, Image/3000 data base management system. Query/3000 data base inquiry language, KSAM/3000 keyed sequential access method, HP VPlus/3000 forms management software, and the facility to execute compiled programs without the source language compiler on the system.

Software products can also be purchased separately. Customers purchasing multiple copies of the same HP application software product are offered price reductions.

Refurbished, previously owned, earlier model HP 3000 systems can be purchased through HP's new System Re-Marketing Operation. User upgrades are one source of equipment for resale, as are lease returns and internal capital equipment. Re-market products are refurbished, warranted, installed, and supported as new equipment. Sales channels are the same as for new products, as are discount schedules. All software products are compatible with these systems.

Hewlett-Packard HP 3000 Series

- Standard lease rates can be calculated as percentages of the list (purchase) price payable per month for terms from three to five years and vary according to the type of lease.

The leases are noncancellable, but a special provision is available that permits cancellation on nine months' notice for an additional premium of 1.25 percent of the list price per month.

A purchase option provision is available throughout the duration of a lease; a substantial portion of the lease payments can be applied to the purchase price.

The HP 3000 is listed on the G.S.A. vendor list.

Most peripherals are also available for operation at 230 VAC, 50 Hertz. Users may specify this feature as option 015.

SUPPORT: Maintenance is separately priced and offered through 84 U.S. offices, 12 Canadian offices, and 121 international offices. Various service plans are available through HP.

Guaranteed Uptime Service provides a service credit guarantee that the uptime shall exceed 99 percent over any three consecutive months. If 99% uptime is not achieved, the user will receive a credit equal to one month's service charge. The service provides continuous coverage, four-hour response to all requests within 100-miles of an HP Primary Service Office. If this service is ordered prior to installation, it will be provided during the warranty period for no additional charge.

Standard System Maintenance Series (SSMS) provides same day reponse, typically within four hours of the request, at sites within 100 miles of a Primary Service Office. Nine different coverage periods are available: 13, 16, or 24 hours per day and 5, 6, or 7 days per week. Preventive maintenance is scheduled regularly. Site Environmental Surveys and installation services for new products are included at no extra charge under SSMS.

Basic System Maintenance Service (BSMS) provides the same features as SSMS but with a slower response time and a reduced cost. Next-day service is available for all sites within 100 miles of an HP Service Office.

HP also provides Product Support Services for workstation items, such as: terminals, small printers, and plotters. On-site service is available with next-day response for sites within the typical 100-mile service radius. Scheduled preventive maintenance for these products is either unnecessary or performed by the user.

An approximate 50 percent savings can be realized through the use of Field Repair Center (FRC) Service. This requires that defective units be shipped to the closest HP Repair Center Facility where HP will repair the units and reship them back to the user within three days of receipt. Customers with 25 or more workstations get a similar discount and may receive weekly scheduled visits to specified work areas, with repair being performed on-site.

The present software support policy for the HP 3000, which became effective in August 1979, contains the following qualifications:

- An HP-trained System Manager responsible for maintaining the integrity of the system's hardware and software or a trained designated alternate must be identified as a contact for HP.
- The same level of service must be purchased for all of the HP software products which make up one computer sys-

tem. Due to the interaction among software elements, service cannot be given to specific software products while omitting others.

- Additional phone-in service can be purchased as many times as desired. The name of a single authorized caller must be provided for each additional caller service purchased. Additional phone-in service cannot be purchased unless Customer Support Service (CSS) has been purchased.
- Central system CSS support of additional systems can be purchased only by customers with multiple installations. It cannot be purchased unless one of the installations has purchased Customer Support Service.
- A minimum of three months of support must be purchased.
- If twelve months of software support is ordered concurrently with the HP 3000 software, HP will provide an additional 90-day period of the services ordered at no charge.

All HP 3000 software products are discountable under Hewlett-Packard Computer Products Purchase Agreements. Software support services are not discountable.

Services that accompany software purchased under the support policy include phone-in consulting with an HP systems engineer (with an advertised four-hour response time) within a 100-mile radius of the HP sales office, software updates every three months, reference manual updates, software status bulletins every two weeks, and installation of software at the customer site. The phone-in consulting service may also be used for customer application bugs and interpretation of HP documentation. Software bulletins and updates also offer an avenue for interpretation of HP documentation.

Hewlett-Packard indicates that if a software product is discontinued from sale, support will continue for an additional five-year period. Thereafter, support will be provided on an as-available and time-and-material basis.

On-site consulting services by HP systems engineers are available to resolve software and documentation problems which cannot be solved using the phone-in service. If the problem reported is not associated with an HP software design error or system malfunction, the on-site services are considered outside the scope of HP's software and support agreement and subject to a time and materials charge. HP is not obligated to provide any on-site services for HP software products which the customer has modified. When on-site, the SE will help the customer to identify, verify, isolate, and work around problems caused by HP software. Assistance is available weekdays, excluding HP holidays, during HP working hours, at distances not more than 100 miles from the nearest HP office designated to provide on-site SE services. Support for facilities farther away can be provided at additional cost.

HP also offers emergency software support service for customers with problems occurring on weekends, holidays, and from 5 p.m. to 8 a.m. Monday through Friday. With this service, HP systems engineers are guaranteed to respond by telephone within 2 hours after receiving a customer's call. If the problem can't be handled over the phone, systems engineers will travel to the customer's site. Maximum response time for an on-site visit is based on the distance of the installation from the HP field office and the user's type of software coverage. Customers have three ways to purchase this service: separately, as an extension to HP's Customer Support Service (CSS), or on an as-needed basis.

For system discount purposes, each HP 3000 system counts as two to four Functional Units depending on the system. All ►

Hewlett-Packard HP 3000 Series

HP computer systems carry functional units and may be combined for discount purposes.

TRAINING: Training courses are available at an HP Technical Center at a per student charge or on-site classes at a per class charge (for up to 10 students). Typical classes are: Programmer's Introduction, Management and Operation, MPE Special Capabilities, HP VPLUS/3000, IMAGE/3000, Application Design, and IML/3000 Training/Consulting Package.

HP makes available, in advance of 3000 Series system shipments, a complete set of user manuals as part of the system.

The HP 3000 Users Group provides information interchange. The fee for membership is \$200 per year.

TYPICAL CONFIGURATIONS: Sample configurations for the HP 3000 follow:

Series 39:

3251B—System Processor Unit with 512K bytes memory, 2 GICs and Fundamental Operating Software (FOS)	\$33,200
7912P—65MB disk with integrated cartridge tape	17,350
2608S—400 lpm printer	11,170
2622A—3 block mode terminals	6,630
TOTAL	\$68,350

Series 42:

32542B—System Processor Unit with 1MB memory, 2 GICs, disk caching, and FOS	\$79,500
7925M—120MB disk	22,510
2611A—600 lpm printer	18,560
7974A—1600 bpi tape drive	12,500
2622A—6 block mode terminals	13,260
TOTAL	\$146,330

Series 68:

32468B—System Processor Unit with 3MB memory, 2 GICs, 1 IMB, disk caching and FOS	\$186,100
7933G—1.2 gigabyte disk subsystem	63,560
7976A—1600/6250 cpi Tape	44,440
2619A—1000 lpm printer	26,370
2622A—10 block mode terminals	22,100
TOTAL	\$342,570

EQUIPMENT: The HP 3000 computers are offered as system processor units, onto which the user configures the peripherals required by the application. Prices for each of the system processor units and peripherals will be found in the following Equipment Price list.

EQUIPMENT PRICING

		Purchase* Price	Standard Monthly Maint.
SYSTEM PROCESSOR UNITS			
3251B	HP 3000 Series 39 System Processor Unit; 120V/60 Hz; single phase; 512K bytes fault control memory; 2 General I/O Channels (GICs); remote diagnostic capability; system cabinet; Fundamental Operating Software FOS; complete user manual set	\$ 33,200	\$ 243
011	Model 11 Packaged System (requires Model 7911 disk drive to be ordered also)	-11,400	0
012	Model 12 Packaged System (requires Model 7912 disk drive to be ordered also)	-8,200	0
014	Model 14 Packaged System (requires Model 7914 disk drive to be ordered also)	-5,200	0
507	Expand memory to 1024K bytes	8,200	16
32542B	HP 3000 Series 42 System Processor Unit; 120V/60 Hz; single phase; 1 megabyte fault control memory; 2 General I/O Channels (GICs); remote diagnostic capability; disk caching; system cabinet; Fundamental Operating Software; complete user manual set	42,400	259
32548B	HP 3000 Series 48 System Processor Unit; 220-240V/60 Hz; single phase; 2 megabytes fault control memory; 2 General I/O Channels (GICs); remote diagnostic capability; disk caching; system cabinet; Fundamental Operating Software; complete user manual set	79,500	297
32468B	HP 3000 Series 68 System Processor Unit; 208V/60 Hz; three phase; 3 megabytes fault control memory; 1 Intermodule Bus (IMB); 2 General I/O Channels (GICs) remote diagnostic capability; disk caching; system cabinet; Fundamental Operating Software; complete user manual set	186,100	765
250	Add Expansion Bay and I/O Adapter (IMB)	25,000	53
30464A	HP 3000 Series 68A Expansion Bay and I/O Adapter (IMB)	30,000	74
30464B	HP 3000 Series 68B Expansion Bay and I/O Adapter (IMB)	30,000	53
35030A	Power Line Conditioner (Series 30, 39, 40 and 42)	1,100	6
FIELD UPGRADE PRODUCTS			
30539B	HP 3000 Series 39 Disk Cache Upgrade; includes disk caching software; 512K bytes memory; and MPE-V firmware	14,000	18
170	Delete 256K bytes memory	-4,500	-14
180	Delete 512K bytes memory	-6,000	-28
30400A	HP 3000 Series 39/4x Firmware Upgrade	4,000	0
30542B	HP 3000 Series 40 and 42 Field Upgrade; includes disk caching software; 1 megabyte memory; and MPE-V firmware	17,000	25
180	Delete 512K byte memory	-2,800	-16
190	Delete 1 megabyte memory	-8,000	-32
30548B	HP 3000 Series 44 to 48 Field Upgrade; includes disk caching software; 1 megabyte memory; and MPE-V firmware	20,000	25
190	Delete 1 megabyte memory	-8,000	-32
30468A	HP 3000 Series 64A to Series 68A Field Upgrade; includes disk caching software; 1 megabyte memory; and MPE-V firmware	25,000	75
190	Delete 1 megabyte memory	-8,000	-75
250	Add Expansion Bay and I/O Adapter (IMB)	25,000	53

*The U.S. list price includes freight charges.

Hewlett-Packard HP 3000 Series

EQUIPMENT PRICING

		Purchase*	Standard Monthly Maint.
		Price	Maint.
▶ 30468B	HP 3000 Series 64B to Series 68B Field Upgrade; includes disk caching software; 1 megabyte memory; and MPE-V firmware	\$ 25,000	\$ 75
190	Delete 1 megabyte memory	-8,000	-75
250	Add Expansion Bay and I/O Adapter (IMB)	25,000	53
UPGRADE PRODUCTS			
32445AH	Upgrade to the Series 40 (32445A) w/512K bytes memory	29,400	224
507	Expands Memory to 1024K bytes memory	8,200	16
601	Upgrade from pre-Series II or HP 2000 w/128K bytes memory	-2,500	0
602	Upgrade from Series II w/128K bytes memory	-3,000	0
603	Upgrade from Series III w/256K bytes memory	-7,000	0
605	Upgrade from S/33A/B w/256K bytes memory, 2649E	-8,000	46
606	Upgrade from S/33C/U w/256K bytes memory, 2649E	-8,000	26
607	Upgrade from S/30A/B w/256K bytes memory, 2649E	-6,000	23
608	Upgrade from S/30C/U w/256K bytes memory, 2649E	-6,000	13
32542BH	Upgrade to the Series 42 (32542A) w/1 megabyte memory	38,600	233
601	Upgrade from pre-Series II or HP 2000 w/128K bytes memory	-2,500	0
602	Upgrade from Series II w/128K bytes memory	-3,000	0
603	Upgrade from Series III w/256K bytes memory	-7,000	0
605	Upgrade from S/33A/B w/256K bytes memory, 2649E	-8,000	26
606	Upgrade from S/33C/U w/256K bytes memory, 2649E	-8,000	26
607	Upgrade from S/30A/B w/256K bytes memory, 2649E	-6,000	13
608	Upgrade from S/30C/U w/256K bytes memory, 2649E	-6,000	13
32440BH	Upgrade to Series 44B (32440B) w/1 megabyte memory	60,700	253
601	Upgrade from pre-Series II or HP 2000 w/128K bytes memory	-7,500	0
602	Upgrade from Series II w/128K bytes memory	-8,000	0
603	Upgrade from Series III w/256K bytes memory	-12,000	0
605	Upgrade from S/33A/B w/256K bytes memory, 2649E	-13,000	46
606	Upgrade from S/33C/U w/256K bytes memory, 2649E	-13,000	26
607	Upgrade from S/30A/B w/256K bytes memory, 2649E	-11,000	23
608	Upgrade from S/30C/U w/256K bytes memory, 2649E	-11,000	13
611	Upgrade from Series 40 w/no memory	-13,825	26
613	Upgrade from Series III w/256K bytes memory and 30341A HP-IB Adapter	-15,000	0
32548BH	Upgrade to Series 48 (32548A) w/2 megabytes memory	75,700	252
601	Upgrade from pre-Series II or HP 2000 w/128K bytes memory	-7,500	0
602	Upgrade from Series II w/128K bytes memory	-8,000	0
603	Upgrade from Series III w/256K bytes memory	-12,000	0
605	Upgrade from S/33A/B w/256K bytes memory, 2649E	-13,000	26
606	Upgrade from S/33C/U w/256K bytes memory, 2649E	-13,000	26
607	Upgrade from S/30A/B w/256K bytes memory, 2649E	-11,000	13
608	Upgrade from S/30C/U w/256K bytes memory, 2649E	-11,000	13
611	Upgrade from Series 40 w/no memory	-13,825	26
613	Upgrade from Series III w/256K bytes memory and 30341A HP-IB Adapter	-15,000	0
614	Upgrade from Series 39 w/no memory	-11,650	13
615	Upgrade from Series 42 w/no memory	-15,075	26
32460BH	Upgrade to Series 64 (32460B) w/2 megabytes memory	162,300	664
601	Upgrade from pre-Series II or HP 2000 w/128K bytes	-2,500	0
602	Upgrade from Series II w/128K bytes memory	-3,000	0
603	Upgrade from Series III w/256K bytes memory	-27,000	0
605	Upgrade from S/33A/B w/256K bytes memory, 2649E	-8,000	26
606	Upgrade from S/33C/U w/256K bytes memory, 2649E	-8,000	26
607	Upgrade from S/30A/B w/256K bytes memory, 2649E	-6,000	13
608	Upgrade from S/30C/U w/256K bytes memory, 2649E	-6,000	13
609	Upgrade from Series 44 w/1 megabyte memory	-43,000	26
611	Upgrade from Series 40 w/no memory	-13,825	26
613	Upgrade from Series III w/256K bytes memory and 30341A HP-IB Adapter	-30,000	0
32468BH	Upgrade to Series 68 (32468B) w/3 megabytes memory	182,300	739
250	Add Expansion Bay & I/O Adapter (IMB)	25,000	53
601	Upgrade from pre-Series II or HP 2000 w/128K bytes memory	-2,500	0
602	Upgrade from Series II w/128K bytes memory	-3,000	0
603	Upgrade from Series III w/256K bytes memory	-27,000	0
605	Upgrade from S/33A/B w/256K bytes, 2649E	-8,000	26
606	Upgrade from S/33C/U w/256K bytes memory, 2649E	-8,000	26
607	Upgrade from S/30A/B w/256K bytes memory, 2649E	-6,000	13
608	Upgrade from S/30C/U w/256K bytes memory, 2649E	-6,000	13
609	Upgrade from Series 44 w/1 megabyte	-43,000	26
611	Upgrade from Series 40 w/no memory	-13,825	26
613	Upgrade from Series III w/256K bytes memory and 30341A HP-IB Adapter	-30,000	0
614	Upgrade from Series 39 w/no memory	-11,650	13
615	Upgrade from Series 42 w/no memory	-15,075	26
616	Upgrade from Series 48 w/1 megabyte memory	-45,500	26

*The U.S. list price includes freight charges.

Hewlett-Packard HP 3000 Series

EQUIPMENT PRICING

		Purchase*	Standard Monthly Maint.
		Price	Price
RE-MARKETED SYSTEMS			
32412CR	HP 3000 Series 33R System (Re-Marketed) (60 Hz) includes 512K bytes memory, 2649E console, FOS on 1600 bpi tape. Must order all ADCCs and GICs separately	\$ 12,225	\$ 307
018	ADCC-main with 4 ports	1,185	10
019	ADCC-extender with 4 ports	1,185	10
507	Expands memory to 1024K bytes memory	6,030	40
720	7920S Slave 50-megabyte disk drive (Re-Marketed) with cables (60 Hz)	9,825	95
721	7920S Slave 50-megabyte disk drive (Re-Marketed) with cables (50 Hz)	9,825	95
725	7925S Slave 120-megabyte disk drive (Re-Marketed) with cables (60 Hz)	13,725	85
726	7925S Slave 120-megabyte disk drive (Re-Marketed) with cables (50 Hz)	13,725	85
920	7920M Master 50-megabyte disk drive (Re-Marketed) with HP-IB interface and cable (60 Hz)	13,175	139
921	7920M Master 50-megabyte disk drive (Re-Marketed) with HP-IB interface and cable (50 Hz)	13,175	139
925	7925M Master 120-megabyte disk drive (Re-Marketed) with HP-IB interface and cable (60 Hz)	17,750	129
926	7925M Master 120-megabyte disk drive (Re-Marketed) with HP-IB interface and cable (50 Hz)	17,750	129
970	7970E 1600 bpi tape drive HP-IB master in upright cabinet (110 VAC)	12,200	154
971	7970E 1600 bpi tape drive HP-IB master in upright cabinet (230 VAC)	12,200	154
32430CR	HP 3000 Series 30R System (Re-Marketed) (60 Hz) includes 512K bytes memory, 2649E console, FOS on 1600 bpi tape. Must order all ADCCs and GICs separately	11,475	296
018	ADCC-main with 4 ports	1,185	10
019	ADCC-extender with 4 ports	1,185	10
507	Expands memory to 1024K bytes memory	6,030	40
720	7920S Slave 50-megabyte disk drive (Re-Marketed) with cables (60 Hz)	9,825	95
721	7920S Slave 50-megabyte disk drive (Re-Marketed) with cables (50 Hz)	9,825	95
725	7925S Slave 120-megabyte disk drive (Re-Marketed) with cables (60 Hz)	13,725	85
726	7925S Slave 120-megabyte disk drive (Re-Marketed) with cables (50 Hz)	13,725	85
920	7920M Master 50-megabyte disk drive (Re-Marketed) with HP-IB interface and cable (60 Hz)	13,175	139
921	7920M Master 50-megabyte disk drive (Re-Marketed) with HP-IB interface and cable (50 Hz)	13,175	139
925	7925M Master 120-megabyte disk drive (Re-Marketed) with HP-IB interface and cable (60 Hz)	17,750	129
926	7925M Master 120-megabyte disk drive (Re-Marketed) with HP-IB interface and cable (50 Hz)	17,750	129
970	7970E 1600 bpi tape drive HP-IB master in upright cabinet (110 VAC)	12,200	154
971	7970E 1600 bpi tape drive HP-IB master in upright cabinet (230 VAC)	12,200	154
32435BR	HP 3000 Series IIIr System (Re-Marketed) includes 512K bytes memory, 1 ATC, with Bell 103, 202T, and 212 modem support, and FOS on 1600 bpi tape	20,400	538
010	INP Board	3,305	43
032	Additional ATC	2,205	15
033	Additional ATC (with modem control)	3,110	18
055	SSLC Board	1,255	19
209	Line Printer Controller	955	6
215	Additional Magnetic Tape Controller	1,985	17
507	Expands memory to 1024K bytes	7,020	50
509	Expands memory to 1524K bytes	14,030	108
511	Expands memory to 2048K bytes	21,035	158
720	7920S Slave 50-megabyte disk drive (Re-Marketed) with cables (60 Hz)	9,825	95
721	7920S Slave 50-megabyte disk drive (Re-Marketed) with cables (50 Hz)	9,825	95
725	7925S Slave 120-megabyte disk drive (Re-Marketed) with cables (60 Hz)	13,725	85
726	7925S Slave 120-megabyte disk drive (Re-Marketed) with cables (50 Hz)	13,725	85
820	7920M Master 50-megabyte disk drive (Re-Marketed) with cables (60 Hz)	12,175	135
821	7920M Master 50-megabyte disk drive (Re-Marketed) with cables (50 Hz)	12,175	135
825	7925M Master 120-megabyte disk drive (Re-Marketed) with cables (60 Hz)	16,750	125
826	7925M Master 120-megabyte disk drive (Re-Marketed) with cables (50 Hz)	16,750	125
870	7970E 1600 bpi tape drive in new upright cabinet (110 VAC)	11,725	100
871	7970E 1600 bpi tape drive in new upright cabinet (230 VAC)	11,725	100
I/O EXPANSION			
30018A	Asynchronous Data Communications Controller (ADCC)—main	1,695	10
30018AR	ADCC-main (remarketed)	1,440	10
30019A	Asynchronous Data Communications Controller (ADCC)—extender	1,695	10
30019AR	ADCC-extender (remarketed)	1,695	10
30079A	General I/O Channel (GIC)	1,900	13
30087A	HP 3000 Series 44 I/O expansion kit	9,000	26
30143A	I/O Adapter Module for Series 64, 68 (IMB)	10,100	34
NOTE: Advanced Terminal Processor (DSN/ATP) consists of an SIB (30144A) and port controller			
30144A	DSN/ATP System Interface Board (SIB)	3,145	15
30145A	DSN/ATP Direct Connect Port Controller. Standard Provides 12 RS-422 Ports	6,530	28
001	First Port Controller on Series 64, 68	-250	0
30155A	DSN/ATP Modem Port Controller	8,070	34
001	First Port Controller on Series 64, 68	-250	0
MEMORY EXPANSION			
30092A	512K-byte Memory Module for Series 39, 4x	8,500	16
30094A	Add-on Series 44, 48 Memory Controller	1,600	11
30142A	1 megabyte Memory Module for Series 64, 68	12,000	75
30161A	1 megabyte Memory Module for Series 39, 4x	12,000	32
30171A	256K-byte Memory Module for Series 39, 40, 42	4,500	8
30171AR	256K byte Memory Module for Series 39, 4x (re-marketed)	3,825	8

*The U.S. list price includes freight charges.

Hewlett-Packard HP 3000 Series

EQUIPMENT PRICING

		Purchase* Price	Standard Monthly Maint.
► MASS STORAGE			
7911P	28-megabyte Disk Drive with Cartridge Tape Drive and One Controller with cable	\$ 14,800	\$ 54
001	Adds second controller	1,840	24
140	Deletes Cartridge Tape Drive	-3,570	-11
7912P	65-megabyte Disk Drive with Cartridge Tape Drive and One Controller with cable	17,350	56
001	Adds second controller	1,840	24
140	Deletes Cartridge Tape Drive	-3,570	-11
7914P	132-megabyte Disk Drive with Integral 67-megabyte Tape Cartridge	19,900	66
001	Adds dedicated controller	1,840	24
140	Deletes Cartridge Tape Drive	-3,570	-14
7914R	132-megabyte Disk Drive for a 7914TD	19,900	66
140	Deletes Cartridge tape drive	-3,570	-14
7914TD	Mass Storage Subsystem Consisting of 132-megabyte 7914 Disk Drive and 7970E ½" Mag Tape Drive (HP-IB Version) Mounted in a 72" high cabinet	26,540	209
002	Adds Cartridge Tape Drive and second controller	5,410	24
114	Adds second 7914 (opt. 140) Disk Drive	14,290	52
7920M	Master 50-megabyte Disk Drive	19,400	135
102	HP-IB interface and cable	1,200	4
7920MR	Master 50-megabyte Disk Drive (Re-Marketed)	12,175	135
102	HP-IB interface and cable	1,000	4
7920S	Add-on 50-megabyte Disk Drive	15,310	95
7920SR	Add-on 50-megabyte Disk Drive (Re-Marketed)	9,825	95
7925M	Master 120-megabyte Disk Drive	22,510	125
102	HP-IB interface and cable	1,200	4
7925MR	Master 120-megabyte Disk Drive (Re-Marketed)	16,750	125
102	HP-IB interface and cable	1,000	4
7925S	Add-on 120-megabyte Disk Drive	18,220	85
250	Disk Controller Upgrade	535	0
7925SR	Add-on 120-megabyte Disk Drive (Re-Marketed)	13,725	85
7925T	Add-on 240-megabyte Disk Storage System	32,190	170
7933H	404-megabyte Fixed Media Disk Drive, Standard Operating Voltage is 208V, with cable	25,520	90
7933G	1.2-gigabyte Storage System, consists of three 7933H, 404-megabyte disk drives each with media, controller, power supply, and cable	63,560	270
7935G	1.2-gigabyte removable Disk system; consists of three 7935H, 404MB disk drives, each with media; controller, power supply and HP-IB cable	74,000	507
7935H	404-megabyte Removable Media Disk Drive, Standard Operating Voltage is 208V, with cable	28,070	169
97935A	404-megabyte Removable Media Module for 7935H Disk Drive	1,531	38
9895A	Flexible Disk System	5,910	77
13394A	7920M/S Disk Pack	560	N/A
13356A	7925M/S Disk Pack	905	N/A
MAGNETIC TAPE SUBSYSTEMS			
7970B	800 cpi/45 ips Magnetic Tape Subsystem	8,410	103
426	HP-IB master drive in lo-boy cabinet	5,110	67
436	HP-IB master drive without cabinet	2,310	54
431	Slave drive without cabinet	300	-7
7971A	Magnetic Tape Subsystem in Upright Cabinet	11,200	0
340	7970E HP-IB Master	5,090	154
344	7970E Two HP-IB masters (Series 44, 48, and 6x only)	16,700	305
330	7970E Slave drive	1,935	93
333	7970E Two slave drives	12,520	183
343	7970E Two drives, HP-IB master and slave	14,560	244
7974A	1600 cpi/50 ips start/stop, 100 ips streaming, Magnetic Tape Subsystem with HP-IB interface	12,500	91
131	Delete cabinet; add hardware for installation in existing 7974A cabinet	-500	0
800	Add 800 cpi NRZI format	2,500	16
7976A	1600/6250 cpi Magnetic Tape Subsystem	44,440	586
7976A	Quantity Two (2) high speed 1600/6250 bpi Tape Systems. Must be ordered together	88,880	1,172
222	Twin-Pack credit	-7,500	0
	Total after credit	81,380	
26074A	Installation Kit for Mounting the 7970B/E in the Bottom Rack of a 7971A Cabinet	460	0
26075A	Multiple System Access Selector. Order Cables Separately	725	6
30215AR	Magnetic Tape Controller. Interfaces fifth through eight 7970B or 7970E magnetic tape drives with 300 level options. (Re-Marketed)	2,710	17
PRINTERS			
Options 301, 302, 344, and 364 for 2611/19A provide a 26069A interface; do not order 26069A separately			
26069A	2611/19A Line Printer Interface for Series 3x, 4x, and 6x. Must order one of the following options	2,475	22
	Cable set	700	0
30209AR	Line Printer Controller to interface 2608A, 2613A, 2617A, and 2619A line printers with option 300. (Re-Marketed)	1,285	6
2601A	40 cps Daisywheel Printer, Modem cable included (02631-60065, 13242N equivalent)	3,520	86
26010D	Dual bin sheetfeeder for 2601A	2,290	27
2602A	20 cps Daisywheel Printer, Cable not included	1,545	50
2608A	400 lpm Printer (1-69 print hrs/month)	11,890	131

*The U.S. list price includes freight charges.

Hewlett-Packard HP 3000 Series

EQUIPMENT PRICING

		Purchase* Price	Standard Monthly Maint.
▶ 2608S	400 lpm Printer (1-69 print hrs/month)	\$ 11,170	\$ 90
055	HP 3000 Multipoint I/O Subsystem	870	0
333	HP-IB interface and cable for S/3x	1,025	0
340	HP-IB interface and cable for S/39, 40, 42	1,025	0
344	HP-IB interface and cable for S/44, 48	1,025	0
364	HP-IB interface and cable for S/64, 68	1,025	0
2611A	600 lpm Printer (1-66 print hours per month)	18,560	303
001	96 character set; 430 lpm	1,455	0
002	64 character set with OCR-B font	700	0
003	96 character set with OCR-B font	2,155	0
2619A	1000 lpm Printer (1-66 print hrs/month)	26,370	381
001	96 character set; 750 lpm	1,455	0
002	64 character set with OCR-B font	700	0
003	96 character set with OCR-B font	2,155	0
	One of the following options must be ordered		
300	HP 3000 Series III cable	1,025	0
301	Series 30 HP-IB interface and cable	2,530	22
302	Series 33 HP-IB interface and cable	2,530	22
340	Series 39, 40, 42 HP-IB interface and cable	2,530	22
344	Series 44, 48 HP-IB interface and cable	2,530	22
364	Series 64, 68 HP-IB interface and cable	2,530	22
2631B	180 cps Dot Matrix Printer. Modem cable 02631-60065 included with standard RS-232 interface	3,970	44
2631G	Graphics Printer. Cable not included	4,970	48
200	Bar Code Printer	600	-9
2680A	Intelligent Page Printer. Includes 125,000 rotations. Cable and documentation is additional	91,600	580
	U02: 125,001 to 200,000 rotations	—	+400
	U03: 200,001 to 275,000 rotations	—	+770
	U04: 275,001 to 350,000 rotations	—	+1,130
060	Graphics/Extended Memory Management	2,565	0
505	Add-on 256K-byte memory module	4,550	6
520	One megabyte Memory (Deletes std. 256K-byte memory)	7,550	24
521	One megabyte Memory Addition	12,000	32
525	Vacuum Paper Splice Option	1,025	0
2680A	Add-on 256K-byte memory module for 2680A and 26804A	4,550	6
26085A	Add-on 1 megabyte memory for the 2680A and 26804A	12,000	32
26086A	Add-on graphics, extended memory management for the 2680A and 26804A	3,690	0
26804A	2685 Model 40 Print Station. Includes 125,000 rotations. Includes cables	164,000	1,092
	U02: 125,001 to 200,000 rotations	—	+400
	U03: 200,001 to 275,000 rotations	—	+770
	U04: 275,001 to 350,000 rotations	—	+1,130
030	Adds Cobol II compiler	5,000	0
031	Adds Fortran compiler	2,100	0
040	Deletes 64 megabyte disk and adds 404 megabyte disk for U.S. 120 VAC	13,350	34
041	Deletes 64 megabyte disk and adds 404 megabyte disk for U.S. (Standard) 208 VAC	13,350	34
050	Expands disk capacity to 120 megabyte disk 120 VAC	10,400	84
051	Expands disk capacity to 120 megabyte disk 120 VAC	10,400	84
052	Deletes 7912/7971, adds 7914TD	-1,000	10
054	Deletes 7912/7971, adds 7914TD; 264 megabyte	13,290	62
060	Graphics/extended memory management	2,565	0
065	Graphics software interface	6,000	0
074	Deletes 7971A; adds 7976A, 120V/60 Hz	30,450	432
077	Deletes 7971A; adds 7976A, 120V/60 Hz	30,450	432
095	Deletes 7971; no replacement	-12,790	-154
096	Deletes 2382A console; no replacement	-1,820	-20
097	Deletes 65 megabyte disk; no replacement	-12,350	-45
098	Deletes 1600 bpi magnetic tape unit and replace with cartridge tape unit on the 7912P	-8,750	-143
099	Deletes design and formatting software and graphics terminal	-10,250	-41
505	256K-byte memory extension	4,550	0
520	One megabyte memory (Deletes std. K-byte memory)	7,550	24
521	One megabyte memory addition	12,000	32
525	Vacuum Paper Splice Option	1,025	0
607	Expand controller memory to 1 megabyte	8,200	16
2687A	Desktop Laser printer	12,800	151
2688A	Text and Graphics Laser printer	29,950	269
040	Deletes IF5/3000 and graphics intrinsics	-4,000	0
26075A	Multiple System Access Selector. Order Cables Separately	725	6
2563A	300 lpm line printer featuring compressed print, multinational and OCR character sets, raster graphics and bar codes	5,780	
2932A	200 cps character-sequential printer	2,495	
2633A	200 cps factory data printer featuring large-character generation and bar-code printing	2,795	
2934A	Distributed office printer with 40 or 67 cps matrix letter-quality print or 200 cps memo-quality print	2,895	
GRAPHICS PLOTTERS			
7220C	Graphics Plotter, includes RS-232 cable	5,860	70
7220T	Graphics Plotter, with automatic paper advance, includes RS-232 cable	7,980	80
7221C	Graphics Plotter, includes RS-232 cable	5,860	70

*The U.S. list price includes freight charges.

Hewlett-Packard HP 3000 Series

EQUIPMENT PRICING

		Purchase* Price	Standard Monthly Maint.
7221T	Graphics Plotter, with automatic paper advance, includes RS-232 cable	\$ 7,980	\$ 80
001	Expanded Buffer Memory for Models 7220 and 7221	225	0
7470A	Graphics Plotter	1,095	24
7475A	Graphics plotter, 6-pen, B-size	1,895	24
7580B	Drafting Plotter-combo HP-IB/RS-232	16,100	124
7585B	Drafting Plotter-combo HP-IB/RS-232	22,900	108
9872C	Graphics Plotter	5,860	70
9872T	Graphics Plotter, with automatic paper advance	7,980	80
17455A	Eavesdrop cable for 747x opt. 001	120	0
DIGITIZERS			
9111A	Graphics Tablet; 16 softkeys	2,275	16
17623A	Graphics tablet for 2627A terminal	1,920	12
TERMINALS			
2382A	Office Display Terminal	1,720	20
2621B	Character Mode Terminal	1,295	24
2622A	Block Mode Terminal	2,210	28
2623A	Graphics Terminal	3,250	36
2624B	Data Entry Terminal	3,035	33
2625A	Dual system terminal	3,495	24
2626A	Display Station. 110V/60 Hz	4,400	41
050	Integral Thermal Printer for the 2621B, 2622A, 2623A, 2624A, 2625A and 2628A	1,210	16
2627A	Color Graphics Terminal	5,975	34
2628A	HPWord terminal	3,195	26
2641A	APL Display Station	5,850	34
2645A	Display Station	4,600	34
2647F	Intelligent Graphics Terminal	9,950	89
072	Second Flexible Mini Disk Drive	1,050	0
890	Series 64, 68 Console	-1,750	0
2648A	Graphics Terminal	7,150	41
096	Shared Peripheral Interface	735	0
007	Integrated dual cartridge tapes	1,400	12
2703A	High Performance Color Graphics Terminal	19,900	160
054	RGB video output interface	1,150	0
072	Dual integral flexible mini-disks	2,200	0
096	Shared peripheral interface	1,250	0
164	Application memory 128K bytes	1,250	0
165	Application memory 256K bytes	1,850	0
174	Increases vector memory by 64K bytes	300	0
175	Increases vector memory by 192K bytes	1,150	0
176	Increases vector memory by 448K bytes	2,650	0
177	Increases vector memory by 960K bytes	5,500	0
186	Double buffered graphics memory	1,350	0
555	Model 55 Technical Design Terminal	4,100	0
560	Model 60 Decision Support Workstation	4,100	0
565	Model 65 Presentation Graphics Workstation	8,100	0
2635B	180 cps Printing Terminal, includes Modem cable	4,370	41
3075A	Desk Top Data Capture Terminal	2,715	54
3076A	Wall Mounted Data Capture Terminal	3,200	54
The following options apply to 3075A and 3076A:			
004	Alphanumeric keyboard	270	0
005	Alphanumeric display	570	0
006	5-inch CRT	985	17
007	Multifunction reader	985	46
008	Type V badge reader	570	26
009	Alphanumeric printer	570	35
010	General Purpose Bar Code Reader	640	12
011	Auxiliary HP-IB Port	805	0
012	Magnetic Stripe Reader	690	13
013	RS-232-C Auxiliary Interface	570	0
021	Delete reference manual	-50	N/A
054	Low resolution industrial bar code reader	1,030	11
055	High resolution industrial bar code reader	1,030	11
3077A	Time Reporting Terminal	3,610	61
001	Replace Type V Reader with Multifunction Reader	460	0
002	Replace Type V Reader with Magnetic Stripe Reader	115	0
005	Alphanumeric Display	635	0
021	Delete Reference Manual	-50	N/A
3081A	Industrial Workstation Terminal	740	7
3092A	Industrial Display Terminal compatible with 2622A	4,305	30
3093A	Industrial Display Terminal compatible with 2623A	6,040	38
The following options apply to 3092A and 3093A:			
054	Low resolution bar code reader	815	11
055	High resolution bar code reader	815	11
056	High resolution bar code slot reader	815	11

*The U.S. list price includes freight charges.

Hewlett-Packard HP 3000 Series

EQUIPMENT PRICING

		<u>Purchase*</u> <u>Price</u>	<u>Standard</u> <u>Monthly</u> <u>Maint.</u>
13231A	Display enhancements (except 2642A)	\$ 400	\$ 0
201	Math symbols alternate character set	105	0
203	Large character alternate character set	160	0
13234A	Terminal 4K memory module (except 2642A)	320	0
13261A	Device support firmware	185	0
13296A	Shared peripheral interface for 2647/48A graphics terminals	745	0

COMMUNICATIONS

2333A	Cluster Controller	2,000	16
2334A	X.25 Cluster Controller	2,350	16
112	4-port serial interface	600	0
3074A	Data link adapter	715	11
3074M	Data link adapter (for asynchronous modem configurations)	820	6
13260C	Asynchronous Multipoint Communications Interface for 264x terminals	460	0
13260D	Synchronous Multipoint Communications Interface for 264x terminals	480	0
13264A	Data link adapter 2626A/2624B terminal	350	—
13267A	Asynchronous Multipoint Interface for first 2626A terminal	400	0
011	Synchronous Multipoint Interface	0	0
30010A	Intelligent Network Processor (INP) for Series III	4,760	43
001	New I/O card cage backplane	400	N/A
30020B	Intelligent Network Processor (INP) for Series 4x or 64	4,235	53
30055A	Synchronous single line controller	2,100	19
001	Replaces synchronous cable with asynchronous cable for hardwired operation	0	0
39301A	Fiber Optic Multiplexer	2,500	18

*The U.S. list price includes freight charges.

SOFTWARE PRICES

		<u>Price</u>
LANGUAGES		
32233A	Cobol II/3000 Compiler	\$5,000
300	Basic/RPG/300 return credit	-1,575
301	SL/300 return credit	-2,100
32233R/M	Right to copy 32233A with/without sublicense	2,500
300	Basic/RPG/300 return credit	-630
301	SL/300 return credit	-840
32213R/M	Right to copy 32213C with/without sublicense	875
32104A	RPG/3000 Compiler	3,000
300	Basic/RPG/300 return credit	-1,575
301	SL/300 return credit	-2,100
32104R/M	Right to copy 32104A with/without sublicense	1,500
300	Basic/RPG/300 return credit	-630
301	SL/300 return credit	-840
32102B	Fortran/3000 Compiler	2,050
300	Basic/RPG/300 return credit	-1,575
301	SL/300 return credit	-2,050
32102R/M	Right to copy 32102B with/without sublicense	1,025
300	Basic/RPG/300 return credit	-630
301	SL/300 return credit	-840
32111A	Basic/3000 Interpreter and Compiler	2,050
300	Basic/RPG/300 return credit	-1,575
301	SL/300 return credit	-2,050
32111R/M	Right to copy 32111A with/without sublicense	1,025
300	Basic/RPG/300 return credit	-840
301	SL/300 return credit	-630
32105R/M	Right to copy 32105A with/without sublicense	3,375
32106A	Pascal/3000 Compiler	5,000
300	Basic/RPG/300 return credit	-1,575
301	SL/300 return credit	-2,100
32106R/M	Right to copy with/without sublicense	2,500
300	Basic/RPG/300 return credit	-630
301	SL/300 return credit	-840
32100A	SPL/3000 Compiler	2,725
300	Basic/RPG/300 return credit	-1,575
301	SL/300 return credit	-2,100
32100R/M	Right to copy 32100A with/without sublicense	1,375
300	Basic/RPG/300 return credit	-630
301	SL/300 return credit	-840

Hewlett-Packard HP 3000 Series

SOFTWARE PRICING

		<u>Price</u>
► DATA COMMUNICATIONS		
30130E	DSN/RJE Remote Job Entry	\$ 1,350
300	31447A RJE/300 credit	-525
30130R/M	Right to copy 30130E with/without sublicense	675
300	31447R RJE/300 credit	-105
32189A	DSN/DS Distributed System Software for MPE-V and MPE-VR based systems	5,000
32189R/M	Right to copy 32189A with/without sublicense	2,500
32190A	DSN/DS Distributed Systems Software	5,000
32190R/M	Right to copy, with/without sublicense	2,500
32191A	DSN/X.25 Packet Switched Network access software for MPE-V and MPE-VR based systems	4,500
32191R/M	Right to copy 32191A with/without sublicense	2,250
32192A	DSN/MRJE Multileaving Remote Job Entry	2,520
300	31447A RJE/300 credit	-525
32192R/M	Right to copy 32192A with/without sublicense	1,260
300	31447A RJE/300 credit	-105
32229A	DSN/IMF Interactive Mainframe Facility	7,000
300	31447A RJE/300 credit	-525
32229R/M	Right to copy 32229A with/without sublicense	3,500
300	31447A RJE/300 credit	-105
32193A	DSN/MTS Multipoint Terminal Support	2,500
30239A	DSN/Workstation configurator	3,500
30239R/M	Right to copy 30239A with/without sublicense	1,750
32193R/M	Right to copy 32193A with/without sublicense	1,250
PROGRAMMER PRODUCTIVITY TOOLS		
32244A	Dictionary/3000 Relational Data Dictionary	5,000
32244R/M	Right to copy 32244A with/without sublicense	2,500
32245A	Report/3000 Report Writer	5,000
32245R/M	Right to copy 32245A with/without sublicense	2,500
32246A	HP Inform/3000 User Report Generator. Requires Dictionary/3000 (32244A)	6,000
32246R/M	Right to copy 32246A with/without sublicense	3,000
32247A	Transact/3000 Transaction Processing Language and Processor	6,000
32247R/M	Right to copy 32247A with/without sublicense	3,000
32248A	Programmer productivity package (Report/3000, Dictionary/3000, Transact/3000)	13,000
32248R/M	Right to copy 32248A with/without sublicense	6,500
32449A	RAPID/3000 Processor, execute only for Transact/3000, and Report/3000 programs	3,500
32258A	HP Report Writer Package	13,000
32258R/M	Right to copy 32258A with/without sublicense	6,500
32350A	HPToolset Program Development System. Requires Cobol II/3000 (32233A)	5,000
32350R/M	Right to copy 32350A with/without sublicense	2,500 ■