KLlog61:DSR8! [30,5637] F3.mem 10/7/82

.\*

.

.

.

# Copyrisht (C) 1982 Disital Equipment Corporation, Maynard, Massachusetts, U.S.A.

This software is furnished under a license and may be used and copied only in accordance with the terms of such license and with the inclusion of the above copyright notice. This software or any other copies thereof may not be provided or otherwise made available to any other person. No title to and ownership of the software is hereby transferred.

The information in this software is subject to change without notice and should not be construed as a commitment by Digital Equipment Corporation.

Disital assumes no responsibility for the use or reliability of its software on equipment which is not supplied by Disital.

#### 1.0 Introduction and Overview

This document is intended to describe the various record formats that the LCG tape utilities, Backup and Dumper, produce. For people interesting in learning about Backup's record formats, you will probably find enough information in the section on Backup. For those seeking to learn about Dumper, you had best read everything. In order to understand how Dumper fails to faithfully follow the Interchange format, you should understand how it is supposed to be done by reading about Backup.

#### \*\*\*WARNING\*\*\*

This document is not intended for the besinner. This document is a reference guide to the record formats. It is sussested that you carefully read the entire document before attempting to use the information. Each section contains information that you will need to know before being able to understand the next section. Each section builds up on the information presented previously. Therefore if you decided to start in the middle and encounter a problem, you probably could have avoided it by reading everything first.

### 1.1 Sources of Information

Backup and Dumper appear to come from two separate realities. Historically Dumper was written before Backup, but the Interchanse mode that they both share is based on the way that Backup does things.

The reader is expected to be able to find out some information on his own. For example, when the various parts of TOPS-10 file RIB or a TOPS-20 FDB are being discussed, it is expected that you can use your Notebook sets to find the appropriate data. (This information can be found in the respective Monitor Calls Reference Guide for your system.) This document will not take the time to explain information readily available in the notebooks except to point out where you can find it.

For TOPS-20 people, recommended reading is the Tape Processing Manual which currently lives in Notebook 16. This will give you a basic understanding of how tapes are supposed to work, how the information is put onto the tape, the differences between labeled and unlabeled tapes, and the format of the tapes in terms of tape files, tape marks, and other system considerations. For those of you who don't have TOPS-20 notebook sets the order number is AA-H180A-TM.

For TOPS-10 people about all you will find is the Backup suide stuck in Appendix F of the Operators Guide, which is in Notebook 15.

Another place to find information is the source code to Backup. Run the source files through RUNOFF and you will get .PLM files. These Program Logic Manuals are somewhat informative, but they are aimed at the engineer/maintainer who works regulary with the internal code.

Basically, the reader should have available the Monitor Calls Reference Guide for their particular system, the users guide for their favorite mastage utility, and a copy of the source code. The reader of this document is expected to be an experienced MACRO prossummer and be familiar with the internal workings of their operating system (TOPS-10 or TOPS-20). This document can also be used as a debuging aid to figure out if/how your tape possibly got corrupted, but where to set break points and how to examine the incomming/outgoing buffers is left to the reader. (Hint: the Backup .PLM manual tells you where the input/output routines are and Dumper uses the DUMPO/DUMPI jsys to put the data to tape.)

#### 2.0 Definitions and Conventions

This section will attempt to set some conventions and explain some defintions that occur in this document. This is \*\*\*NOT\*\*\* a primer on how mastapes work.

#### Record

A record is one buffer of information written/read to tape. A record is made up of a header section and a data area.

#### Header

A header is at the top of a record. A header contains information about the contents of the record such as the checksum and the sequence number of the record. The header information is an unique identifier for each record on the tape.

#### Data Area

The data area of a record is where the contents of a disk file or other types of file information are stored. The data areas for both Backup and Dumper are one pase in length. This size conviently holds 1 pase of disk data. Room is not reserved in the header area for variable length information about a file such as the filename, the user name, or the path of the directory. This kind of information can be found in the data area. With only one exception, you will not find disk data and variable information in the data area at the same time.

#### Record Type

There are different types of records. Not all records contain disk file data. There are records that indicate the start and the end of a disk file, there are records which indicate the start and the end of a saveset (tape file). Each record type is given a different numeric value to distinguish it from the rest.

#### Sequence Numbers

A sequence number is siven to each record on a tape. The first record is siven a sequence number of one, the second a sequence number of two, and so on. If a record is duplicated on tape due to an error on write, a sequence number will be repeated to indicate that both records are supposed to contain identical information. Therefore if there is an error

in reading the record back and then the next record contains the same sequence number, then that record has a second chance at being restored successfully.

#### Relative Tape Numbers

Relative tape numbers are issued in the same manner as record sequence numbers. All of the files saved on the first tape of tape volume will have a relative tape number of one, files saved onto the next continuation tape will have a relative tape number of two, and so on.

#### Tare Label

A tape label is a record which identifies the tape. It is the first record written to tape and can contain such information as density, parity, system information and reel-id of the tape. System software will read this information and set parameters with it.

#### 3.0 Labeled and Unlabeled Tares

TOPS-20 is the only LCG system that writes labeled tapes at this point in history. Labeled tapes for TOPS-10 is commins at some point in the future. Labeled tapes contain "extra" records which identify the start of a volume, start of a saveset, end of a saveset, etc. These records will not be discussed here because they are supposed to be transparent to the user and they are already described in the Tape Processins Manual. The only warning that should be heeded about labeled tapes is that they only work when the software to read those labels is running (IE. MOUNTR, GALAXY). You cannot expect to use labeled tapes for INTERCHANGE mode between 10 and 20. Dumper will not handle labeled tapes without GALAXY/MOUNTR running as well.

Then there are unlabeled tapes. Currently, all the tapes that TOPS-10 produces are unlabeled. Unlabeled tapes contain only the records that are dicussed in this document.

### 4.0 Backup Tape Format

All records have a standard length of 544(10) words. The first 32(10) words are the header and the remaining 512(10) words are the data area. All undefinded or unused words are written with zeros and ignored on read. This maximizes the probability of reading old tapes.

### 4.1 Record Types

Name	Value	Contents
T\$LBL	1	Tare Label - Must be at start of tare.
T\$BEG	2	Saveset Header - includes o Saveset name o Device o System
		- Must be first record of saveset
TSEND	3	<ul><li>Saveset Trailer</li><li>identical to T\$BEG in format</li></ul>
T\$FIL	4	- data record
T\$UFD	5	<ul><li>contains directory information</li><li>is used to rebuild directory</li><li>not written in Interchanse mode</li></ul>
T\$EOV	6	- end of volume
T # C O M	7	- comment record (isnored)
T\$CON	10	- continuation of saveset - same as T\$BEG in format

# 4.2 Standard Record Format

The first 12 words of the header are identical for every record. Words zero through 6 and 13 are already defined. Words 7 through 12 are empty for future use. In Interchange mode, the customer word will be set to zero on write and ignored on read.

Word	Name	Contents
Word O	(G\$TYPE)	Contains record type value.
Word 1	(G\$SEQ)	Sequence number of record.
		This is incremented by one for each record on the
		tare. If a record is reseated because of a tare
		write error, the number of the reseated record is
		the same as that of the original.
Word 2	(G\$RTNM)	Relative tare number.
Word 3	(G\$FLAG)	Various flass about the record.
	GF\$EOF	(1BO) Last record of disk file.
	GF\$RPT	(1B1) Reseat of last record.
	GF\$NCH	(1B2) Isnore checksum.
	GF\$SOF	(1B3) Start of file.
	GF\$UFE	Disk error.
Word 4	(G\$CHK)	Checksum of record.
Word 5	(G\$SIZ)	Number of words used as data.
Word 6	(G\$LND)	Number of words to skip before data starts.
Word 13	(G\$CUSW)	Customer word.

#### 4.3 Non-data Information Blocks

Non-data information blocks start with a control word containing the numeric type of the information block in the left half, and the length of the block (including the control word) in the right half. More than one type of non-data information block may appear per record. These non-data blocks will appear in the data section of the record. They do not contain the contents of the file, they are merely pieces of information about the disk file being written on tape.

Value	Name	Contents
1	0\$NAME	Path identification of file
2	O\$FILE	File information
3	O\$DIRT	Directory information
4	O\$SYSN	System header
5	O\$SSNM	Saveset name

#### 4.3.1 O\$NAME block

- full path identification of file without punctuation
- uses sublocks to store information
  - o device
  - o directories (top-down order)
  - o file
  - o extension
  - o version
  - o seneration
- each sub-block headed by a control word of:
   [type, length]
- information is ASCII string terminated by a null
- omitted fields are defaulted
- in Interchanse only name, ext, and version are written

### 4.3.2 OsfILE (File Information)

The O\$FILE block contains file attribute information. The first section of this block is a fixed length header area containing in fixed locations either single word attributes or byte pointers to ASCIZ string attributes located in the remaining section. All dates and time are in universal date/time format. In Interchange mode only the critical attributes (starred) will be written, and the rest of this block will contain zeros. In the description which follows, the symbols in brackets represent the RIB data from which the attribute values will be converted.

	Name	Value	Contents
(*)	A\$FHLN	0 Fix	ed header length in words
	A\$FLGS	1 fla:	as s
	B\$PERM	(1BO)	Pernament [RP.NDL]
	B\$TEMP	(1B1)	Temporary
	<b>B\$DELE</b>	(182)	Already deleted
	B\$DLRA	(1B3)	Don't delete [RP.ABU]
	B\$NQCF	(1B4)	Not quota checked [RP.NQC]
	B\$NOCS	(185)	No valid checksums [RP.ABC]
	B\$CSER	(186)	Checksum error ERP.FCEl
	B\$WRER	(1B7)	Disk has write error [RP.FWE]
	<b>B\$MRER</b>	(1B8)	Backup read error on restore [RP.BFA]
	B\$DAER	(189)	Bad by damase assesment [RP.BDA]
(*)	A\$WRIT	2 Date	e/Time of last write [RB.CRD, RB.CRT]
(*)	A\$ALLS	3 All	ocated size in words [.RBALC]
(*)	A\$MODE	4 Mod	e of last write [RB.MOD]
<b>(*)</b>	A\$SIZ	5 Len:	sth (bytes) [.RBSIZ]
<b>(*)</b>	A\$BSIZ	6 Bet	size (7 or 36)
(※)	A\$VERS	7 Ver	sion (.JBVER format) [.RBVER]
	A\$PROT	10 Pro	tection [RB.FRV]
	A\$ACCT	11 Byt	e pointer to account string
	A\$NOTE	12 Bst	e pointer to annotation string [.RPSPL]
	A\$CRET		ation date and time of this seneration
	A\$REDT	14 Las	t read (date/time) [RB.ACD]
	A\$MODT	15 Mon	itor set last write [.RMTIM]
	A\$ESTS		imated size (words) [.RBEST]
	A\$RADR		uested disk address [.RBPOS]
	A\$FSIZ		file size (words)
	A\$MUSR		e pointer to last modifier
	A\$CUSR		e pointer to last creator [,RBAUT]
	A\$BKID		e pointer to BACKUP-id [.RBMTA]
	A\$BKDT		e/Time of last Backup
	A\$NGRT		ber of senerations to retain
	A\$NRDS		ber of opens for read this seneration
	A\$NWRT		ber of opens for write this seneration
	A\$USRW		efined User word [.RBNCA]
	A\$PCAW	31 Pri	ved Customer word [.RBPCA]

The following is a constant value rather than word with contents.

LN\$AFH 32 Length of fixed header

### 4.3.2.1 Protection codes (A\$PROT) -

The protection for directories appears in the directory attribute block (O\$DIRT). For files, the protection word has four fields of eight bits with a "5" in the leftmost three bits to prevent from looking like a byte pointer.

Bits 0-2 "5"

Bit 3 Reserved for future expansion

Bits 4-11 Future access

Bits 12-19 Owner access

Bits 20-27 Affinity group access

"World" access

Each access field is sub-divided into bytes which represent the attribute, write and read protections associated with the file.

Name	Value	Contents
		Reserved for special checkins Attribute sub-field of 3-bit butes
	File attr: Can chanse Reserved 1 Can chanse	is visible (7-6) ibutes are visible (5-2) unprotected attributes for future expansion
PR\$WRT	O No write a Append (4 Write (3)	- m · · · · · · · · · · · · ·
FR\$RED	0 No read at Execute of Can read	

### 4.3.3 O\$DIRT (Directors Attribute Information)

The O\$DIRT block contains directory attributes (not written in Interchanse mode). The first section of this block is a fixed length header area containing either directory attributes or pointers to attributes located in the remaining section. The symbols in brackets represent the RIB data used for conversion (the location is zero if none is siven). The directory protection word appears in this block rather than in the O\$FILE block (A\$FROT is zero for directories).

Nsme	Valu	e Contents
D\$FHLN D\$FLGS	0 1	Fixed header length in words. Directory flags.
DF\$F DF\$A DF\$R	AL	(1BO) Files only directory (1B1) Alpha accounts are lesal (1B2) Repeat losin messases
D\$ACCT	2	Account number or ASCII byte ptr to account
D\$PROT	3	Directors protection [RP.PRV].
D\$FPRT	4	Default file protection.
D\$LOGT	5	Date/time of last losin [RB.CRD and RB.CRT].
D\$GENR	6	Default number of senerations to keep.
D\$QTF	7	First-come-first-served lossed-in quota (words) [.RBQTF].
D\$QTO	10	Lossed out quota in words [.RBQTO].
D\$ACSL	11	List of groups that can access this directory.
D\$ISRL	12	List of groups that the user is in.
D\$PRVL	1.3	Privilese list.
D\$PSWD	14	ASCII byte pointer to password.

#### 4.3.4 O\$SYSN (System Header Information)

This block contains system header line in an ASCIZ string.

#### 4.3.5 O\$SSNM (Saveset Name)

This block contains the user supplied saveset name in ASCIZ (max of 30 characters). This block is omitted if no saveset name was specified.

# 4.4 Backup Record Formats

# 4.4.1 T\$LBL Record

The T\$LBL record contains only header information. There is nothing stored in the data area.

# 4.4.2 T\$BEG, T\$END, T\$CON Records

These records all contain the same information. They also contain O\$SYSN and O\$SSNM blocks in their data areas. They are distinguished by their record types and their occurance on tape.

Word	Name	Contents
Word O	(G\$TYPE)	Record Type
Word 1	(G\$SEQ)	Sequence number of record
Word 2	(G\$RTNM)	Relative tape number
Word 3	(G\$FLAG)	Flass
Word 4	(G\$CHK)	Checksum of record
Word 5	(G\$SIZ)	Number of words used as data
Word 6	(G\$LND)	Number of words to skip before data starts
Word 13	(G\$CUSW)	Customer word
Word 14	(S\$DATE)	Universal Date and Time
Word 15	(S\$FMT)	Format version (BKFMT)
Word 16	(S\$BVER)	Backup version (.JBVER)
Word 17	(S\$MON)	%CNMNT monitor type
Word 20	(S\$SVER)	%CNDVN system version
Word 21	(S\$APR)	Processor serial number (integer)
Word 22	(S\$DEV)	SIXBIT device written by
Word 23	(S\$MTCH)	Tracks; density
Word 24	(S\$RLNM)	SIXBIT reel-id
Word 25	(S\$LBLT)	Octal label type
Word 37	(S\$CUSW)	Customer Word

# 4.4.3 T\$UFD Record

This record contains the information needed to re-create a .UFD. This record is not written in Interchanse format. When written, the data portion contains two or three non-data blocks: types O\$NAME, O\$FILE (optional) and O\$DIRT in the data section.

Word	Name	Contents
Word O	(G\$TYPE)	Record Type
Word 1	(G\$SEQ)	Sequence number of record
Word 2	(G\$RTNM)	Relative tare number
Word 3	(G\$FLAG)	Flass (none)
Word 4	(G\$CHK)	Checksum of record
Word 5	(G\$SIZ)	Number of words used as data
Word 6	(G\$LND)	Number of words to skip before data starts
Word 13	(G\$CUSW)	Customer word
Word 14	(D\$PCHK)	Path Checksum
Word 15	(D\$LVL)	UFD level (O=UFD, 1= first SFD, etc)
Word 16	(D\$STR)	File structure name
Word 37	(D\$CUSW)	Customer word

### 4.4.4 T\$FIL Record

This record contains file data. On the first record, an O\$NAME and an O\$FILE information block is written. File data is put in the first record only if all of the file contents will fit in the block, otherwise file data starts with the next (second) record.

Word	Name	Contents
Word O	(G\$TYPE)	Record Type
Word 1	(G\$SEQ)	Sequence number of record
Word 2	(G\$RTNM)	Relative tape number
Word 3	(G\$FLAG)	Flags
Word 4	(G\$CHK)	Checksum of record
Word 5	(G\$SIZ)	Used only in first data record
Word 6	(G\$LND)	Used only in first data record
Word 13	(G\$CUSW)	Customer word
Word 14	(F\$PCHK)	Path checksum of file
Word 15	(F\$RDW)	Relative data word
Word 16	(F\$PTH)	12 word block for path info
Word 37	(F\$CUSW)	Customer word

### 5.0 Dumper Tape Formats

Dumper has two distinctly different record formats. One is the mode that Dumper ordinarily uses by default, and the second is used for INTERCHANGE mode.

Although Dumper uses only two different types of record formats, it will use different types of hardware data modes within those records. The INDUSTRY compatible switch will change the hardware mode from the standard unbuffered dump mode to industry compatible mode as defined in the TOPS-20 Monitor Calls Reference Guide.

#### 5.1 Standard Dumper Format

Each physical record of the tape is 518(10) words long. The first 6 words contain the checksum, access, tape number, page number, type of record, and sequence number of the record. The remaining 512(10) words of the record contains either 1 page of disk data or information related to the type of record being written.

The following block description is pulled out of the source code of Dumper.

FORMAT OF DUMPER TAPES

Each physical record written by Dumper contains one or more logical records, each of which 518 (1006 octal) words long.

Each logical record has the following format:

CHKSUM	0!	CHECKSUM OF ENTIRE 518-WORD RECORD	: ! !
ACCESS	1	PAGE ACCESS BITS (CURRENTLY NOT USED)	!
TAPNO	1 iscD!	SAVESET SOUMBER 17! TAPE SOUMBER 35	!
PAGNO	3   F1   F2	FILE WIN SET J! PAGE MON FILE 34	· ·
TYP	4!	RECORD TYPE CODE (NEGATED)	: ! 1
SEQ	6	RECORD SEQUENCE NUMBER (INCREASES BY 1)	: ! == !
	!	CONTENTS OF FILE PAGE IF DATA RECORD	; !
	:	OTHER TYPES HAVE OTHER INFORMATION HERE	!
	:		: :=:!

**** **** ****	*** *** *** ***	100 900 900 900 007 000 007
DATA	0	Contents of file rase
TPHD	1	Non-continued saveset header
FLHD	2	File header (contains filespec, FDB)
FLTR	3	File trailer
TPTR	4	Tape trailer (occurs only after last saveset)
USR	5	User directory information
CTPH	6	Continued saveset header
FILL	7	No meaning, used for padding

SCD (3 bits)

O=Normal save 1=Collection 2=Archive 3=Migration

F1	F2	Meanins
	****	med sero cone clin cold from least
0	0	Old-format tape (no file # in FAGNO bits 2-17)
1	1	Old-format tape, continued file
0	1	New-format tare (file # in PAGNO bits 2-17)
1	0	New-format tape, continued file
1	1	

Lift if=7F1, file#isvally
Continuel
File

A Dumper tape is a collection of records organized in the following fashion:

HEADER FOR FIRST SAVESET (TPHD)  USER INFO (USR) OR FILE (SEE BELOW)  USER INFO OR FILE  HEADER FOR SECOND SAVESET (TPHD)  USER INFO (USR) OR FILE (SEE BELOW)  USER INFO OR FILE  SUBSEQUENT SAVESETS  LAST SAVESET  TAPE TRAILER (TPTR)	
USER INFO OR FILE  HEADER FOR SECOND SAVESET (TPHD)  USER INFO (USR) OR FILE (SEE BELOW)  USER INFO OR FILE  SUBSEQUENT SAVESETS  LAST SAVESET  TAPE TRAILER (TPTR)	! HEADER FOR FIRST SAVESET (TPHD) !
HEADER FOR SECOND SAVESET (TPHD)  USER INFO (USR) OR FILE (SEE BELOW)  USER INFO OR FILE  SUBSEQUENT SAVESETS  LAST SAVESET  TAPE TRAILER (TPTR)	USER INFO (USR) OR FILE (SEE BELOW)
USER INFO (USR) OR FILE (SEE BELOW)  USER INFO OR FILE  USER INFO OR FILE  SUBSEQUENT SAVESETS  LAST SAVESET  TAPE TRAILER (TPTR)	USER INFO OR FILE
USER INFO (USR) OR FILE (SEE BELOW)  USER INFO OR FILE  USER INFO OR FILE  SUBSEQUENT SAVESETS  LAST SAVESET  TAPE TRAILER (TPTR)	: !
USER INFO (USR) OR FILE (SEE BELOW)  USER INFO OR FILE  USER INFO OR FILE  SUBSEQUENT SAVESETS  LAST SAVESET  TAPE TRAILER (TPTR)	: ! !
USER INFO OR FILE	! HEADER FOR SECOND SAVESET (TPHD) !
	USER INFO (USR) OR FILE (SEE BELOW)
!	USER INFO OR FILE
! ! LAST SAVESET ! ! TAPE TRAILER (TPTR)	· ! !
! ! LAST SAVESET ! ! ! TAPE TRAILER (TPTR)	· ! !==================================
! TAPE TRAILER (TPTR)	SUBSEQUENT SAVESETS
! TAPE TRAILER (TPTR)	!
! TAPE TRAILER (TPTR)	! LAST SAVESET !
	! TAPE TRAILER (TPTR)

#### Notes:

- 1. On labeled tames, the TPTR record appears only if the saveset is continued on another tame.
- Solitary tape marks (EOF's) are isnored on input.
   Two consecutive tape marks are interpreted as TPTR.
- 3. On labeled tapes, each saveset occupies exactly one file.
- 4. The first record of a continued saveset is CTPH instead of TPHD.

A disk file saved on a Dumper tape always has this sequence of records:

!		
į	FILE HEADER (FLHD)	!
!		
į	DATA RECORD: 1 PAGE OF FILE (DATA)	
	DATA RECORD: 1 PAGE OF FILE (DATA)	!
		ļ
	• !	ļ
	,	!
į	<b>.</b>	į
	NO 100 100 100 100 100 100 100 100 100 10	ļ
	FILE TRAILER (FLTR)	į
;		ļ

# 5.1.1 Types of Physical Records

There are eight types of records that Dumper can write to tape

TYP	Name	Contents
0	DATA	1 page of disk data
1	TPHD	Saveset Header
2	FLHD	File Header
3	FLTR	File Trailer
4	TPTR	Tape Trailer (after last saveset)
5	USR	User-Directory Information
6	CTPH	Continuation Header
7	FILL	Paddins

# 5.1.2 Data Record (record type 0)

A DATA record contains the following information.

Word		Location	Contents
Word	0	CHKSUM	Checksum of record
Word	1	ACCESS	(not used)
Word	2	TAPNO	Relative Tare Number
Word	3	PAGNO	Pase Number in File
Word	4	TYP	Record Type Code (nesated) [0]
Word	5	SEQ	Record Sequence Number
Word	6-10	05	One page of disk file data

# 5.1.3 Saveset Header (record type 1)

The Saveset Header contains the name of the saveset as siven with the SSNAME command, the current tape format number and the date and time. The current record format for Dumper is 4 as defined by CURFMT. The date and time are in the universal date and time format. This record is the first record of every saveset.

Word	Location	Contents			
	CHKSUM ACCESS TAPNO PAGNO TYP SEQ BFMSGV BGNTAI	Checksum of record (not used) Relative Tape Number Pase Number in File Record Type Code (nesated) [-1] Record Sequence Number 3 Universal date and time Saveset name, ASCIZ string	6	Record	forma

BFMSGP | - PTR to SSNUME BF + MD 2 - UST of Sche BFMSG 3 - SSNUME

### 5.1.4 File Header (record type 2)

The file header record contains the ASCII name of the file as well as the contents of that file's FDB. This record is the first record of every file.

Word	Location	Contents	
	CHKSUM ACCESS TAPNO PAGNO TYP SEQ	Checksum of record (not used) Relative Tape Number Pase Number in File Record Tupe Code (nesated) [-2] Record Sequence Number ASCII file name of the form:	FHNaW=0
Word 20 <b>\$</b> 6	str: <dir>FDB</dir>	file.ext.sen;P(protection);A(account) 30g words of files FDB starting at word 0 10g words, ASCII author string 10g words, ASCII last writer string 6gwords containing archive information	FHFDB=200

The FDB is broken up when stored. Only the first 30 words are stored in their original continuous form. The words for the author and last writer strings contain offsets to the 10 word blocks where the ASCIZ strings are actually stored. Finally the last 6 words of the FDB, which contains archive information, is stored in the same order as in the FDB. This became split because archiving and extending FDBs were added in version 4 of TOPS-20. You will find the FDB stored in this "broken-up" fashion in other Dumper tape records as well.

# 5.1.5 File Trailer (record type 3)

The File Trailer record contains the FDB of the file. This record is the last record written for every file.

Word	Location	Contents
Word O	CHKSUM	Checksum of record
Word 1	ACCESS	(not used)
Word 2	TAPNO	Relative Tape Number
Word 3	PAGNO	Pase Number in File
Word 4	TYP	Record Type Code (nesated) [-3]
Word 5	SEQ	Record Sequence Number
Word 6	FDB	30 words of files FDB starting at word 0
		10 words, ASCII author string
		10 words, ASCII last writer string
		6 words containing archive information

# 5.1.6 Tape Trailer (record type 4)

This record is the same in format as the File Trailer record. This record is written only at the end of the last saveset written to tape. There is no saveset trailer record for every saveset as there is in Backup on TOPS-10.

Word	Location	Contents
Word 0 Word 1 Word 2 Word 3 Word 4 Word 5 Word 6	CHKSUM ACCESS TAPNO PAGNO TYP SEQ FDB	Checksum of record (not used) Relative Tape Number Pase Number in File Record Type Code (nesated) [-4] Record Sequence Number 30 words of files FDB starting at word 0 10 words, ASCII author string 10 words, ascii last writer string
		6 words containing archive information

# 5.1.7 User-directory Information (record type 5)

This record contains all the needed information to rebuild a user's directory. This information is set up to be taken as the argument block to the CRDIR jsys. See the CRDIR jsys for a more detailed explanation of the values contained in the argument block.

This record appears on the tape before the first file saved in that directors. User-directors information can only be saved by privlesed users (WHEEL or OPERATOR) with their capabilities enabled.

Word	Location	Contents	
Word 0 Word 1 Word 3 Word 4 Word 5 Word 6 Word 7 Word 10 Word 11 Word 12 Word 13 Word 14 Word 15	CHKSUM ACCESS TAPNO PAGNO TYP SEQ	Checksum of record (not used) Relative Tape Number Pase Number in File Record Type Code (nesated) [-5] Record Sequence Number Lensth of arsument block (20) Password Pointer (offset) Workins disk Quota (octal) Capabilities mode word Pernament disk quota (octal) Directory number (octal)	
Word 16 Word 20 Word 21 Word 22 Word 23 Word 25 Word 65 Word 105 Word 205 Word 605		n, directory protection Default Number of generations to keep Date of last login (universal) Address (offset) to user group list Address (offset) to directory group list Maximum number of Sub-directories Address (offset) of user group list Byte pointer to default account string Password Account string User group list Directory Group list User group list	UH Neuma PSW: Par Club Lew Club Club Club
			c D SG

UHNOME 40 Nue String
PSW=60 PW "

ACT 100 HECT

Clock 200 Usergrap Lawgrh

COUG 200 Usergrap

COUG 400 DIR Grass

COSG 600 Subscript

# 5.1.8 Continuation Header (record type 6)

This record is the same in format as the Saveset Header record. This header is written only when a saveset must be continued from the end of one reel onto another.

Word		Location	Contents
Word	0	CHKSUM	Checksum of record
Word	1	ACCESS	(not used)
Word	2	TAPNO	Relative Tape Number
Word	3	PAGNO	Page Number in File
Word	4	TYP	Record Type Code (nesated)[-6]
Word	5	SEQ	Record Sequence Number
Word	6	BFMSG	3
Word	7	BGNTAD	Universal date and time
Word	10	SSNBUF	Saveset name, ASCIZ string

#### 5.2 Interchange Format Dumper Tapes

Interchanse tapes were originally supported to take information from a DECsystem-10 to a DECSYSTEM-20. However, it is commonly used as a means of transporting files, via tape, to either system. Dumper attempts to copy the Interchange format as defined in Backup. There are some system dependencies such as the existence of end of file marks between savesets that cause glitches in the exchange of tapes.

Dumper makes up a tape record as if it were writting an ordinary Dumper tape, and at the last minute, converts that record into the equivalent Backup Interchanse record. Dumper determines the maximum buffer length by taking the largest header it knows about (Interchanse mode, 32(10)) and adds a page plus one to it ( 512(10) 1). So when Dumper goes off and creats Interchange records, it doesn't have to expand the buffer space in the program, it just keeps shuffling things down to the end.

Dumper does not fill all of the fields that Backup does in Interchange formats. Items such as the physical device the tape was written on and the CPU number of the system used are missing.

In the following record descriptions, all the words are named. The contents of those words are written by Dumper only if something is mentioned in the "Contents" field of a line.

The records are described in order as if there were "ordinary" Dumper records (ie. record type O through 7). The description which follows is the end-result of Dumper's effort of converting the "ordinary" record into an Interchange record.

Dumper always sets the GF\$NCH (ignore checksum) bit of the G\$FLAG word, and then (of course) proceeds to put the checksum from the -20 into the G\$CHK word anyways.

# 5.2.1 Interchange Data Record (record type 0)

This record starts out as a normal data record. This record is analasous to a T\$FIL record as written by Backup.

Word		Name	Contents
Word	0	(G\$TYPE)	Record Tupe
Word	1	(G\$SEQ)	Record sequence Number
Word	2	(G\$RTNM)	Relative Tape Number
Word	3	(G\$FLAG)	GF\$EOF!GF\$NCH
Word	4	(G\$CHK)	Checksum (isnored)
Word	5	(G\$SIZ)	ICOLEN
Word	6	(G\$LND)	
Word	13	(G\$CUSW)	Customer Word
Word	14	(F\$PCHK)	
Word	15	(F\$RDW)	Relative Block Number
Word	16	(F\$PTH)	
Word	37	(F\$CUSW)	Customer Word
Word	40		Data

# 5.2.2 Interchange Tape Header (record type 1)

This Saveset header is stored in this record. This is analogous to a T\$BEG record in Backup.

Word	Name	Contents
Word 0	(G\$TYPE)	Record Tupe
Word 1	(G\$SEQ)	Record sequence Number
Word 2	(G\$RTNM)	Relative Tape Number
Word 3	(G\$FLAG)	GF\$NCH
Word 4	(G\$CHK)	Checksum (ignored)
Word 5	(G\$SIZ)	
Word 6	(G\$LND)	Word count of saveset name
Word 13	(G\$CUSW)	Customer Word
Word 14	(S\$DATE)	Universal Date and Time
Word 15	(S\$FMT)	BKFMT (1)
Word 16	(S\$BVER)	expected but not provided
Word 17	(S\$MON)	expected but not provided
Word 20	(S\$SVER)	expected but not provided
Word 21	(S\$APR)	expected but not provided
Word 22	(S\$DEV)	
Word 23	(S\$MTCH)	
Word 24	(S\$RLNM)	
Word 25	(S\$LBLT)	
Word 37	(S\$CUSW)	
Word 40	(D\$SSNM)	5,,word count of saveset name
Word 41		Saveset name, ASCIZ strins

### 5.2.3 Interchanse File Header (record type 2)

The file header record in Interchanse mode contains only system independent data about the file. This record is analosous to a T\$FIL record in Backup.

Word		Name	Contents
######################################	0 1 2 3 4 5 6 1 3 1 4 1 5 1 6 7 0 2 4 1 2 4 2 4 3 4 5 4 5 6 6 1 7 6 7 6 7 6 7 7 8 7 8 7 8 7 8 7 8 7 8 7	Name (G\$TYPE) (G\$SEQ) (G\$SENM) (G\$SELND) (G\$SIZ) (G\$SLND) (G\$SLND) (F\$PDW) (F\$PDW) (F\$PDW) (F\$PDW) (F\$PDW) (F\$PLSNAME) (A\$FLLS) (A\$HLDS) (A\$HLDS) (A\$HLDS) (A\$HLDS)	Contents  Record Type Record sequence Number Relative Tape Number GF\$NCH!GF\$SOF Checksum (isnored)  F\$NND (400) Customer Word  1,,200 2,,200 LN\$AFH (32) not used .FBWRT of FDB ICOLEN .DMIMG .FBSIZ of FDB
Word Word	247 250	(A\$BSIZ) (A\$VERS)	

The O\$NAME and O\$FILE blocks always appear in the same place in the same order. Dumper hardwires the lengths and the offsets of these blocks and lets monitor calls like SOUT terminate on the null at the end of the string.

### 5.2.4 Interchange File Trailer (record type 3)

The standard Dumper File Trailer has no counterpart in Backup. The end of file in Interchanse mode is determined by the GF\$EOF flas in the G\$FLAG word of a T\$FIL record.

# 5.2.5 Interchanse Tape Trailer (record type 4)

The tape trailer for Dumper Interchanse contains the saveset name. This generates a T\$END record.

Word		Name	Contents
Word	0	(G\$TYPE)	Record Type
	1	(G\$SEQ)	Record sequence Number
Word	2	(G\$RTNM)	Relative Tare Number
Word	3	(G\$FLAG)	GF\$NCH
Word	4	(G\$CHK)	Checksum (isnored)
Word	5	(G\$SIZ)	
Word	6	(G\$LND)	Length of Saveset Name
Word	13	(G\$CUSW)	Customer Word
Word	14	(S\$DATE)	Universal Date and Time
Word	15	(S\$FMT)	BKFMT (1)
Word	16	(S\$BVER)	expected but not provided
Word	17	(S\$MON)	expected but not provided
Word	20	(S\$SVER)	expected but not provided
Word	21	(S\$APR)	expected but not provided
Word	22	(S\$DEV)	
Word	23	(S\$MTCH)	
Word	24	(S\$RLNM)	
Word	25	(S\$LBLT)	
Word	37	(S\$CUSW)	
Word	40	(O\$SSNM)	5,,word count of saveset name
Word	41		Saveset name, ASCIZ strins

# 5.2.6 Interchanse User Information (record type 5)

This record is not written because it contains system dependent information.

# 5.2.7 Interchanse Continuation Header (record type 6)

This record is written on an Interchanse tape. It is analasous to a T\$CON record in Backup.

Word		Name	Contents
Word	٥	(G\$TYPE)	Record Type
Word	1	(G\$SEQ)	Record sequence Number
Word	2	(G\$RTNM)	Relative Tape Number
Word	3	(G\$FLAG)	GF\$NCH
Word	4	(G\$CHK)	Checksum (isnored)
Word	5	(G\$SIZ)	
Word	6	(G\$LND)	Length of Saveset Name
Word	13	(G\$CUSW)	Customer Word
Word	14	(F\$PCHK)	
Word	15	(F\$RDW)	Relative Block Number
Word	16	(F\$PTH)	
Word	37	(F\$CUSW)	Customer Word
Word	40	(O\$SSNM)	5,,words in saveset name
Word	41		Saveset name, ASCIZ string

# 5.2.8 Interchange Filler (record type 7)

This record type has no counterpart in Interchanse mode.