

DILOG

Model DQ60X

SEAGATE ST506 INTERFACE COMPATIBLE WINCHESTER DISC CONTROLLER

DEC LSI-11 COMPATIBLE

FEATURES


- Interfaces LSI-11, 11/2 and 11/23 computers to the Seagate Technology ST506 or interface compatible disc drives.
- Emulates DEC RK05, RL01/RL02 or RP02/RP03 software drivers in RT-11 and RSX-11 software systems.
- Low cost microprocessor based intelligent controller, completely contained on one quad printed circuit card.
- Automatic media flaw compensation with bad-sector flagging and transparent, automatic, track-skipping feature.
- Automatic retry on read errors.
- Full sector data buffer for elimination of Q-BUS data late errors due to DMA latency.
- On-board bootstrap loader for RK05, RL01/RL02 or RP02/RP03 and TM-11 support, with jumper selectable bootstrap address selection.
- Automatic self-test with status indicator and data protect feature.
- Multiple sector transfer to 64K words.
- Memory addressing capability to 128K words.
- Automatic power fail/power down protection.
- Low power consumption, less than 3.5 amps @ 5 volts.

DESCRIPTION

The Distributed Logic Corporation (DILOG) Model DQ601 (RK05 emulation), DQ604 (RL01/RL02 emulation) Disc Controller interfaces up to two Seagate Technology ST506 or interface compatible disc drives to a DEC LSI-11, 11/2 or 11/23 based computer system. The controller runs under the RT-11 and RSX operating software systems using the standard DEC RK05 or RL01 drivers.

The Model DQ60X controllers are microprocessor based, and implemented on a single quad board which plugs into and requires one slot in any LSI-11 compatible backplane. On-board firmware provides such features as automatic media flaw compensation and write protect features.

A complete disc subsystem is comprised of the controller, one or more disc drives, and the necessary interconnecting ribbon cables. No specially wired connectors, additional formatting circuitry, bus converters, chassis or power supply are required for the controller to function. The single quad printed circuit board contains all necessary disc drive and Q-BUS interfaces, in addition to all formatting and control functions.



DISC DRIVE COMPATIBILITY

The Model DQ60X can interface up to two Seagate Technology ST506 or interface compatible disc drives. With drives available from some manufacturers, increased capacities over and above those allowed for by the DEC RK05 (DQ601) or RL01/RL02 (DQ604) disc driver software are optionally available.

SOFTWARE SUPPORT

The Model DQ60X will run the standard DEC RK05 (DQ601) or RL01/RL02 (DQ604) drivers (or modified drivers for increased capacity) in RT-11 and RSX-11 software systems. A format diagnostic routine is supplied with each unit. The factory should be contacted for special drivers requiring different logical unit sizing.

MEDIA FLAW COMPENSATION

The Model DQ60X comes with two methods of providing for prevention of data errors caused by media flaws. The first is bad sector mapping when formatting the disc. The second is automatic flawed media compensation, built into the firmware, which causes a transparent track-skipping function to be implemented whenever a hard error is detected on a given track. Soft errors are compensated for by an automatic read retry function.

HARDWARE BOOTSTRAP

The Model DQ60X contains an on-board hardware bootstrap loader for RK05 (DQ601), or RL01/RL02 (DQ604), and TM-11 mag tape support. On-board jumpers allow you to select one of two bootstrap addresses, in addition to enabling/disabling of the bootstrap. When the bootstrap is disabled, the Model DQ60X will boot from the standard DEC bootboard.

AUTOMATIC SELF-TEST FEATURE

The Model DQ60X is supplied with an Automatic Self-Test Feature, which causes on-board microdiagnostics to be run on the controller each time the Q-BUS is initialized. A green card-edge LED indicator is lit after each successful completion of the microdiagnostics. Should the microdiagnostics fail, the LED indicator is extinguished, and a data protect feature is invoked which disallows any communications between the CPU and the disc, thus protecting critical data base areas from the overwriting of erroneous information.

MODE CONTROL SWITCHES

The Model DQ60X contains on-board jumpers and switches for selection of starting bootstrap address, bootstrap enable/disable and disc mapping control.

FULL SYSTEM SUPPORT

Distributed Logic Corporation also supplies fully integrated and tested disc systems, including the discs themselves. For the customer that wishes to purchase drives directly from the manufacturer, they can be drop-shipped to our facility where they will be integrated, tested, and shipped as a complete system with the Model DQ60X.

DOCUMENTATION

Each Model DQ60X is supplied with an Instruction Manual.

OPTIONS

Disc drive I/O Cables • Disc Drives • Factory integration of customer-supplied drives.

CONTROLLER SPECIFICATIONS

Mechanical—The Model DQ60X is completely contained on one quad module 10.44 inches wide by 8.88 inches deep, and plugs into and requires one slot in any DEC LSI-11 based system quad backplane.

Computer I/O

Register Addresses (PROM selectable)

Factory set at:	DQ601	DQ604
— Drive Status	(RKDS) 777 400	N/A
— Error Register	(RKER) 777 402	N/A
— Control Status	(RKCS) 777 404	(CS) 774 400
— Word Count	(RKWC) 777 406	N/A
— Current Bus Address	(RKBA) 777 410	(BA) 774 402
— Disc Address	(RKDA) 777 412	(DA) 774 404
— Data Buffer	(RKDB) 777 416	N/A
— Multipurpose	N/A	(MP) 774 406
— Maximum Block Size Per Transfer	64K Words	5K Words
— Interrupt Vector Address	222	330
Priority Level	BR5	BR5

Data Transfer

- Method DMA

Bus Load

- 1 std unit load

Address Ranges

- Disc Drive: 20 megabytes (DQ601) or 40 megabytes (DQ604)
- Computer memory to 128K words

Disc Drive I/O

- one 34 pin and two 20 pin flat ribbon connectors mounted on outer edge of controller module.

Signal—Seagate Technology ST506 compatible.

Power— +5 volts @ 3.5 amps from computer power supply.

Environment—Operating temperature 40°F. to 140°F., humidity 10-95% non-condensing.

Shipping Weight—5 pounds, includes documentation and cables.

†Specifications subject to change without notice.

**DISTRIBUTED
LOGIC CORP.**



12800-G Garden Grove Blvd.
Garden Grove, CA 92643
Phone: (714) 534-8950
Telex: 681 399 DILOG GGVE

