








**Systems Reference Library**

**IBM System/360 Operating System  
Assembler [F] Programmer's Guide**

**Program Number 360S-AS-037**

This publication complements the IBM System/360 Operating System Assembler Language publication. It provides a guide to program assembling, linkage editing, executing, interpreting listings, assembler programming considerations, diagnostic messages, and object output cards.



## PREFACE

This publication is oriented to the F level assembler program (the assembler) functioning in the IBM System/360 Operating System (Primary Control Program, MFT, and MVT).

This publication is divided into an introduction and four sections which describe the following:

1. Assembler options and data set requirements.
2. Use of IBM-provided cataloged procedures for assembling; assembling and linkage editing; assembling, linkage editing, and executing assembler language source programs.
3. Use and interpretation of the assembler listing.
4. Programming considerations.

In addition, the appendixes provide a list and explanation of diagnostic messages, a description of object output cards, and a sample program listing.

Other System Reference Library publications in the IBM System/360 Operating System series provide fuller, more detailed discussions of the topics introduced in this publication: a careful reading of the publication IBM System/360 Operating System: Concepts and Facilities, Form C28-6535, is recommended. Knowledge of the assembler language is assumed. Where appropriate, the reader is directed to the following publications:

IBM System/360 Operating System: Job Control Language (Form C28-6539)

IBM System/360 Operating System: Storage Estimates (Form C28-6551)

IBM System/360 Operating System: Linkage Editor (Form C28-6538)

IBM System/360 Operating System: Supervisor and Data Management Services (Form C28-6646)

IBM System/360 Operating System: Supervisor and Data Management Macro-Instructions (Form C28-6647)

IBM System/360 Operating System: TESTRAN (Form C28-6648)

IBM System/360 Operating System: Messages, Completion Codes, and Storage Dumps (Form C28-6631)

IBM System/360 Operating System: Assembler Language (Form C28-6514)

IBM System/360 Operating System: Utilities (Form C28-6586)

IBM System/360 Operating System: FORTRAN IV (E), Library Subprograms (Form C28-6596)

IBM System/360 Operating System: System Programmer's Guide (Form C28-6550)

IBM System/360 Operating System: FORTRAN IV (E) Programmer's Guide (Form C28-6603)

IBM System/360 Operating System: COBOL (E) Programmer's Guide (Form C24-5029)

References to these publications are usually by a short title, e.g., Linkage Editor or Data Management Services.

### Third Edition

This is a major revision of, and obsoletes, C26-3756-1. Changes are designated as follows:

1. A vertical line appears to the left of affected text where only a part of the page has been changed.
2. A dot (•) appears to the left of the page number of a page that has been changed throughout.
3. A dot appears to the left of the title of a changed illustration.

The major changes in this publication are concerned with the inclusion of the cataloged procedures necessary to support the MVT Control Program (Option 4) of the Operating System.

Specifications contained herein are subject to change from time to time. Any such changes will be reported in subsequent revisions or Technical Newsletters.

Requests for copies of IBM publications should be made to your IBM representative or to the IBM branch office serving your locality.

Address comments concerning the contents of the publication to IBM Corporation, Programming Publications Dept. 232, San Jose, California 95114

CONTENTS

INTRODUCTION . . . . .	1	PROGRAMMING CONSIDERATIONS . . . . .	15
ASSEMBLER OPTIONS AND DATA SET		Saving and Restoring General	
REQUIREMENTS . . . . .	2	Register Contents . . . . .	15
Assembler Options . . . . .	2	Program Termination . . . . .	15
Assembler Data Set Requirements . . . . .	2	PARM Field Access . . . . .	15
Ddname SYSUT1, SYSUT2, SYSUT3. . . . .	3	Macro-Definition Library Additions. . . . .	15
Ddname SYSIN . . . . .	3	Load Module Modification - Entry	
Ddname SYSLIB. . . . .	3	Point Restatement. . . . .	16
Ddname SYSPRINT. . . . .	3	Object Module Linkage . . . . .	16
Ddname SYSPUNCH. . . . .	3	Dictionary Size and Source Statement	
Ddname SYSGO . . . . .	3	Complexity . . . . .	16
Defining Data Set Characteristics . . . . .	3	Dictionaries Used in Conditional	
Return Codes. . . . .	5	Assembly and Macro Instruction	
CATALOGED PROCEDURES. . . . .	6	Expansion. . . . .	17
Cataloged Procedure for Assembly		Global Dictionary at Collection	
(ASMFC). . . . .	6	Time. . . . .	18
Cataloged Procedure for Assembly and		Local Dictionaries at Collection	
Linkage Editing (ASMFCLE) . . . . .	7	Time. . . . .	18
Cataloged Procedure for Assembly,		Global Dictionary at Generation	
Linkage-Editing, and Execution		Time. . . . .	18
(ASMFCLE) . . . . .	8	Local Dictionaries at Generation	
Overriding Statements in Cataloged		Time. . . . .	19
Procedures . . . . .	9	Additional Dictionary Requirements . . . . .	19
EXEC Statements. . . . .	9	Source Statement Complexity . . . . .	19
DD Statements. . . . .	9	Macro Generation and Conditional	
Examples . . . . .	9	Assembly Limitation . . . . .	20
ASSEMBLER LISTING . . . . .	10	Assembler Portion Limitations. . . . .	20
External Symbol Dictionary (ESD). . . . .	10	APPENDIX A.  DIAGNOSTIC MESSAGES. . . . .	21
Source and Object Program . . . . .	12	APPENDIX B.  OBJECT DECK OUTPUT . . . . .	29
Relocation Dictionary . . . . .	13	APPENDIX C.  ASSEMBLER F PROGRAM LISTING	32
Cross Reference . . . . .	13	APPENDIX D.  DYNAMIC INVOCATION OF THE	
Diagnostics . . . . .	14	ASSEMBLER . . . . .	41
		INDEX . . . . .	43

ILLUSTRATIONS

Figures

Figure 1.	Cataloged Procedure for Assembly (ASMFC) . . . . .	6	Assembly, Linkage Editing, and Execution (ASMFCCLG) . . . . .	8	
Figure 2.	Cataloged Procedure for Assembling and Linkage Editing (ASMFCLE) . . . . .	7	Figure 4.	Assembler Listing . . . . .	11
Figure 3.	Cataloged Procedure for		Figure 5.	Linkage Statements . . . . .	17
			Figure 6.	TESTRAN SYM Card Format . . . . .	31

Tables

Table 1.	Data Set Characteristics . . . . .	4	Table 7.	Collection Time . . . . .	18
Table 2.	Return Codes . . . . .	5	Table 8.	Global Dictionary Entries at Generation Time . . . . .	19
Table 3.	Device Naming Conventions . . . . .	6	Table 9.	Local Dictionary Entries at Generation Time . . . . .	19
Table 4.	Types of ESD Entries . . . . .	10	Table 9.	Macro Definition Local Dictionary Parameter Table . . . . .	19
Table 5.	Global Dictionary Entries at Collection Time . . . . .	18			
Table 6.	Local Dictionary Entries at				

Through the medium of job control statements, the programmer specifies job requirements directly to the operating system, thus eliminating many of the functions previously performed by the operating personnel. The job consists of one or more job steps. For example, the job of assembling, linkage-editing, and executing a source program involves three job steps:

1. Translating the source program, i.e., executing the assembler component of the operating system to produce an object module.
2. Processing the output of the assembler, i.e., executing the linkage-editor component of the operating system to produce a load module.
3. Executing the assembled and linkage-edited program, i.e., executing the load module.

A procedure is a sequence of job control language statements specifying a job. Procedures may enter the system via the input stream or from a library of procedures,

which are previously defined and contained in a procedure library. The input stream is the flow of job control statements and, optionally, input data entering the system from one input device. At the sequential scheduling system level of the operating system, only one input stream may exist at a time. (For a description of the operating system environment see IBM System/360 Operating System: Concepts and Facilities.)

The job definition (JOB), execute (EXEC), data definition (DD), and delimiter (/\*) job control statements are shown in this publication as they are used to specify assembler processing. Detailed explanations of these statements are given in IBM System/360 Operating System: Job Control Language.

Operating system factors influencing program preparation, such as terminating the program, saving and restoring general registers, and linking of independently produced object modules, are discussed in Programming Considerations, as are guides to determine whether assembler dictionary sizes and complexity limitations of source statements will be exceeded.

## ASSEMBLER OPTIONS AND DATA SET REQUIREMENTS

### ASSEMBLER OPTIONS

The programmer may specify the following assembler options in the PARM= field of the EXEC statement. They must appear between two apostrophes, separated by commas with no imbedded blanks. They can appear in any order and, if an entry is omitted, a standard setting will be assumed as shown below under Default Entry.

```
PARM= 'DECK LOAD, LIST TEST, XREF, RENT'  
      or or or or or LINECNT=nn, or  
      'NODECK,NOLOAD,NOLIST,NOTEST,NOXREF, NORENT'
```

These options are defined as follows:  
DECK -- The object module is placed on the device specified in the SYSPUNCH DD statement.  
LOAD -- The object module is placed on the device specified in the SYSGO DD statement.

NOTE: Specification of the parameter LOAD causes object output to be written on a data set with dname SYSGO. This action occurs independently of the output on SYSPUNCH caused by the parameter DECK. The output on SYSGO and SYSPUNCH is identical except that SYSPUNCH is closed with a disposition of LEAVE, and SYSGO is closed with a disposition of REREAD.

LIST -- An assembler listing is produced.  
TEST -- The object module contains the special source symbol table required by the test translator (TESTSTRAN) routine.  
XREF -- The assembler produces a cross-reference table of symbols as part of the listing.  
RENT -- The assembler checks for a possible coding violation of program re-entrability.

The prefix,NO, is used with the above options to indicate which options are not wanted. If contradictory options are entered, e.g., LIST, NOLIST, the rightmost option, NOLIST, is used.

LINECNT=nn This parameter specifies the number of lines to be printed between headings in the listing. The permissible range is 01 to 99 lines.

The following is an example of specifying assembler options:

```
EXEC PGM=IEUASM,PARM='LOAD,NODECK,TEST'
```

### DEFAULT ENTRY

If no options are specified the assembler assumes the following default entry:

```
PARM='NOLOAD,DECK,LIST,NOTEST,XREF,LINECNT=55,NORENT'
```

The cataloged procedures discussed in this guide assume the default entry. However, the programmer may override any or all of the default options (see Overriding Statements in Cataloged Procedures).

### ASSEMBLER DATA SET REQUIREMENTS

The assembler requires the following four data sets:

- SYSUT1, SYSUT2, SYSUT3 -- utility data sets used as intermediate external storage.
- SYSIN -- an input data set containing the source statements to be processed.

In addition to the above, four additional data sets may be required:

- SYSLIB -- a data set containing macro definitions (for macro definitions not defined in the source program) and/or source coding to be called for through COPY assembler instructions.
- SYSPRINT -- a data set containing output text for printing (unless NOLIST option is specified).
- SYSPUNCH -- a data set containing object module output usually for punching (unless NODECK option is specified).

- **SYSGO** -- a data set containing object module output usually for the linkage editor (only if LOAD option is specified).

The above data sets are described in the following text. The dname that must be used in the DD statement describing the data set appears as the heading for each description.

#### Ddnames SYSUT1, SYSUT2, SYSUT3

These utility data sets are used by the assembler as intermediate external storage devices when processing the source program. The input/output device(s) assigned to these data sets must be capable of sequential access to records. The assembler does not support multi-volume utility data sets. Refer to the Storage Estimate manual for the space required.

#### Ddname SYSIN

This data set contains the input to the assembler -- the source statements to be processed. The input/output device assigned to this data set may be either the device transmitting the input stream, or another sequential input device designated by the programmer. The DD statement describing this data set appears in the input stream. The IBM-supplied procedures do not contain this statement.

#### Ddname SYSLIB

From this data set, the assembler obtains macro definitions and assembler language statements to be called by the COPY assembler instruction. It is a partitioned data set and each macro definition or sequence of assembler statements is a separate member, with the member name being the macro instruction mnemonic or COPY code name. The data set may be defined as SYS1.MACLIB or a user's private macro definition or COPY library. SYS1.MACLIB contains macro definitions for the system macro instructions provided by IBM. A user's private library may be concatenated with SYS1.MACLIB. The two libraries must have the same attributes, i.e., the same blocking factors, block sizes, and record formats. The Job Control Language publication explains the concatenation of data sets.

#### Ddname SYSPRINT

This data set is used by the assembler to produce a listing. Output may be directed to a printer, magnetic tape, or DASD. The assembler uses the machine code carriage-control characters for this data set.

#### Ddname SYSPUNCH

The assembler uses this data set to produce the object module. The input/output unit assigned to this data set may be either a card punch or an intermediate storage device (capable of sequential access).

#### Ddname SYSGO

This is a DASD, magnetic tape, or card punch data set used by the assembler. It contains the same output text as SYSPUNCH. It is used as input for the linkage editor and may also be used as a punch device (see NOTE under Assembler Options).

### DEFINING DATA SET CHARACTERISTICS

Before a data set can be made available to a problem program, descriptive information defining the data set must be placed into a data control block for the access routines. Sources of information for the data control block are keyword operands in the DCB macro instruction or, in some cases, the DD statement, data set label, or user's problem program. General information concerning data set definition is contained in the Data Management Services manual (see Preface). Characteristics of data sets supplied by the DCB macro instruction are described in the Data Management Macro-Instructions manual (see Preface).

The specific information that must be supplied depends upon the data set organization and access method. The following access methods are used to process the assembler data sets:

<u>Access Method</u>	<u>Data Sets</u>
QSAM (Queued Sequential)	SYSPRINT, SYSPUNCH, SYSGO, SYSIN
BSAM (Basic Sequential)	SYSUT1, SYSUT2, SYSUT3
BPAM (Basic Partitioned)	SYSLIB

Table 1 summarizes the assembler capabilities and restrictions on record length

●Table 1. Data Set Characteristics

	SYSIN	SYSLIB	SYSPRINT	SYSPUNCH	SYSGO	SYSUT1 SYSUT2 SYSUT3
LRECL	Fixed at 80	Fixed at 80	Fixed at 121	Fixed at 80	Fixed at 80	N/A
RECFM ①	User must specify in LABEL or DD card F, FS, FBS, FB, FBST, FBT	User must specify in LABEL or DD card F, FS, FBS, FB, FBST, FBT	Set by assembler: if BLKSIZE=LRECL, RECFM=FSM; if BLKSIZE>LRECL, RECFM=FBSM	Set by assembler: if BLKSIZE=LRECL, RECFM=FS; if BLKSIZE>LRECL, RECFM=FBS	Set by assembler: if BLKSIZE=LRECL, RECFM=FS; if BLKSIZE>LRECL, RECFM=FBS	Fixed for U
BLKSIZE ②	User must specify in LABEL or DD card, must be a multiple of LRECL	User must specify in LABEL or DD card, must be a multiple of LRECL	Optional, but must be a multiple of LRECL; if omitted BLKSIZE=LRECL	Optional, but must be a multiple of LRECL; if omitted BLKSIZE=LRECL	Optional, but must be a multiple of LRECL; if omitted BLKSIZE=LRECL	User can not specify; maximum of 4000, minimum of 1739
BUFNO	Optional; if omitted 2 is used	Set by assembler to 1	Optional; if omitted 2 is used	Optional; if omitted 3 is used for unit record and 1 for other devices	Optional; if omitted 3 is used for unit record and 1 for other devices	User can not specify; either 1 or 2
For 44K availability	BLKSIZE times BUFNO can not be greater than 3600	BLKSIZE can not be greater than 3600	BLKSIZE times BUFNO can not be greater than 1210	BLKSIZE times BUFNO can not be greater than 400	BLKSIZE times BUFNO can not be greater than 400	
For calculating core requirements	L1 = BLKSIZE times BUFNO	L2 = BLKSIZE	L3 = BLKSIZE times BUFNO	L4 = BLKSIZE times BUFNO	L5 = BLKSIZE times BUFNO	
<p>③ Minimum core required for the assembler = <math>\left\{ \begin{array}{l} L_1 + L_2 + 37000 \\ L_3 + L_4 + L_5 + 37000 \end{array} \right\}</math>  whichever is greater</p> <p>③ Maximum core that the assembler can effectively use = <math>L_4 + L_5 + 535,000</math></p>						

- ① U = undefined, F = fixed length records, B = blocked records, S = standard blocks, T = track overflow, M = machine code carriage control
- ② Blocking is not allowed on unit record devices. Blocking on other direct access can not be greater than the track size unless T is specified on RECFM
- ③ For MVT environment add 5,000 for core required

and format, and blocksize and buffering facilities available to the user. The values shown in Table 1 are based upon the minimum core requirements of Assembler F (44K), which will allow a symbol table length of approximately 7000 bytes. If more than 44K is available, the block sizes and buffer numbers can be increased. However, if the user specifies a combination of blocking and buffering which does not leave room for the symbol table, abnormal termination of the task may occur (ABEND 804) when the assembler attempts to issue a GETMAIN macro instruction.

In addition to the data set characteristics shown in Table 1, the following options are available to the user (refer to the Supervisor and Data Management Macro-Instructions publication). Options not shown below are fixed by the assembler and cannot be specified.

<u>Data Sets</u>	<u>Options</u>
SYSIN, SYSPUNCH, SYSPRINT, SYSGO	DEVD (device type) BFALN (buffer boundary alignment) BUFL (buffer length) EROPT (error option)
SYSUT1, 2, 3	DEVD (device type) OPTCD (optional ser- vice for validity checking and chained scheduling)

#### RETURN CODES

Table 2 shows the return codes issued by the assembler for use with the COND= parameter of JOB or EXEC statements. The COND= parameter is explained in the Job Control Language publication.

The return code issued by the assembler is the highest severity code that is:

1. Associated with any error detected by the assembler (see Appendix A for diagnostic messages and severity codes).
2. Associated with MNOTE messages produced by macro instructions.
3. Associated with an unrecoverable I/O error occurring during the assembly.

If a permanent I/O error occurs on any of the assembler files or a DD card for a required data set is missing, a message is printed on the operator's console and an ABEND with a user ABEND code of 20 is given by the assembler. This terminates the assembly.

Table 2. Return Codes

Return Code	Explanation
0	No errors detected
4	Minor errors detected; successful program execution is probable
8	Errors detected; unsuccessful program execution is possible
12	Serious errors detected; unsuccessful program execution is probable
16	Critical errors detected; normal execution is impossible
20	Unrecoverable I/O error occurred during assembly or missing data sets; assembly terminated

CATALOGED PROCEDURES

This section describes three IBM-provided cataloged procedures: a procedure for assembling (ASMFC), a procedure for assembling and linkage editing (ASMFCL), and a procedure for assembling, linkage editing, and executing (ASMFCLG). The procedures rely on conventions regarding the naming of device classes. These conventions, shown in Table 3, must be incorporated into the system at system generation time.

Table 3. Device Naming Conventions.

Device Classname	Devices Assigned
SYSSQ	Any devices allowing sequential access to records for reading and writing
SYSDA	Direct-access devices
SYSCP	Card punches

To use cataloged procedures, EXEC statements naming the desired procedures are placed in the input stream following the JOB statement. Subsequently, the specified cataloged procedure is brought from a procedure library and merged into the input stream.

The System Programmer's Guide discusses the placing of procedures in the procedure library.

CATALOGED PROCEDURE FOR ASSEMBLY (ASMFC)

This procedure requests the operating system to load and execute the assembler. The name ASMFC must be used to call this procedure. The result of execution is an object module, in punched card form, and an assembler listing.

In the following example, input enters via the input stream. The statements entered in the input stream to use this procedure are:

```
//jobname      JOB
//stepname     EXEC PROC= ASMFC
//ASM.SYSIN   DD  *
               |
               | source program statements
               |
/* (delimiter statement)
```

The statements of the ASMFC procedure are brought from the procedure library and merged into the input stream.

Figure 1 shows the statements that make up the ASMFC procedure.

```
1 //ASM      EXEC PGM=IEUASM,REGION=50K
2 //SYSLIB   DD  DSNAME=SYS1.MACLIB,DISP=SHR
3 //SYSUT1   DD  UNIT=SYSSQ,SPACE=(1700,(400,50))
4 //SYSUT2   DD  UNIT=SYSSQ,SPACE=(1700,(400,50))
5 //SYSUT3   DD  UNIT=(SYSSQ,SEP=(SYSUT2,SYSUT1,SYSLIB)),
//           SPACE=(1700,(400,50))
6 //SYSPRINT DD  SYSOUT=A
7 //SYSPUNCH DD  SYSOUT=B
-----
-----
```

1 PARM= or COND= parameters may be added to this statement by the EXEC statement that calls the procedure (see Overriding Statements in Cataloged Procedures). The system name IEUASM identifies Assembler F.

2 This statement identifies the macro library data set. The data set name SYS1.MACLIB is an IBM designation.

3 4 5 These statements specify the assembler utility data sets. The device classname used here, SYSSQ, may represent a collection of tape drives, or direct-access units, or both. The I/O units assigned to this name are specified by the installation when the system is generated. A unit name, e.g., 2311 may be substituted for SYSSQ.

The SEP= subparameter in statement 5 and the SPACE= parameter in statements 3, 4, and 5 are effective only if the device assigned is a direct-access device; otherwise they are ignored. The space required is dependent on the make-up of the source program. The Job Control Language publication explains space allocation.

6 This statement defines the standard system output class, SYSOUT=A, as the destination for the assembler listing.

7 This statement describes the data set that will contain the object module produced by the assembler.

Figure 1. Cataloged Procedure for Assembly (ASMFC)




CATALOGED PROCEDURE FOR ASSEMBLY,  
LINKAGE-EDITING, AND EXECUTION  
(ASMFCLG)

This procedure consists of three job steps: assembling, linkage editing, and executing.

Figure 3 shows the statements that make up the ASMFCLG procedure. Only those statements not previously discussed are explained in the figure.

The name ASMFCLG must be used to call this procedure. Assembler and linkage editor listings are produced.

The statements entered in the input stream to use this procedure are:



//ASM	EXEC	PGM=IEUASM,PARM=LOAD,REGION=50K	
//SYSLIB	DD	DSNAME=SYS1.MACLIB,DISP=SHR	
//SYSUT1	DD	UNIT=SYSSQ,SPACE=(1700,(400,50))	
//SYSUT2	DD	UNIT=SYSSQ,SPACE=(1700,(400,50))	
//SYSUT3	DD	UNIT=(SYSSQ,SEP=(SYSUT2,SYSUT1,SYSLIB)),	X
//		SPACE=(1700,(400,50))	
//SYSPRINT	DD	SYSOUT = A	
//SYSPUNCH	DD	SYSOUT=B	
//SYSGO	DD	DSNAME=&LOADSET,UNIT=SYSSQ,SPACE=(80,(100,50)),	X
//		DISP=(MOD,PASS)	
<sup>1</sup> //LKED	EXEC	PGM=IEWL,PARM=(XREF,LET,LIST,NCAL),REGION=96K,	X
//		COND=(8,LT,ASM)	
//SYSLIN	DD	DSNAME=&LOADSET,DISP=(OLD,DELETE)	
//	DD	DDNAME=SYSIN	
<sup>2</sup> //SYSLMOD	DD	DSNAME=&GOSET(GO),UNIT=SYSDA,SPACE=(1024,(50,20,1)),	X
//		DISP=(MOD,PASS)	
//SYSUT1	DD	UNIT=(SYSDA,SEP=(SYSLIN,SYSLMOD)),SPACE=(1024,(50,20))	
//SYSPRINT	DD	SYSOUT=A,DCB=(,BLKSIZE=121)	
<sup>3</sup> //GO	EXEC	PGM=*.LKED.SYSLMOD,COND=((8,LT,ASM) ,(4,LT,LKED))	
		-----	
		-----	

<sup>1</sup> The LET linkage-editor option specified in this statement causes the linkage editor to mark the load module as executable even though errors were encountered during processing.

<sup>2</sup> The output of the linkage editor is specified as a member of a temporary data set, residing on a direct-access device, and is to be passed to a succeeding job step.

<sup>3</sup> This statement initiates execution of the assembled and linkage edited program. The notation \*.LKED.SYSLMOD identifies the program to be executed as being in the data set described in job step LKED by the DD statement named SYSLMOD. When running with MVT (Option 4) the REGION parameter can be calculated with the help of the Storage Estimates publication (see preface).

Figure 3. Cataloged Procedure for Assembly, Linkage Editing and Execution (ASMFCLG)

**OVERRIDING STATEMENTS IN CATALOGED PROCEDURES**

Any parameter in a cataloged procedure can be overridden except the PGM= parameter in the EXEC statement. Such overriding of statements or fields is effective only for the duration of the job step in which the statements appear. The statements, as stored in the procedure library of the system, remain unchanged.

Overriding for the purposes of re-specification, addition, or nullification is accomplished by including in the input stream statements containing the desired changes and identifying the statements to be overridden.

EXEC Statements

The PARM= and COND= parameters can be added or, if present, re-specified by including in the EXEC statement calling the procedure the notation PARM.stepname=, or COND.stepname=, followed by the desired parameters. "Stepname" identifies the EXEC statement within the procedure to which the modification applies. Overriding the PGM= parameter is not possible.

If the procedure consists of more than one job step, a PARM.stepname= or COND.stepname= parameter may be entered for each step. The entries must be in order, i.e., PARM.step1=, PARM.step2=, etc.

DD Statements

All parameters in the operand field of DD statements may be overridden by including in the input stream (following the EXEC card calling the procedure) a DD statement with the notation //stepname.ddname in the name field. "Stepname" refers to the job step in which the statement identified by "ddname" appears.

Examples

In the assembly procedure ASMFC (Figure 1), the production of a punched object deck could be suppressed and the UNIT= and SPACE= parameters of data set SYSUT1 re-specified, by including the following statements in the input stream:

```
//stepname EXEC PROC=ASMFC, X
// PARM.ASM=NODECK X

//ASM.SYSUT1 DD UNIT=2311, X
// SPACE=(200,(300,40))

//ASM.SYSIN DD *
```

In procedure ASMFCLG (Figure 3), suppressing production of an assembler listing and adding the COND= parameter to the EXEC statement, which specifies execution of the linkage editor, may be desired. In this case, the EXEC statement in the input stream would appear as follows:

```
//stepname EXEC PROC=ASMFCLG, X
// PARM.ASM=(NOLIST,LOAD), X
COND.LKED=(8.LT,stepname.ASM)
```

NOTE: Overriding the LIST parameter effectively deletes the PARM=LOAD so this must be repeated in the override statement.

For current execution of procedure ASMFCLG, no assembler listing would be produced, and execution of the linkage editor job step //LKED would be suppressed if the return code issued by the assembler (step ASM) was greater than 8. Using the procedure ASMFCL (Figure 2) to

1. Read input from a non-labeled 9-track tape on unit 282 that has a standard blocking factor of 10;
2. Put the output listing on a labeled tape VOLID=TAPE10, with a data set name of PROG1 and a blocking factor of 5;
3. Block the SYSGO output of the assembler and use it as input to the linkage editor with a blocking factor of 5;
4. Link edit the module only if there are no errors in the assembler, i.e., COND=0;
5. Link edit on to a previously allocated and cataloged data set USER.LIBRARY with a member name of PROG, the input stream appears as follows:

```
//jobname JOB
//stepname EXEC PROC=ASMFCL, X
// COND.LKED=(0,NE,stepname.ASM)
//ASM.SYSPRINT DD DSNAME=PROG1,UNIT=TAPE, X
// VOLUME=SER=TAPE10,DCB=(BLKSIZE=605)
//ASM.SYSGO DD DCB=(BLKSIZE=400)
//ASM.SYSIN DD UNIT=282,LABEL=(,NL), X
// DCB=(RECFM=FSB,BLKSIZE=800)
//LKED.SYSIN DD DCB=stepname.ASM.SYSGO
//LKED.SYSLMOD DD DSNAME=USER.LIBRARY(PROG),DISP=OLD
/*
```

NOTE: The order of appearance of ddnames within job steps ASM and LKED has been preserved. Thus, SYSPRINT precedes SYSGO within step ASM. The ddname ASM.SYSIN was placed last since SYSIN does not occur at



all within step ASM. These points are covered in the section Using Cataloged Procedures in the Job Control Language manual.

To assemble two programs, link edit the two assemblies into one load module and execute the load module, entering at PROG, the input stream appears as follows:

```
//stepname1 EXEC   PROC=ASMFC,PARM.ASM='LOAD'  
//ASM.GO DD      DSNAME=&LOADSET,UNIT=SYSSQ, X  
//              SPACE=(80,(100,50)), X  
//              DISP=(MOD,PASS),DCB=(BLKSIZE=400)  
//ASM.SYSIN DD    *  
              |  
              |  
              | source program 1 statements  
              |  
              |  
/*  
//stepname2 EXEC   PROC=ASMFC  
//ASM.SYSGO DD     DCB=(BLKSIZE=400)  
//ASM.SYSIN DD     *  
              |  
              |  
              | source program 2 statements  
              |  
              |  
/*  
//LKED.SYSLIN DD   DCB=(RECFM=FB,BLKSIZE=400)  
//LKED.SYSIN DD   *  
              ENTRY  PROG  
/*  
//GO.ddname dd cards for GO step
```

The overriding step with ddname =LKED.SYSLIN is necessary whenever output from an assembly and output from at least one or more processors (including the Assembler) is placed on SYSLIN. The DCB=(RECFM=FB,...) allows the linkage editor to process all the blocked input. Otherwise it will stop reading SYSLIN whenever it encounters a partial block. Such a situation arises if, say, the first assembly produces 22 cards. These 22 cards result in 4 full blocks of 400 bytes (5 times 80) plus 1 partial block of 160 bytes (2 times 80).

The Job Control Language and System Programmer's Guide publications provide additional description of overriding techniques.

## ASSEMBLER LISTING

The assembler listing (Figure 4) consists of five sections, ordered as follows: external symbol dictionary items, the source and object program statements, relocation dictionary items, symbol cross reference table, and diagnostic messages. In addition, three statistical messages may appear in the listing:

1. After the diagnostics, a statements-flagged message indicates the total number of statements in error. It appears as follows: nnn STATEMENTS FLAGGED IN THIS ASSEMBLY.
2. After the statements-flagged message, the assembler prints the highest severity code encountered (if non-zero). This is equal to the assembler return code. The message appears as follows: nn WAS HIGHEST SEVERITY CODE.
3. After the severity code, the assembler prints a count of lines printed, which appears as follows: nnn PRINTED LINES. This is a count of the actual number of 121-byte records generated by the assembler; it may be less than the total number of printed and blank lines appearing on the listing if the SPACE n assembler instruction is used. For a SPACE n that does not cause an eject, the assembler inserts n blank lines in the listing by generating n/3 blank 121-byte records -- rounded to the next lower integer if a fraction results; e.g., for a SPACE 2, no blank records are generated. The assembler does not generate a blank record to force a page eject.

In addition to the above items, the assembler prints the deck identification and current date on every page of the listing. If the timer is available, the assembler prints the time of day to the left of the date on page 1 of the ESD listing. This is the time when printing starts, rather than the start of the assembly, and is intended only to provide unique identification for assemblies made on the same day. The time is printed as hh.mm, where hh is the hour of the day (midnight beginning at 00), and mm is the number of minutes past the hour.

### EXTERNAL SYMBOL DICTIONARY (ESD)

This section of the listing contains the external symbol dictionary information passed to the linkage-editor in the object module. The entries describe the control sections, external references, and entry points in the assembled program. There are six types of entries, shown in Table 4,

along with their associated fields. The circled numbers refer to the corresponding heading in the sample listing (Figure 4). The X's indicate entries accompanying each type designation.

Table 4. Types of ESD Entries

① SYMBOL	② TYPE	③ ID	④ ADDR	⑤ LENGTH	⑥ LD ID
X	SD	X	X	X	-
X	LD	-	X	-	X
X	ER	X	-	-	-
-	PC	X	X	X	-
-	CM	X	X	X	-
X	XD	X	X	X	-

1. This column contains the name of every external dummy section, control section, entry point, and external symbol.
2. This column contains the type designator for the entry, as shown in the table. The type designators are defined as:

SD--Names section definition. The symbol appeared in the name field of a CSECT or START statement.

LD--The symbol appeared as the operand of the ENTRY statement.

ER--External reference. The symbol appeared as the operand of an EXTRN statement, or was defined as a V-type address constant.

PC--Unnamed control section definition.

CM--Common control section definition.

XD--External dummy section.

3. This column contains the external symbol dictionary identification number (ESDID). The number is a unique two-digit hexadecimal number identifying the entry. It is used by the LD entry of the ESD and by the relocation dictionary for cross-referencing the ESD.
4. This column contains the address of the symbol (hexadecimal notation) for SD- and LD-type entries, and zeros for ER-type entries. For PC- and CM-type entries, it indicates the beginning address of the control section. For

EXTERNAL SYMBOL DICTIONARY

EXAM SYMBOL	TYPE	ID	ADDR	LENGTH	LD	ID
① SAMPLR	SD	01	000000	000388		

Page 1  
00.16 4/11/66

EXAM	SAMPLE PROGRAM						Page 3
⑩ LOC	⑪ OBJECT CODE	⑫ ADDR1	⑬ ADDR2	⑭ STMT	⑮ SOURCE STATEMENT		⑯ F 14FEB66 4/11/66
000000	47F0 F00A		0000A	59+BEGIN	B	10(0,15) BRANCH AROUND ID	
000004	05			60+	DC	AL1(5)	
000005	C2C5C7C9D5			61+	DC	CL5'BEGIN' IDENTIFIER	
00000A	90EC D00C		0000C	62+	STM	14,12,12(13) SAVE REGISTERS	⑰
00000E	05C0			63	BALR	R12,0 ESTABLISH ADDRESSABILITY OF PROGRAM	SAMPL057
000010				64	USING	*,R12 AND TELL THE ASSEMBLER WHAT BASE TO USE	SAMPL058

RELOCATION DICTIONARY

EXAM	⑱ POS.ID	⑲ REL.ID	⑳ FLAGS	㉑ ADDRESS
	01	01	0C	0001FC
	01	01	0C	00020C
	01	01	0C	00021C
	01	01	0C	0002D4
	01	01	0C	000334

Page 1  
⑲  
4/11/66

CROSS-REFERENCE

EXAM	㉒ SYMBOL	㉓ LEN	㉔ VALUE	㉕ DEFN	㉖ REFERENCES					
	BEGIN	00004	000000	0059	0156	0158	0174	0184	0186	0220
	EXIT	00004	00007E	0096	0111					
	HIGHER	00002	0000F4	0130	0125					
	IHB0005	00001	00007B	0093	0090					
	IHB0005A	00002	00007C	0094	0089					

Page 1  
⑲  
4/11/66

DIAGNOSTICS

XAM	㉗ TMT	㉘ ERROR CODE	㉙ MESSAGE
	19	IEU025	NEAR OPERAND COLUMN 7--RELOCATABILITY ERROR
	21	IEU035	NEAR OPERAND COLUMN 9--ADDRESSABILITY ERROR
	2	STATEMENTS FLAGGED IN THIS ASSEMBLY	
	8	WAS HIGHEST SEVERITY CODE	
	261	PRINTED LINES	

Page 1  
⑲  
4/11/66

Figure 4. Assembler Listing

5. This column contains the assembled length, in bytes, of the control

6. This column contains, for LD-type entries, the identification (ID) number assigned to the ESD entry that identifies the control section in which the symbol was defined.

## SOURCE AND OBJECT PROGRAM

This section of the listing documents the source statements and the resulting object program.

7. This is the four-character deck identification. It is the symbol that appears in the name field of the first TITLE statement. The assembler prints the deck identification and date (item 16) on every page of the listing.
8. This is the information taken from the operand field of a TITLE statement.

NOTE: TITLE, SPACE and EJECT statements will not appear in the source listing unless the statement is continued onto another card. Then the first card of the statement is printed. However, any of these three types of statements, if generated as macro instruction expansion, will never be listed regardless of continuation.

9. Listing page number. Each section of the listing starts with page 1.
10. This column contains the assembled address (hexadecimal notation) of the object code.
11. This column contains the object code produced by the source statement. The entries are always left-justified. The notation is hexadecimal. Entries are machine instructions or assembled constants. Machine instructions are printed in full with a blank inserted after every four digits (two bytes). Constants may be only partially printed (see the PRINT assembler instruction in the Assembler Language publication).
12. These two columns contain effective addresses (the result of adding together a base register value and displacement value):

- a. The column headed ADDR1 contains the effective address for the first operand of an SS instruction.
- b. The column headed ADDR2 contains the effective address of the second operand of any instruction referencing storage.

Both address fields contain six digits; however, if the high-order digit is a zero, it is not printed.

13. This column contains the statement number. A plus sign (+) to the right of the number indicates that the statement was generated as the result of macro instruction processing.

14. This column contains the source program statement. The following items apply to this section of the listing:

- a. Source statements are listed, including those brought into the program by the COPY assembler instruction, and including macro definitions submitted with the main program for assembly. Listing control instructions are not printed, except for the following case: PRINT is listed when PRINT ON is in effect and a PRINT statement is encountered.
- b. Macro definitions obtained from SYSLIB are not listed.
- c. The statements generated as the result of a macro instruction follow the macro instruction in the listing.
- d. Assembler or machine instructions in the source program that contain variable symbols are listed twice: as they appear in the source input, and with values substituted for the variable symbols.
- e. Diagnostic messages are not listed in-line in the source and object program section. An error indicator, \*\*\*ERROR\*\*\*, follows the statement in error. The message appears in the diagnostic section of the listing.
- f. MNOTE messages are listed in-line in the source and object program section. An MNOTE indicator appears in the diagnostic section of the listing for MNOTE statements other than MNOTE\*. The MNOTE message format is severity code, message text.
- g. The MNOTE\* form of the MNOTE statement results in an in-line message only. An MNOTE indicator does not appear in the diagnostic section of the listing.
- h. When an error is found in a programmer macro definition, it is treated the same as any other assembly error: the error indication appears after the statement in error, and a diagnostic is placed in the list of diagnostics. However, when an error is encountered during the expansion of a macro instruction (system- or programmer-defined), the error indication appears in place of the erroneous statement, which is not listed. The error indication follows the last statement listed before the

erroneous statement was encountered, and the associated diagnostic message is placed in the list of diagnostics.

- i. Literals that have not been assigned locations by an LTORG statement appear in the listing following the END statement. Literals are identified by the equal (=) sign preceding them.
  - j. If the END statement contains an operand, the transfer address appears in the location column (LOC).
  - k. In the case of COM, CSECT, and DSECT statements, the location field contains the beginning address of these control sections, i.e., the first occurrence.
  - l. In the case of EXTRN, ENTRY, and DXD instructions, the location field and object code field are blank.
  - m. For a USING statement, the location field contains the value of the first operand.
  - n. For LTORG and ORG statements, the location field contains the location assigned to the literal pool or the value of the ORG operand.
  - o. For an EQU statement, the location field contains the value assigned.
  - p. Generated statements always print in normal statement format. Because of this, it is possible for a generated statement to occupy three or more continuation lines on the listing. This is unlike source statements, which are restricted to two continuation lines.
15. This column contains the identifier of the assembler (F) and the date when this version was released by Systems Development Division to DPD Program Information Department.
  16. Current date (date run is made).
  17. Identification-sequence field from the source statement.

#### RELOCATION DICTIONARY

This section of the listing contains the relocation dictionary information passed to the linkage editor in the object module. The entries describe the address constants in the assembled program that are affected by relocation.

18. This column contains the external symbol dictionary ID number assigned to the ESD entry that describes the control section in which the address constant is used as an operand.

19. This column contains the external symbol dictionary ID number assigned to the ESD entry that describes the control section in which the referenced symbol is defined.
20. The two-digit hexadecimal number in this column is interpreted as follows:

First Digit. A zero indicates that the entry describes an A-type or Q-type address constant. A one indicates that the entry describes a V-type address constant. A three describes a CXD entry.

Second Digit. The first three bits of this digit indicate the length of the constant and whether the base should be added or subtracted:

<u>Bits 0 and 1</u>	<u>Bit 2</u>
00 = 1 byte	0 = +
01 = 2 bytes	1 = -
10 = 3 bytes	
11 = 4 bytes	

21. This column contains the assembled address of the field where the address constant is stored.

#### CROSS REFERENCE

This section of the listing information concerns symbols which are defined and used in the program.

22. This column contains the symbols.
23. This column states the length (decimal notation), in bytes, of the field occupied by the symbol value.
24. This column contains either the address the symbol represents, or a value to which the symbol is equated.
25. This column contains the statement number of the statement in which the symbol was defined.
26. This column contains the statement numbers of statements in which the symbol appears as an operand. In the case of a duplicate symbol, the assembler fills this column with the message:

\*\*\*\*DUPLICATE\*\*\*\*

The following notes apply to the cross-reference section:

- Symbols appearing in V-type address constants do not appear in the cross-reference listing.
- A PRINT OFF listing control instruction does not affect the production of the cross-reference section of the listing.

- In the case of an undefined symbol, the assembler fills columns 23, 24, and 25 with the message:

\*\*\*\*UNDEFINED\*\*\*\*.

## DIAGNOSTICS

This section contains the diagnostic messages issued as a result of error conditions encountered in the program. The text, severity code, and explanatory notes for each message are contained in Appendix A.

27. This column contains the number of the statement in error.
28. This column contains the message identifier.
29. This column contains the message, and, in most cases, an operand column pointer that indicates the vicinity of the error. In the following example, the approximate location of the addressability error occurred in the 9th column of the operand field:

### Example:

STMT	ERROR CODE	MESSAGE
21	IEU035	NEAR OPERAND COLUMN 9 -- ADDRESSABILITY ERROR

The following notes apply to the diagnostic section:

- An MNOTE indicator of the form MNOTE STATEMENT appears in the diagnostic section if an MNOTE statement other than MNOTE\* is issued by a macro instruction. The MNOTE statement itself is in-line in the source and object program section of the listing. The operand field of an MNOTE\* is printed as a comment, but does not appear in the diagnostic section.

- A message identifier consists of six characters and is of the form: IEUxxx

IEU identifies the issuing agent as Assembler F, and xxx is a unique number assigned to the message.

NOTE: Editing errors in system macro instructions are discovered at the time the macro instruction is read from the library, i.e., after the END statement. To determine the location of these errors it is necessary to punch all system macro instructions, including inner macro instructions, and insert them in the source program as programmer macro instructions. To aid in debugging, it is advisable to run all macro instructions as programmer macro instructions before incorporating them as system macro instructions.

This section consists of a number of discrete subjects about assembler language programming.

SAVING AND RESTORING GENERAL REGISTER CONTENTS

A problem program should save the values contained in the general registers upon commencing execution and, upon completion, restore to the general registers these same values. Thus, as control is passed from the operating system to a problem program and, in turn, to a subprogram, the status of the registers used by each program is preserved. This is done through use of the SAVE and RETURN system macro instructions.

The SAVE macro instruction should be the first statement in the program. It stores the contents of registers 14, 15, and 0 through 12 in an area provided by the program that passes control. When a problem program is given control, register 13 points to an area in which the general register contents should be saved.

If the program calls any subprograms, or uses any operating system services other than GETMAIN, FREEMAIN, ATTACH, and XCTL, it must first save the contents of register 13 and then load the address of an 18 full-word save area into register 13. This save area is in the problem program and is used by any subprograms or operating system services called by the problem program.

At completion, the problem program restores the contents of general registers 14, 15 and 0-12 by use of the RETURN system macro instruction (which also indicates program completion). The content of register 13 must be restored before execution of the RETURN macro instruction.

The coding sequence that follows illustrates the basic process of saving and restoring the registers. A complete discussion of the SAVE and RETURN macro instructions and the saving and restoring of registers is contained in the Data Management Services and Data Management Macro-Instructions publications (see Preface).

Name	Operation	Operand
BEGIN	SAVE	(14, 12)
	.	set up base register
	ST	13,SAVEBLK+4
	LA	13,SAVEBLK
	.	
SAVEBLK	L	13,SAVEBLK+4
	RETURN	(14, 12)
	DC	18F'0'

PROGRAM TERMINATION

Completion of an assembler source program is indicated by using the RETURN system macro instruction to pass control from the terminating program to the program that initiated it. The initiating program may be the operating system or, if a subprogram issued the RETURN, the program that called it.


In addition to indicating program completion and restoring registers, the RETURN macro instruction may also pass a return code -- a condition indicator that may be used by the program receiving control. If the return is to the operating system, the return code is compared against the condition stated in the COND= parameter of the JOB or EXEC statements. If return is to another problem program, the return code is available in general register 15, and may be used as desired. Register 13 should be restored before issuing the RETURN macro instruction.

The RETURN system macro instruction is discussed in detail in the Supervisor and Data Management Macro-Instructions publication.

PARAM FIELD ACCESS

Access to information in the PARM field of an EXEC statement is gained through general register 1. When control is given to the problem program, general register 1 contains the address of a full word which, in turn, contains the address of the data area containing the information.

The data area consists of a half word containing the count (in binary) of the number of information characters, followed by the information field. The information field is aligned to a full-word boundary. The following diagram illustrates this process.



MACRO DEFINITION LIBRARY ADDITIONS

Source statement coding, to be retrieved by the COPY assembler instruction, and

macro definitions may be added to the macro library. The IEBUPDAT utility program is used for this purpose. Details of this program and its control statements are contained in the Utilities publication. The following sequence of job control statements can be used to call the utility program and identify the needed data sets. It is assumed that the job control statements, IEBUPDAT program control statements, and data are to enter the system via the input stream.

```
//jobname    JOB
//stepname   EXEC  PGM=IEBUPDAT,PARM=NEW
//SYSUT2     DD    DSN=SYS1.MACLIB,DISP=OLD
//SYSPRINT   DD    SYSOUT=A
//SYSIN      DD    *
```

IEBUPDAT control statements and source statements or macro-definitions to be added to the macro-library (SYS1.MACLIB)

/\* (delimiter statement)

#### LOAD MODULE MODIFICATION - ENTRY POINT RESTATEMENT

If the editing functions of the linkage editor are to be used to modify a load module, the entry point to the load module must be restated when the load module is reprocessed by the linkage editor. Otherwise, the first byte of the first control section processed by the linkage editor will become the entry point. To enable restatement of the original entry point, or designation of a new entry point, the entry point must have been identified originally as an external symbol, i.e., appeared as an entry in the external symbol dictionary. External symbol identification is done automatically by the assembler if the entry point is the name of a control section or START statement; otherwise, an assembler ENTRY statement must be used to identify the entry point name as an external symbol.

When a new object module is added to or replaces part of the load module, the entry point is restated in one of three ways:

- By placing the entry point symbol in the operand field of an EXTRN statement and an END statement in the new object module.

- By using an END statement in the new object module to designate a new entry point in the new object module.
- By using a linkage editor ENTRY statement to designate either the original entry point or a new entry point for the load module.

Further discussion of load module entry points is contained in the Linkage Editor publication.

#### OBJECT MODULE LINKAGE

Object modules, whether Assembler-, FORTRAN-, or COBOL-generated, may be combined by the linkage editor to produce a composite load module, provided each object module conforms to the data formats and linkage conventions required. This topic discusses the use of the CALL system macro instruction to link an assembler language "main" program to subprograms produced by FORTRAN and COBOL. The Supervisor and Data Management Macro-Instructions publication contains additional details concerning linkage conventions and the CALL system macro instruction.

Figure 5 shows the statements used to establish the assembler program linkage to the called subprograms.

If any input/output operations are performed by called subprograms, appropriate DD statements for the data sets used by the subprograms must be supplied. See the FORTRAN IV (E) Programmer's Guide publication for explanation of the DD statements used to describe data sets for FORTRAN programs and a description of the special FORTRAN data set record formats. The COBOL (E) Programmer's Guide publication provides DD statement information for COBOL programs.

#### DICTIONARY SIZE AND SOURCE STATEMENT COMPLEXITY

This section describes the composition of the assembler dictionaries and their entry sizes, and describes methods for determining if the limits on source statement complexity will be exceeded.

Dictionary entries, e.g., sequence symbol names, prototype symbolic parameters, vary in length. Therefore, the number of entries a dictionary can hold is determined by the types of entries.

Source statement complexity -- the number of symbols, characters, operators, delimiters, references to length attributes, self-defining terms, literals, and expressions appearing in a source statement -- determines whether or not the source statement can be successfully processed.

```

        SAVE    (14,12)
        .
        .      set up base register
1       .
        ST     13,SVAREA+4
        LA     15,SVAREA
        ST     15,8(13)
        LR     13,15
        .
        .
2       .
        CALL   name,(V1,V2,V3),VL
        .
        .
        L     13,SVAREA+4
3       RETURN (14,12)
4 SVAREA DC    18F'0'
5 V1    DC    (data)
6 V2    DC    (data)
6 V3    DC    (data)
        END

```

1 This is an example of OS linkage convention. See the publication Supervisor and Data Management Services for details.

2 The symbol used for "name" in this statement is:

- a. The name of a subroutine or function, when the linkage is to a FORTRAN-written subprogram.
- b. The name defined by the following COBOL statements in the procedure division:

```
ENTER LINKAGE. ENTRY'name'.
```

- c. The name of a CSECT or START statement, or a name used in the operand field of an ENTRY statement in an assembler subprogram.

The order in which the parameter list is written must reflect the order in which the called subprogram expects the argument. If the called routine is a FORTRAN-written function, the returned argument is not in the parameter list: a real or double precision function returns the value in floating point register zero; an integer function returns the value in general purpose register zero.

CAUTION: When linking to FORTRAN-written subprograms, consideration must be given to the storage requirements of IBCOM (FORTRAN execution-time I/O and interrupt handling routines) which accompanies the compiled FORTRAN subprogram. In some instances the call for IBCOM is not automatically generated during the FORTRAN compilation. The FORTRAN IV Library publication provides information about IBCOM requirements and assembler statements used to call IBCOM.

FORTRAN - written subprograms and FORTRAN library subprograms allow variable-length parameter lists in linkages which call them; therefore all linkages to FORTRAN subprograms are required to have the high-order bit in the last parameter in the linkage set to 1. COBOL-written subprograms have fixed-length calling linkages; therefore, for COBOL the high-order bit in the last parameter need not be set to 1.

3 This statement reserves the save area needed by the called subprogram. When control is passed to the subprogram, register 13 contains the address of this area.

4 5 6 When linking to a FORTRAN or COBOL subprogram, the data formats declared in these statements are determined by the data formats required by the FORTRAN or COBOL subprograms.

Figure 5. Linkage Statements

#### DICTIONARIES USED IN CONDITIONAL ASSEMBLY AND MACRO INSTRUCTION EXPANSION

To accomplish macro instruction expansion and conditional assembly, the assembler constructs a general dictionary consisting of two parts: one global dictionary for the entire program, and an area for all of the local dictionaries.

The global dictionary contains one entry for each machine operation code, extended mnemonic operation code, assembler operation code, macro instruction, and global SET variable symbol.

The local dictionary area consists of one local dictionary for each different

macro definition in the program, and one local dictionary for the main portion of the program (those statements not within a macro definition, also called "open code."). The contents of the local dictionaries are described in subsequent paragraphs.

The capacity of the general dictionary (global dictionary and all local dictionaries) is up to 64 blocks of 1024 bytes each. The division of the dictionary into global and local sections is done dynamically: as the global dictionary becomes larger, it occupies blocks taken from the local dictionary area. Thus, the global dictionary is always core resident. As it

expands into the local dictionary area, the local dictionaries may overflow onto a utility file. The size of the dictionaries in core depends upon core availability. The minimum core allocation is three blocks for the global dictionary and two blocks for each local dictionary.

Each block in the global and local dictionaries contains complete entries. Any entry not fitting into a block is placed in the next block; the remaining bytes in the current block are not used.

The global and local dictionaries take two forms: one when the dictionary entries are collected, i.e., picked up during the initial scan of the source program, and one during the actual conditional assembly and macro generation, i.e., generation time. The following text describes the global and local dictionaries at both collection time and generation time.

#### Global Dictionary at Collection Time

One global dictionary is built for the entire program. It contains machine operation codes, extended mnemonic operation codes, assembler operation codes, macro instruction mnemonics, and global SET variable symbols. One entry is made for each. The size of each type of entry is shown in Table 5.

Table 5. Global Dictionary Entries at Collection Time

Entry	Size
Each machine operation code **	5 bytes plus mnemonic*
Each extended mnemonic operation code or assembler operation **	6 bytes plus mnemonic*
Each macro mnemonic operation code	10 bytes plus mnemonic*
Each global SET variable symbol	6 bytes plus name*

\*One byte is used for each character in the name or mnemonic.

\*\*For the first two types of entries, a total of 06FE<sub>16</sub> (1790<sub>10</sub>) bytes of core is required.

Fixed overhead for this dictionary is  
 8 bytes for the first block  
 4 bytes for each succeeding block  
 5 bytes for the last block.

#### Local Dictionaries at Collection Time

For the main portion of the program (those statements not within a macro definition), one local dictionary is constructed in which ordinary symbols, sequence symbols, and local SET variable symbols are entered. In addition, one local dictionary is constructed for each different macro definition in the program. These local dictionaries contain one entry for each local SET variable symbol, sequence symbol, and prototype symbolic parameter declared within the macro definition. If a sequence symbol is defined before it is referenced, an extra entry for the symbol is made. Table 6 shows the size of each type of entry.

Table 6. Local Dictionary Entries at Collection Time

Entry	Size
Each sequence symbol	10 bytes plus name*
Each local SET variable symbol	6 bytes plus name*
Each prototype symbolic parameter	5 bytes plus name*
Each ordinary symbol appearing in the main portion of the program.	10 bytes plus name*

\*One byte is used for each character in the name or mnemonic.

Fixed overhead for this dictionary is  
 8 bytes for the first block (if in the main program)  
 32 bytes for the first block (if in a macro definition)  
 4 bytes for each succeeding block  
 5 bytes for the last block

#### Global Dictionary at Generation Time

The sizes of the global dictionary entries at generation time are shown in Table 7.

Table 7. Global Dictionary Entries at Generation Time

Entry	Size
Each macro mnemonic operation code	3 bytes
Each global SETA symbol (dimensioned)	1 byte plus 4N*
Each global SETA symbol (undimensioned)	4 bytes
Each global SETB symbol (dimensioned)	1 byte plus (N/8)* (N/8 is rounded to the next highest integer)
Each global SETB symbol (undimensioned)	1 bit
Each global SETC symbol (dimensioned)	1 byte plus 9N*
Each global SETC symbol (undimensioned)	9 bytes

\*N = dimension

Fixed overhead for this dictionary is 4 bytes plus word alignment.

Local Dictionaries at Generation Time

Table 8 shows the sizes of the various entries appearing in the local dictionaries at generation time.

Table 8. Local Dictionary Entries at Generation Time.

Entry	Size
Each sequence symbol	5 bytes
Each local SETA symbol (dimensioned)	1 byte plus 4N*
Each local SETA symbol (undimensioned)	4 bytes
Each local SETB symbol (dimensioned)	1 byte plus (N/8)* (N/8 is rounded to the next highest integer)
Each local SETB symbol (undimensioned)	1 bit
Each local SETC symbol (dimensioned)	1 byte plus 9N*
Each local SETC symbol (undimensioned)	9 bytes
Each ordinary symbol appearing in the main portion of the program.**	5 bytes

\*N=dimension

\*\*These entries appear only in the main program local dictionary.

Fixed overhead for this dictionary is 20 bytes plus word alignment.

Additional Dictionary Requirements

The generation time global dictionary and the generation time local dictionary for the main portion of the program must be resident in main storage.

In addition, if the program contains any macro instructions, main storage is required for the largest local dictionary of the macro definitions being processed. Furthermore, during processing of macro definitions containing inner macro instructions, main storage is required for the generation time local dictionaries for the inner macro instructions contained within the macro definition.

In addition to those requirements specified for the local dictionary of the main portion of the program, each macro definition local dictionary requires space for entries shown in Table 9.

Table 9. Macro Definition Local Dictionary Parameter Table

Entry	Size
Each character string (1)	3 bytes plus L
Each hexadecimal, binary, decimal, and character self-defining term (2)	7 bytes plus L
Each symbol (3)	9 bytes plus L
Each sublist	9 bytes plus 3N bytes plus Y

L = Length of BCD entry in bytes

N = Number of entries in sublist

Y =  $E_1 + E_2 + E_3 + \dots + E_n$   
 where E = size of an entry (formats 1,2, and 3 above)

Fixed overhead for the macro definition local dictionary parameter table is 22 bytes. Each nested macro instruction also requires space in its local dictionary for the following:

Parameter pointer list 8 bytes plus 2N  
 (N = the number of operands)

Pointers to parameter pointer list and parameter table 8 bytes plus word alignment

SOURCE STATEMENT COMPLEXITY

The complexity of a source statement is limited both by the macro generator and the assembler portions of the assembler. The

following topics provide the information necessary to determine if statement-complexity limitations for either portion of the assembler are being exceeded.

#### Macro Generation and Conditional Assembly Limitation

For any statement which

1. Is a conditional assembly statement,
2. Is a DC or DS statement,
3. Is an EXTRN statement,
4. Contains a sequence symbol or a variable symbol,
5. Is not a macro instruction or prototype statement,

the total number of explicit occurrences of

1. Ordinary symbols (includes machine mnemonics, assembler mnemonics, conditional assembly mnemonics, and macro instruction mnemonics),
2. Variable symbols,
3. Sequence symbols,

must not exceed 50 for the entire statement.

For macro instructions and prototype statements the number of occurrences of

ordinary symbols, variable symbols, and sequence symbols must not exceed 50 in the name and operation fields combined; or in each operand unless the operand is a sublist, in which case the limit is applied to each sublist operand. In any operand if a character string has the same form as a symbol, it is counted as a symbol.

#### Examples of Counts:

```
&B2 SETB (T'NAME EQ 'W') count=3 (&B2,SETB,NAME)
EXTRN A,B,C,&C          count=5 (EXTRN,A,B,C,&C)
```

#### Assembler Portion Limitations

1. Generated statements may not exceed 236 characters. Statement length includes name, operation, operand, and comments. If a comments field exists, the blank separating the operand and comments field is included in the statement length. The statement is truncated if it exceeds 236 characters.
2. DC, DS, DXD, and literal DCs cannot contain more than 32 operands per statement.

APPENDIX A. DIAGNOSTIC MESSAGES

<u>Code</u>	<u>Message</u>	<u>Explanation</u>	<u>Severity Code</u>
IEU001	DUPLICATION FACTOR ERROR	A duplication factor is not an absolute expression, or is zero in a literal: * in duplication factor expression; invalid syntax in expression.	12
IEU002	RELOCATABLE DUPLICATION FACTOR	A relocatable expression has been used to specify the duplication factor.	12
IEU003	LENGTH ERROR	The length specification is out of permissible range or specified invalidly; * in length expression; invalid syntax in expression; no left-parenthesis delimiter for expression.	12
IEU004	RELOCATABLE LENGTH	A relocatable expression has been used to specify length.	12
IEU005	S-TYPE CONSTANT IN LITERAL	Self-explanatory.	8
IEU006	INVALID ORIGIN	The location counter has been reset to a value less than the starting address of the control section; ORG operand is not a simply relocatable expression or specifies an address outside the control section.	12
IEU007	LOCATION COUNTER ERROR	The location counter has exceeded $2^{24}-1$ , or passed out of control section in negative direction (3 byte arithmetic).	12
IEU008	INVALID DISPLACEMENT	The displacement in an explicit address is not an absolute value within the range of 0 to 4095.	8
IEU009	MISSING OPERAND	Self-explanatory	12
IEU010	INCORRECT REGISTER SPECIFICATION	The value specifying the register is not an absolute value within the range 0-15, an odd register is specified where an even register is required, or a register was used where none can be specified.	8
IEU011	SCALE MODIFIER ERROR	The scale modifier is not an absolute expression or is too large, negative scale modifier for floating point, * in scale modifier expression; invalid syntax or illegally specified scale modifier.	8
IEU012	RELOCATABLE SCALE MODIFIER	A relocatable expression has been used to specify the scale modifier.	8
IEU013	EXPONENT MODIFIER ERROR	The exponent is not specified as an absolute expression or is out of range; * in exponent modifier expression; invalid syntax; illegally specified exponent modifier.	8
IEU014	RELOCATABLE EXPONENT MODIFIER	A relocatable expression has been used to specify the exponent modifier.	8

<u>Code</u>	<u>Message</u>	<u>Explanation</u>	<u>Severity Code</u>
IEU015	INVALID LITERAL USAGE	A valid literal is used illegally, e.g., it specifies a receiving field or a register, or it is a Q-type constant.	8
IEU016	INVALID NAME	A name entry is incorrectly specified, e.g., it contains more than 8 characters, it does not begin with a letter, or has a special character imbedded.	8
IEU017	DATA ITEM TOO LARGE	The constant is too large for the data type or for the explicit length; operand field for packed DC exceeds 32 characters and for zoned DC exceeds 16 characters (excluding decimal points).	8
IEU018	INVALID SYMBOL	The symbol is specified invalidly, e.g., it is longer than 8 characters.	8
IEU019	EXTERNAL NAME ERROR	A CSECT and DSECT statement have the same name, or a symbol is used more than once in an EXTRN or the name field of DXD statements.	8
IEU020	INVALID IMMEDIATE FIELD	The value of the immediate operand exceeds 255, or the operand requires more than one byte of storage.	8
IEU021	SYMBOL NOT PREVIOUSLY DEFINED	Self-explanatory.	8
IEU022	ESDTABLE OVERFLOW	The combined number of control sections and dummy sections plus the number of unique symbols in EXTRN statements and V-type constants exceeds 255. (A DSECT which appears as XD makes two entries).	12
IEU023	PREVIOUSLY DEFINED NAME	The symbol which appears in the name field has appeared in the name field of a previous statement.	8
IEU024	UNDEFINED SYMBOL	A symbol being referenced has not been defined in the program.	8
IEU025	RELOCATABILITY ERROR	A relocatable or complex relocatable expression is specified where an absolute expression is required, an absolute expression or complex relocatable expression is specified where a relocatable expression is required, or a relocatable term is involved in multiplication or division.	8
IEU026	TOO MANY LEVELS OF PARENTHESES	An expression specifies more than 5 levels of parentheses.	12
IEU027	TOO MANY TERMS	More than 16 terms are specified in an expression.	12
IEU028	REGISTER NOT USED	A register specified in a DROP statement is not currently in use.	4

<u>Code</u>	<u>Message</u>	<u>Explanation</u>	<u>Severity Code</u>
IEU029	CCW ERROR	Bits 37-39 of the CCW are set to non-zero.	8
IEU030	INVALID CNOP	An invalid combination of operands is specified.	12
IEU031	UNKNOWN TYPE	Incorrect type designation is specified in a DC, DS, or literal.	8
IEU032	OP-CODE NOT ALLOWED TO BE GENERATED	Self-explanatory.	8
IEU033	ALIGNMENT ERROR	Referenced address is not aligned to the proper boundary for this instruction, e.g., START operand not a multiple of 8.	4
IEU034	INVALID OP-CODE	Syntax error, e.g., more than 5 characters in operation field, not followed by blank on first card, missing.	8
IEU035	ADDRESSABILITY ERROR	The referenced address does not fall within the range of a USING instruction.	8
IEU036	(No message is assigned to this number)		
IEU037	MNOTE STATEMENT	This indicates that an MNOTE statement has been generated from a macro definition. The text and severity code of the MNOTE statement will be found in line in the listing.	Variable
IEU038	ENTRY ERROR	A symbol in the operand of an ENTRY statement appears in more than one ENTRY statement, it is undefined, it is defined in a dummy section or in blank common, or it is equated to a symbol defined by an EXTRN statement.	8
IEU039	INVALID DELIMITER	This message can be caused by any syntax error, e.g., missing delimiter, special character used which is not a valid delimiter, delimiter used illegally, operand missing, i.e., nothing between delimiters, unpaired parentheses, imbedded blank in expression.	12
IEU040	GENERATED RECORD TOO LONG	There are more than 236 characters in a generated statement.	12
IEU041	UNDECLARED VARIABLE SYMBOL	Variable symbol is not declared in a defined SET symbol statement or in a macro prototype.	8
IEU042	SINGLE TERM LOGICAL EXPRESSION IS NOT A SETB SYMBOL	The single term logical expression has not been declared as a SETB symbol.	8
IEU043	SET SYMBOL PREVIOUSLY DEFINED	Self-explanatory.	8
IEU044	SET SYMBOL USAGE INCONSISTENT WITH DECLARATION	A SET symbol has been declared as undimensioned, but is subscripted, or has been declared dimensioned, but is unsubscripted.	8

<u>Code</u>	<u>Message</u>	<u>Explanation</u>	<u>Severity Code</u>
IEU045	ILLEGAL SYMBOLIC PARAMETER	An attribute has been requested for a variable symbol which is not a legal symbolic parameter.	8
IEU046	AT LEAST ONE RELOCATABLE Y TYPE CONSTANT IN ASSEMBLY	Self-explanatory.	4
IEU047	SEQUENCE SYMBOL PREVIOUSLY DEFINED	Self-explanatory.	12
IEU048	SYMBOLIC PARAMETER PREVIOUSLY DEFINED OR SYSTEM VARIABLE SYMBOL DECLARED AS SYMBOLIC PARAMETER	Self-explanatory.	12
IEU049	VARIABLE SYMBOL MATCHES A PARAMETER	Self-explanatory.	12
IEU050	INCONSISTENT GLOBAL DECLARATIONS	A global SET variable symbol, defined in more than one macro definition or defined in a macro definition and in the source program, is inconsistent in SET type or dimension.	8
IEU051	MACRO DEFINITION PREVIOUSLY DEFINED	Prototype operation field is the same as a machine or assembler instruction or a previous prototype.	12
IEU052	NAME FIELD CONTAINS ILLEGAL SET SYMBOL	SET symbol in name field does not correspond to SET statement type.	8
IEU053	GLOBAL DICTIONARY FULL	The global dictionary is full, assembly terminated.	12
IEU054	LOCAL DICTIONARY FULL	The local dictionary is full, current macro aborted. If in open code, assembly terminated.	12
IEU055	INVALID ASSEMBLER OPTION(S) ON THE EXECUTE CARD	Self-explanatory.	8
IEU056	ARITHMETIC OVERFLOW	The intermediate or final result of an expression is not within the range of $-2^{31}$ to $2^{31}-1$ .	8
IEU057	SUBSCRIPT EXCEEDS MAXIMUM DIMENSION	&SYSLIST or symbolic parameter subscript exceeds 200, or is negative, or zero, or SET symbol subscript exceeds dimension.	8
IEU058	RE-ENTRANT CHECK FAILED	An instruction has been detected, which, when executed, might store data into a control section or a common area. This message is generated only when requested via control cards and merely indicates a possible re-entrant error.	4
IEU059	UNDEFINED SEQUENCE SYMBOL	Self-explanatory.	12
IEU060	ILLEGAL ATTRIBUTE NOTATION	L', S', or I' requested for a parameter whose type attribute does not allow these attributes to be requested.	8

<u>Code</u>	<u>Message</u>	<u>Explanation</u>	<u>Severity Code</u>
IEU061	ACTR COUNTER EXCEEDED	Self-explanatory.	12
IEU062	GENERATED STRING GREATER THAN 255 CHARACTERS	Self-explanatory.	8
IEU063	EXPRESSION 1 OF SUB- STRING IS ZERO OR MINUS	Self-explanatory.	8
IEU064	EXPRESSION 2 OF SUB- STRING IS ZERO OR MINUS	Self-explanatory.	8
IEU065	INVALID OR ILLEGAL TERM IN ARITHMETIC EXPRESSION	The value of a SETC symbol used in the arithmetic expression is not composed of decimal digits, or the parameter is not a self-defining term.	8
IEU066	UNDEFINED OR DUP- LICATE KEYWORD OPERAND OR EXCESSIVE POSITIONAL OPERANDS	The same keyword operand occurs more than once in the macro instruction; a keyword is not defined in a prototype statement; in a mixed mode macro instruction, more positional operands are specified than are specified in the prototype.	12
IEU067	EXPRESSION 1 OF SUB- STRING GREATER THAN LENGTH OF CHARACTER EXPRESSION	Self-explanatory.	8
IEU068	GENERATION TIME DICTIONARY AREA OVERFLOWED	See <u>Dictionary Size and Source Statement Complexity</u> .	12
IEU069	VALUE OF EXPRESSION 2 OF SUBSTRING GREATER THAN 8	Self-explanatory.	8
IEU070	FLOATING POINT CHARACTERISTIC OUT OF RANGE	Self-explanatory.	12
IEU071	ILLEGAL OCCURRENCE OF LCL, GBL, OR ACTR STATEMENT	LCL, GBL, or ACTR statement is not in proper place in the program.	8
IEU072	ILLEGAL RANGE ON ISEQ STATEMENT	Self-explanatory.	4
IEU073	ILLEGAL NAME FIELD	Either a statement which requires a name has been written without a name, or a statement has a name which is not allowed to have a name.	8
IEU074	ILLEGAL STATEMENT IN COPY CODE OR SYSTEM MACRO	Self-explanatory.	8

<u>Code</u>	<u>Message</u>	<u>Explanation</u>	<u>Severity Code</u>
IEU075	ILLEGAL STATEMENT OUTSIDE OF A MACRO DEFINITION	Self-explanatory.	8
IEU076	SEQUENCE ERROR	Self-explanatory.	12
IEU077	ILLEGAL CONTINUATION CARD	Either there are too many continuation cards, or there are non-blanks between the begin and continue columns on the continuation card.	8
IEU078	(No message is assigned to this number)		
IEU079	ILLEGAL STATEMENT IN MACRO DEFINITION	This operation is not allowed within a macro definition.	8
IEU080	ILLEGAL START CARD	Statements affecting or depending upon the location counter have been encountered before a START statement.	8
IEU081	ILLEGAL FORMAT IN GBL OR LCL STATE- MENTS	An operand is not a variable symbol.	8
IEU082	ILLEGAL DIMENSION SPECIFICATION IN GBL OR LCL STATEMENT	Dimension is other than 1 to 255.	8
IEU083	SET STATEMENT NAME FIELD NOT A VARIABLE SYMBOL	Self-explanatory.	8
IEU084	ILLEGAL OPERAND FIELD FORMAT	Syntax invalid, e.g., AIF statement operand does not start with a left parenthesis; operand of AGO is not a sequence symbol; operand of PUNCH, TITLE, MNOTE not enclosed in quotes.	8
IEU085	INVALID SYNTAX IN EXPRESSION	Invalid delimiter, too many terms in expression, too many levels of parentheses, two operators in succession, two terms in succession, or illegal character.	8
IEU086	ILLEGAL USAGE OF SYSTEM VARIABLE SYMBOL	A system variable symbol appears in the name field of a SET statement, is used in a mixed mode or keyword macro definition, is declared in a GBL or LCL statement, or is an unsubscripted &SYSLIST in a context other than N'&SYSLIST.	8
IEU087	NO ENDING APOSTROPHE	There is an unpaired apostrophe or ampersand in the statement.	8
IEU088	UNDEFINED CODE	Self-explanatory.	12
IEU089	INVALID ATTRIBUTE NOTATION	Syntax error inside a macro definition, e.g., the argument of the attribute reference is not a symbolic parameter.	8

<u>Code</u>	<u>Message</u>	<u>Explanation</u>	<u>Severity Code</u>															
IEU090	INVALID SUBSCRIPT	Syntax error, e.g., double subscript where single subscript is required or vice versa; not right parenthesis after subscript.	8															
IEU091	INVALID SELF-DEFINING TERM	Value is too large or is inconsistent with the data type, e.g., severity code greater than 255.	8															
IEU092	INVALID FORMAT FOR VARIABLE SYMBOL	The first character after the ampersand is not alphabetic, or the variable symbol contains more than 8 characters.	8															
IEU093	UNBALANCED PARENTHESIS OR EXCESSIVE LEFT PARENTHESES	Self-explanatory.	8															
IEU094	INVALID OR ILLEGAL NAME OR OPERATION IN PROTOTYPE STATEMENT	Self-explanatory.	12															
IEU095	ENTRY TABLE OVERFLOW	Number of ENTRY symbols, i.e., ENTRY instruction operands, exceeds 100.	8															
IEU096	MACRO INSTRUCTION OR PROTOTYPE OPERAND EXCEEDS 255 CHARACTERS IN LENGTH	Self-explanatory.	12															
IEU097	INVALID FORMAT IN MACRO INSTRUCTION OPERAND OR PROTOTYPE PARAMETER	<p>This message can be caused by:</p> <ol style="list-style-type: none"> <li>1. Illegal "=".</li> <li>2. A single "&amp;" appears somewhere in the standard value assigned to a prototype keyword parameter.</li> <li>3. First character of a prototype parameter is not "&amp;".</li> <li>4. Prototype parameter is a subscripted variable symbol.</li> <li>5. Invalid use of alternate format in prototype statement, e.g., <table border="0" style="margin-left: 2em;"> <tr> <td style="padding-right: 2em;">10</td> <td style="padding-right: 2em;">16</td> <td style="padding-right: 2em;">72</td> </tr> <tr> <td>PROTO</td> <td>&amp;A,&amp;B,</td> <td></td> </tr> <tr> <td></td> <td style="text-align: center;">or</td> <td></td> </tr> <tr> <td>PROTO</td> <td>&amp;A,&amp;B,</td> <td>X</td> </tr> <tr> <td></td> <td style="text-align: center;">&amp;C</td> <td></td> </tr> </table> </li> <li>6. Unintelligible prototype parameter, e.g., "&amp;A*" or "&amp;A&amp;&amp;."</li> <li>7. Illegal (non-assembler) character appears in prototype parameter or macro-instruction operand.</li> </ol>	10	16	72	PROTO	&A,&B,			or		PROTO	&A,&B,	X		&C		12
10	16	72																
PROTO	&A,&B,																	
	or																	
PROTO	&A,&B,	X																
	&C																	
IEU098	EXCESSIVE NUMBER OF OPERANDS OR PARAMETERS	Either the prototype has more than 200 parameters, or the macro instruction has more than 200 operands.	12															
IEU099	POSITIONAL MACRO INSTRUCTION OPERAND, PROTOTYPE PARAMETER OR EXTRA COMMA FOLLOWS KEYWORD	Self-explanatory.	12															

<u>Code</u>	<u>Message</u>	<u>Explanation</u>	<u>Severity Code</u>
IEU100	STATEMENT COMPLEXITY EXCEEDED	More than 32 operands in a DC, DS, DXD, or literal DC, or more than 50 terms in a statement.	8
IEU101	EOD ON SYSIN	EOD before END card.	12
IEU102	INVALID OR ILLEGAL ICTL	The operands of the ICTL are out of range, or the ICTL is not the first statement in the input deck.	16
IEU103	ILLEGAL NAME IN OPERAND FIELD OF COPY CARD	Syntax error, e.g., symbol has more than 8 characters or has an illegal character.	12
IEU104	COPY CODE NOT FOUND	The operand of a COPY statement specified COPY text which cannot be found in the library.	12
IEU105	EOD ON SYSTEM MACRO LIBRARY	EOD before MEND card.	12
IEU106	NOT NAME OF DSECT OR DXD	Self-explanatory.	8
IEU107	INVALID OPERAND	Invalid syntax in DC operand, e.g., invalid hexadecimal character in hexadecimal DC; operand string too long for X, B, C, DC's; operand unrecognizable, contains invalid value, or incorrectly specified.	4
IEU108	PREMATURE EOD	Indicates an internal assembler error; should not occur.	16
IEU109	PRECISION LOST	Self-explanatory.	8
IEU110	EXPRESSION VALUE TOO LARGE	Value of expression greater than -16777216 to +16777215.  Expressions in EQU and ORG statements are flagged if (1) they include terms previously defined as negative values, or (2) positive terms give a result of more than three bytes in magnitude. The error indication may be erroneous due to (1) the treatment of negative values as three-byte positive values, or (2) the effect of large positive values on the location counter if a control section begins with a START statement having an operand greater than zero, or a control section is divided into subsections.	8
IEU111	SYSGO DD CARD MISSING NOLOAD OPTION USED	Self-explanatory.	16
IEU112	SYSPUNCH DD CARD MISSING NODECK OPTION USED	Self-explanatory.	16
IEU997	SYSPRINT DD CARD MISSING NOLIST OPTION USED	Self-explanatory. Printed on console typewriter.	0
IEU998	ASSEMBLY TERMINATED. MISSING DATA SET FOR (ddname)	Self-explanatory. Printed on console typewriter.	20
IEU999	ASSEMBLY TERMINATED. PERMANENT I/O ERROR ON (ddname)	Self-explanatory. Printed on console typewriter.	20

APPENDIX B. OBJECT DECK OUTPUT

TEXT (TXT) CARD FORMAT

The format of the TXT cards is as follows:

<u>Columns</u>	<u>Contents</u>
1	12-2-9 punch
2-4	TXT
5	Blank
6-8	Relative address of first instruction on card
9-10	Blank
11-12	Byte count -- number of bytes in information field (cc 17-72)
13-14	Blank
15-16	ESDID
17-72	56-byte information field
73-76	Deck ID (from first TITLE card)
77-80	Card sequence number

RLD CARD FORMAT

The format of the RLD card is as follows:


<u>Columns</u>	<u>Contents</u>
1	12-2-9 punch
2-4	RLD
5-10	Blank
11-12	Data field count -- number of bytes of information in data field (cc 17-72)
13-16	Blank
17-72	Data field:
17-18	Relocation ESDID
19-20	Position ESDID
21	Flag byte
22-24	Absolute address to be relocated
25-72	Remaining RLD entries
73-76	Deck ID (from first TITLE card)
77-80	Card sequence number

If the rightmost bit of the flag byte is set, the following RLD entry has the same Relocation ESDID and Position ESDID, and this information will not be repeated; if the rightmost bit of the flag byte is not set, the next RLD entry has a different Relocation ESDID and/or Position ESDID, and both ESDIDs will be recorded.

For example, if the RLD Entries 1, 2, and 3 of the program listing (Appendix C) contain the following information:

	<u>Pos.</u>	<u>Rel.</u>		
	<u>ESDID</u>	<u>ESDID</u>	<u>Flag</u>	<u>Address</u>
Entry 1	02	04	0C	000100
Entry 2	02	04	0C	000104
Entry 3	03	01	0C	000800

Columns 17-36 of the RLD card would appear as follows:



ESD CARD FORMAT

The format of the ESD card is as follows:

<u>Columns</u>	<u>Contents</u>
1	12-2-9 punch
2-4	ESD
5-10	Blank
11-12	Variable field count -- number of bytes of information in variable field (cc 17-64)
13-14	Blank
15-16	ESDID of first SD, XD, CM, PC, or ER in variable field
17-64	Variable field. One to three 16-byte items of the following format: 8 bytes -- Name, padded with blanks 1 byte -- ESD type code 3 bytes -- Address 1 byte -- Alignment if XD; otherwise blank 3 bytes -- Length, LDID, or blank
65-72	Blank
73-76	Deck ID (from first TITLE card)
77-80	Card sequence number

END CARD FORMAT

The format of the END card is as follows:

<u>Columns</u>	<u>Contents</u>
1	12-2-9 punch
2-4	END
5	Blank
6-8	Entry address from operand of END card in source deck (blank if no operand)

9-14	Blank
15-16	ESDID of entry point (blank if no operand)
17-72	Blank
73-76	Deck ID (from first TITLE card)
77-80	Card sequence number

TESTRAN (SYM) CARD FORMAT

If requested by the user, the assembler punches out symbolic information for TESTRAN concerning the assembled program. This output appears ahead of all loader text. The format of the card images for TESTRAN output is as follows:

<u>Columns</u>	<u>Contents</u>
1	12-2-9 punch
2-4	SYM
5-10	Blank
11-12	Variable field count -- number of bytes of text in variable field (cc 17-72)
13-16	Blank
17-72	Variable field (see below)
73-76	Deck ID (from first TITLE card)
77-80	Card sequence number

The variable field (columns 17-72) contains up to 56 bytes of TESTRAN text. The items making the text are packed together, consequently only the last card may contain less than 56 bytes of text in the variable field. The formats of a text card and an individual text item are shown in Figure 6. The contents of the fields within an individual entry are as follows:

1. Organization (1 byte)
  - Bit 0:
    - 0 = non-data type
    - 1 = data type
  - Bits 1-3 (if non-data type):
    - 000 = space
    - 001 = control section
    - 010 = dummy control section
    - 011 = common
    - 100 = instruction
    - 101 = CCW

- Bit 1 (if data type):
  - 0 = no multiplicity
  - 1 = multiplicity (indicates presence of M field)
- Bit 2 (if data type):
  - 0 = independent (not a packed or zoned decimal constant)
  - 1 = cluster (packed or zoned decimal constant)
- Bit 3 (if data type):
  - 0 = no scaling
  - 1 = scaling (indicates presence of S field)
- Bit 4:
  - 0 = name present
  - 1 = name not present

Bits 5-7:

2. Address (3 bytes) - displacement from base of control section
3. Symbol Name (0-8 bytes) - symbolic name of particular item

NOTE: The following fields are only present for data-type items.

4. Data Type (1 byte) - contents in hexadecimal
  - 00 = character
  - 04 = hexadecimal
  - 08 = binary
  - 10 = fixed point, full
  - 14 = fixed point, half
  - 18 = floating point, short
  - 1C = floating point, long
  - 20 = A-type or Q-type data
  - 24 = Y-type data
  - 28 = S-type data
  - 2C = V-type data
  - 30 = packed decimal
  - 34 = zoned decimal
5. Length (2 bytes for character, hexadecimal, or binary items; 1 byte for other types) - length of data item minus 1
6. Multiplicity - M field (3 bytes) - equals 1 if not present
7. Scale - signed integer - S field (2 bytes) - present only for F, H, E, D, P and Z type data, and only if scale is non-zero.




Figure 6. TESTRAN SYM Card Format

APPENDIX C. ASSEMBLER F PROGRAM LISTING

The Assembler F listing shown in this appendix results from assembling the source program documented in an appendix to the Assembler Language publication. For easy reference to the explanations that appear in the section

The Assembler Listing, the headings on the listing are numbered.

Since there were no errors in the assembly, a diagnostic list was not produced. Each of the following pages represents one printer-produced listing page.

EXAM SYMBOL	(2) TYPE	(3) ID	(4) ADDR	(5) LENGTH	(6) LD ID	EXTERNAL SYMBOL DICTIONARY	PAGE 1 00.16 4/11/66
(1) SAMPLR	SD	01	000000	000388			

⑦  
EXAM

⑨  
PAGE 1

⑩  
LOC

⑪  
OBJECT CODE

⑫  
ADDR1 ADDR2

⑬  
STMT

⑭  
SOURCE STATEMENT

⑮  
F 14FEB66

⑯  
4/11/66

```
1 **      THIS IS THE EXECUTABLE SAMPLE PROGRAM SHOWN IN THE SRL - *
2 **      ASSEMBLER LANGUAGE MANUAL.           - *
```

⑩ LUC      ⑪ UBJECT CODE      ⑫ ADDR1 ADDR2      ⑬ STMT      ⑭ SOURCE STATEMENT

⑮ F 14FEB66      ⑯ 4/11/66

	4	PRINT DATA	⑰ SAMPL002
	5 *		SAMPL003
	6 *	THIS IS THE MACRO DEFINITION	SAMPL004
	7 *		SAMPL005
	8	MACRO	SAMPL006
	9	MOVE &TO,&FROM	SAMPL007
	10 .*		SAMPL008
	11 .*	DEFINE SETC SYMBOL	SAMPL009
	12 .*		SAMPL010
	13	LCLC &TYPE	SAMPL011
	14 .*		SAMPL012
	15 .*	CHECK NUMBER OF OPERANDS	SAMPL013
	16 .*		SAMPL014
	17	AIF (N'&SYSLIST NE 2).ERROR1	SAMPL015
	18 .*		SAMPL016
	19 .*	CHECK TYPE ATTRIBUTES OF OPERANDS	SAMPL017
	20 .*		SAMPL018
	21	AIF (T'&TO NE T'&FROM).ERROR2	SAMPL019
	22	AIF (T'&TO EQ 'C' OR T'&TO EQ 'G' OR T'&TO EQ 'K').TYPECGK	SAMPL020
	23	AIF (T'&TO EQ 'D' OR T'&TO EQ 'E' OR T'&TO EQ 'H').TYPEDEH	SAMPL021
	24	AIF (T'&TO EQ 'F').MOVE	SAMPL022
	25	AGO .ERROR3	SAMPL023
	26	.TYPEDEH ANOP	SAMPL024
	27 .*		SAMPL025
	28 .*	ASSIGN TYPE ATTRIBUTE TO SETC SYMBOL	SAMPL026
	29 .*		SAMPL027
	30 &TYPE	SETC T'&TO	SAMPL028
	31 .MOVE	ANOP	SAMPL029
	32 *	NEXT TWO STATEMENTS GENERATED FOR MOVE MACRO	SAMPL030
	33	L&TYPE 2,&FROM	SAMPL031
	34	ST&TYPE 2,&TO	SAMPL032
	35	MEXIT	SAMPL033
	36 .*		SAMPL034
	37 .*	CHECK LENGTH ATTRIBUTES OF OPERANDS	SAMPL035
	38 .*		SAMPL036
	39 .TYPECGK	AIF (L'&TO NE L'&FROM OR L'&TO GT 256).ERROR4	SAMPL037
	40 *	NEXT STATEMENT GENERATED FOR MOVE MACRO	SAMPL038
	41	MVC &TO,&FROM	SAMPL039
	42	MEXIT	SAMPL040
	43 .*		SAMPL041
	44 .*	ERROR MESSAGES FOR INVALID MOVE MACRO INSTRUCTIONS	SAMPL042
	45 .*		SAMPL043
	46 .ERROR1	MNOTE 1,'IMPROPER NUMBER OF OPERANDS, NO STATEMENTS GENERATED'	SAMPL044
	47	MEXIT	SAMPL045
	48 .ERROR2	MNOTE 1,'OPERAND TYPES DIFFERENT, NO STATEMENTS GENERATED'	SAMPL046
	49	MEXIT	SAMPL047
	50 .ERROR3	MNOTE 1,'IMPROPER OPERAND TYPES, NO STATEMENTS GENERATED'	SAMPL048
	51	MEXIT	SAMPL049
	52 .ERROR4	MNOTE 1,'IMPROPER OPERAND LENGTHS, NO STATEMENTS GENERATED'	SAMPL050
	53	MEND	SAMPL051
	54 *		SAMPL052
	55 *	MAIN ROUTINE	SAMPL053
	56 *		SAMPL054
000000	57 SAMPLR	CSECT	SAMPL055
	58 BEGIN	SAVE (14,12),,*	SAMPL056

7

8

9

EXAM SAMPLE PROGRAM

PAGE 3

10

11

12

13

14

15

16

LCG

OBJECT CODE

ADDR1 ADDR2

STMT

SOURCE STATEMENT

F 14FEB66 4/11/66

```

000000 47F0 F00A          0000A  59+BEGIN  B    10(0,15) BRANCH AROUND ID
000004 05                60+    DC    AL1(5)
000005 C2L5C7C9D5        61+    DC    CL5*BEGIN* IDENTIFIER
00000A 90EC D00C          0000C  62+    STM  14,12,12(13) SAVE REGISTERS
00000E 05C0                63    BALR R12,0    ESTABLISH ADDRESSABILITY OF PROGRAM
000010 50L0 C0B8          0000C  64    USING *,R12   AND TELL THE ASSEMBLER WHAT BASE TO USE
000014 9857 C390          003A0  65    ST    13,SAVE13
000000                66    LM    R5,R7,=(ALISTAREA,16,LISTEND) LOAD LIST AREA PARAMETERS
000018 45E0 C0BE          000CE  67    USING LIST,R5 REGISTER 5 POINTS TO THE LIST
00001C 9180 C0BC          000CC  68 MORE     BAL  R14,SEARCH  FIND LIST ENTRY IN TABLE
000020 4710 C0B0          000C0  69          TM  SWITCH,NONE CHECK TO SEE IF NAME WAS FOUND
000000                70          BD  NOTTHERE   BRANCH IF NOT
000000                71    USING TABLE,R1 REGISTER 1 NOW POINTS TO TABLE ENTRY
000000                72    MOVE TSWITCH,LSWITCH  MOVE FUNCTIONS
000024 D200 1003 5008 00003 00008  73+*     NEXT STATEMENT GENERATED FOR MOVE MACRO
000000                74+    MVC  TSWITCH,LSWITCH
000000                75    MOVE TNUMBER,LNUMBER          FROM LIST ENTRY
00002A D202 1000 5009 00000 00009  76+*     NEXT STATEMENT GENERATED FOR MOVE MACRO
000000                77+    MVC  TNUMBER,LNUMBER
000000                78    MOVE ADDRESS,LADDRESS      TO TABLE ENTRY
000000                79+*     NEXT TWO STATEMENTS GENERATED FOR MOVE MACRO
000030 5E20 500C          0000C  80+    L    2,LADDRESS
000034 5020 1004          00004  81+    ST    2,TADDRESS
000038 8756 C008          00018  82 LISTLOOP BXLE R5,R6,MORE  LOOP THROUGH THE LIST
00003C D5EF C240 C0F0 00250 00100  83    CLC  TESTTABL(240),TABLAREA
000042 4770 C07C          0008C  84          BNE  NOTRIGHT
000046 D55F C330 C1E0 00340 001F0  85    CLC  TESTLIST(96),LISTAREA
00004C 4770 C07C          0008C  86          BNE  NOTRIGHT
000050                87    WTD  *ASSEMBLER SAMPLE PROGRAM SUCCESSFUL*
000050                88+    CNOP 0,4
000050 4510 C06C          0007C  89+    BAL  1,IHB0005A BRANCH AROUND MESSAGE
000054 0027                90+    DC  AL2(IHB0005-*) MESSAGE LENGTH
000056 0000                91+    DC  AL2(0)
000058 C1E2E2C5D4C2D3C5  92+    DC  C*ASSEMBLER SAMPLE PROGRAM SUCCESSFUL* MESSAGE
000060 D940E2C1D407D3C5
000068 40D7D9D6C7D9C1D4
000070 40E2E4C3C3C5E2E2
000078 C6E4D3
00007B                93+IHB0005 EQU  *
00007C                94+IHB0005A DS  0H
00007E 0A23                95+    SVC  35 ISSUE SVC
00007E 58D0 C0B8          000C8  96 EXIT    L    R13,SAVE13
000000                97    RETURN (14,12),RC=0
000082 98EC D00C          0000C  98+    LM  14,12,12(13) RESTORE THE REGISTERS
000086 41F0 0000          00000  99+    LA  15,0(0,0) LOAD RETURN CODE
00008A 07FE                100+   BR  14 RETURN
000000                101 *
00008C                102 NOTRIGHT WTD  *ASSEMBLER SAMPLE PROGRAM UNSUCCESSFUL*
000000                103+   CNOP 0,4
00008C 4510 COAA          000BA  104+NOTRIGHT BAL  1,IHB0007A BRANCH AROUND MESSAGE
000090 0029                105+   DC  AL2(IHB0007-*) MESSAGE LENGTH
000092 0000                106+   DC  AL2(0)
000094 C1E2E2C5D4C2D3C5  107+   DC  C*ASSEMBLER SAMPLE PROGRAM UNSUCCESSFUL* MESSAGE
00009C D940E2C1D407D3C5
0000A4 40D7D9D6C7D9C1D4

```

17

SAMPL057

SAMPL058

SAMPL059

SAMPL060

SAMPL061

SAMPL062

SAMPL063

SAMPL064

SAMPL065

SAMPL066

SAMPL067

SAMPL068

SAMPL069

SAMPL070

SAMPL071

SAMPL072

SAMPL073

SAMPL074

SAMPL075

SAMPL076

SAMPL077

SAMPL078

7	8	10	11	12	13	14	15	16	17
EXAM	SAMPLE PROGRAM	LUC	OBJECT CODE	ADDR1	ADDR2	STMT	SOURCE STATEMENT		
0000AC	40E4D5E2E4C3C3C5								
0000B4	E2E2C6E4D3								
0000B9						108+IH80007	EQU *		
0000BA						109+IH80007A	DS OH		
0000BA	0A23					110+	SVC 35 ISSUE SVC		
0000BC	47F0 C06E				0007E	111	B EXIT		SAMPL079
0000C0	9680 5008			00008		112 NOTTHERE	OI LSWITCH,NONE TURN ON SWITCH IN LIST ENTRY		SAMPL080
0000C4	47FC C028				00038	113	B LISTLOOP GO BACK AND LOOP		SAMPL081
0000C8	00000000					114 SAVE13	DC F'0'		SAMPL082
0000CC	00					115 SWITCH	DC X'00'		SAMPL083
0000B0						116 NONE	EQU X'80'		SAMPL084
						117 *			SAMPL085
						118 *	BINARY SEARCH ROUTINE		SAMPL086
						119 *			SAMPL087
0000CD	00					120 SEARCH	NI SWITCH,255-NONE TURN OFF NOT FOUND SWITCH		SAMPL088
0000CE	947F C08C			000CC		121	LM R1,R3,=F'128,4,128' LOAD TABLE PARAMETERS		SAMPL089
0000D2	9813 C39C			003AC		122	LA R1,TABLAREA-16(R1) GET ADDRESS OF MIDDLE ENTRY		SAMPL090
0000D6	4111 C0E0			000F0		123 LOOP	SRL R3,1 DIVIDE INCREMENT BY 2		SAMPL091
0000DA	8830 0001			00001		124	CLC LNAME,TNAME COMPARE LIST ENTRY WITH TABLE ENTRY		SAMPL092
0000DE	0507 5000	1008	00000	00008		125	BH HIGHER BRANCH IF SHOULD BE HIGHER IN TABLE		SAMPL093
0000E4	4720 C0E4			000F4		126	BCR 8,R14 EXIT IF FOUND		SAMPL094
0000E8	078E					127	SR R1,R3 OTHERWISE IT IS LOWER IN THE TABLE		XSAMPL095
0000EA	1B13								SAMPL096
0000EC	4620 COCA			000DA	128	BCT R2,LOOP LOOP 4 TIMES			SAMPL097
0000F0	47F0 COEA			000FA	129	B NOTFOUND ARGUMENT IS NOT IN THE TABLE			SAMPL098
0000F4	1A13				130 HIGHER	AR R1,R3 ADD INCREMENT			SAMPL099
0000F6	4620 COCA			000DA	131	BCT R2,LOOP LOOP 4 TIMES			SAMPL100
0000FA	9680 C08C			000CC	132 NOTFOUND	OI SWITCH,NONE TURN ON NOT FOUND SWITCH			SAMPL101
0000FE	07FE				133	BR R14 EXIT			SAMPL102
					134 *				SAMPL103
					135 *	THIS IS THE TABLE			SAMPL104
					136 *				SAMPL105
000100					137	DS OD			SAMPL106
000100	0000000000000000				138	TABLAREA DC XL8'O',CL8'ALPHA'			SAMPL107
000108	C1D3D7C8C1404040								
000110	0000000000000000				139	DC XL8'O',CL8'BETA'			SAMPL108
000118	C2L5E3C140404040								
000120	0000000000000000				140	DC XL8'O',CL8'DELTA'			SAMPL109
000128	C4C5D3E3C1404040								
000130	0000000000000000				141	DC XL8'O',CL8'EPSILON'			SAMPL110
000138	C5D7E2C9D3D6D540								
000140	0000000000000000				142	DC XL8'O',CL8'ETA'			SAMPL111
000148	C5E3C14040404040								
000150	0000000000000000				143	DC XL8'O',CL8'GAMMA'			SAMPL112
000158	C7C1D4D4C1404040								
000160	0000000000000000				144	DC XL8'O',CL8'IOTA'			SAMPL113
000168	C9D6E3C140404040								
000170	0000000000000000				145	DC XL8'O',CL8'KAPPA'			SAMPL114
000178	D2C1D7D7C1404040								
000180	0000000000000000				146	DC XL8'O',CL8'LAMBDA'			SAMPL115
000188	D3C1D4C2C4C14040								
000190	0000000000000000				147	DC XL8'O',CL8'MU'			SAMPL116
000198	D4E4404040404040								
0001A0	0000000000000000				148	DC XL8'O',CL8'NU'			SAMPL117

(7) EXAM	(8) SAMPLE PROGRAM	(12) ADDR1	(13) ADDR2	(14) STMT	(14) SOURCE STATEMENT	(9) PAGE	(15) F 14FEB66	(16) 4/11/66	(17) 5
(10) LOC	(11) OBJECT CODE								
0001A8	D5E4404040404040			149	DC XL8*0*,CL8*OMICRON*				SAMPL118
0001B0	0000000000000000								
0001B8	D6D4C9C3D9D6D540			150	DC XL8*0*,CL8*PHI*				SAMPL119
0001C0	0000000000000000								
0001C8	D7C8C94040404040			151	DC XL8*0*,CL8*SIGMA*				SAMPL120
0001D0	0000000000000000								
0001D8	E2C9C7D4C1404040			152	DC XL8*0*,CL8*ZETA*				SAMPL121
0001E0	0000000000000000								
0001E8	E9C5E3C140404040			153 *					SAMPL122
				154 *	THIS IS THE LIST				SAMPL123
				155 *					SAMPL124
0001F0	D3C1D4C2C4C14040			156	LISTAREA DC CL8*LAMBDA*,X*0A*,FL3*29*,A(BEGIN)				SAMPL125
0001F8	0A00001D0000000000								
000200	E9C5E3C140404040			157	DC CL8*ZETA*,X*05*,FL3*5*,A(LOOP)				SAMPL126
000208	C50000050000000A								
000210	E3C8C5E3C1404040			158	DC CL8*THETA*,X*02*,FL3*45*,A(BEGIN)				SAMPL127
000218	0200002D00000000								
000220	E3C1E44040404040			159	DC CL8*TAU*,X*00*,FL3*0*,A(1)				SAMPL128
000228	0000000000000001								
000230	D3C9E2E340404040			160	DC CL8*LIST*,X*1F*,FL3*465*,A(0)				SAMPL129
000238	1F00C1D100000000								
000240	C1E3D7C8C1404040			161	LISTEND DC CL8*ALPHA*,X*00*,FL3*1*,A(123)				SAMPL130
000248	000000100000078								
				162 *					SAMPL131
				163 *	THIS IS THE CONTROL TABLE				SAMPL132
				164 *					SAMPL133
000250				165	DS OD				SAMPL134
000258	0000010000000078			166	TESTTABL DC FL3*1*,X*00*,A(123),CL8*ALPHA*				SAMPL135
000258	C1D3D7C8C1404040								
000260	0000000000000000			167	DC XL8*0*,CL8*BETA*				SAMPL136
000268	C2C5E3C140404040								
000270	0000000000000000			168	DC XL8*0*,CL8*DELTA*				SAMPL137
000278	C4C5D3E3C1404040								
000280	0000000000000000			169	DC XL8*0*,CL8*EPSILON*				SAMPL138
000288	C5D7E2C9D3D6D540								
000290	0000000000000000			170	DC XL8*0*,CL8*ETA*				SAMPL139
000298	C5E3C14040404040								
0002A0	0000000000000000			171	DC XL8*0*,CL8*GAMMA*				SAMPL140
0002A8	C7C1D4D4C1404040								
0002B0	0000000000000000			172	DC XL8*0*,CL8*IOTA*				SAMPL141
0002B8	C9D6E3C140404040								
0002C0	0000000000000000			173	DC XL8*0*,CL8*KAPPA*				SAMPL142
0002C8	D2C1D7D7C1404040								
0002D0	00001D0A00000000			174	DC FL3*29*,X*0A*,A(BEGIN),CL8*LAMBDA*				SAMPL143
0002D8	D3C1D4C2C4C14040								
0002E0	0000000000000000			175	DC XL8*0*,CL8*MU*				SAMPL144
0002E8	D4E4404040404040								
0002F0	0000000000000000			176	DC XL8*0*,CL8*NU*				SAMPL145
0002F8	D5E4404040404040								
000300	0000000000000000			177	DC XL8*0*,CL8*OMICRON*				SAMPL146
000308	D6D4C9C3D9D6D540								
000310	0000000000000000			178	DC XL8*0*,CL8*PHI*				SAMPL147
000318	D7C8C94040404040								
000320	0000000000000000			179	DC XL8*0*,CL8*SIGMA*				SAMPL148

⑦ EXAM	⑧ SAMPLE PROGRAM	⑫ ADDR1	⑬ ADDR2	⑭ STMT	SOURCE STATEMENT	⑨ PAGE	⑩ LOC	⑪ OBJECT CODE	⑮ F 14FEB66	⑯ 4/11/66	⑰ SAMPL
000328	E2C9C7D4C1404040			180	DC						SAMPL149
000330	00000505000000DA										
000338	E9C5E3C140404040										
				181 *							SAMPL150
				182 *	THIS IS THE CONTROL LIST						SAMPL151
				183 *							SAMPL152
000340	D3C1D4C2C4C14040			184	TESTLIST DC						SAMPL153
000348	0A00001D00000000										
000350	E9C5E3C140404040			185	DC						SAMPL154
000358	05000005000000DA										
000360	E3C8C5E3C1404040			186	DC						SAMPL155
000368	8200002D00000000										
000370	E3C1E4404C404040			187	DC						SAMPL156
000376	8C00000000000001										
000380	D3C9E2E340404040			188	DC						SAMPL157
000388	9F0001D100000000										
000390	C1D3D7C8C1404040			189	DC						SAMPL158
000398	06000010000007B										
				190 *							SAMPL159
				191 *	THESE ARE THE SYMBOLIC REGISTERS						SAMPL160
				192 *							SAMPL161
000000				193	R0 EQU 0						SAMPL162
000001				194	R1 EQU 1						SAMPL163
000002				195	R2 EQU 2						SAMPL164
000003				196	R3 EQU 3						SAMPL165
000005				197	R5 EQU 5						SAMPL166
000006				198	R6 EQU 6						SAMPL167
000007				199	R7 EQU 7						SAMPL168
00000C				200	R12 EQU 12						SAMPL169
00000D				201	R13 EQU 13						SAMPL170
00000E				202	R14 EQU 14						SAMPL171
00000F				203	R15 EQU 15						SAMPL172
				204 *							SAMPL173
				205 *	THIS IS THE FORMAT DEFINITION OF LIST ENTRIES						SAMPL174
				206 *							SAMPL175
000000				207	LIST DSECT						SAMPL176
000000				208	LNAME DS CL8						SAMPL177
000008				209	LSWITCH DS C						SAMPL178
000009				210	LNUMBER DS FL3						SAMPL179
000000				211	LADDRESS DS F						SAMPL180
				212 *							SAMPL181
				213 *	THIS IS THE FORMAT DEFINITION OF TABLE ENTRIES						SAMPL182
				214 *							SAMPL183
000000				215	TABLE DSECT						SAMPL184
000000				216	TNUMBER DS FL3						SAMPL185
000003				217	TSWITCH DS C						SAMPL186
000004				218	TADDRESS DS F						SAMPL187
000008				219	TNAME DS CL8						SAMPL188
000000				220	END BEGIN						SAMPL189
0003A0	000001F0			221	=A(LISTAREA,16,LISTEND)						
0003A4	0000008000000004			222	=F*128,4,128*						
0003AC	00000080										

⑦  
EXAM

RELOCATION DICTIONARY

⑨  
PAGE 1  
⑩  
4/11/66

⑧ POS-ID	⑨ REL-ID	⑩ FLAGS	⑪ ADDRESS
01	01	0C	0001FC
01	01	0C	00020C
01	01	0C	00021C
01	01	0C	0002D4
01	01	0C	000334
01	01	0C	00034C
01	01	0C	00035C
01	01	0C	00036C
01	01	0C	0003A0

7  
EXAM

CROSS-REFERENCE

9  
PAGE 1  
16  
4/11/66

(22) SYMBOL	(23) LEN	(24) VALUE	(25) UDFN	(26) REFERENCES
BEGIN	00004	000000	0059	0156 0158 0174 0184 0186 0220
EXIT	00004	00007E	0096	0111
HIGHER	00002	0000F4	0130	0125
IHB0005	00001	00007B	0093	0090
IHB0005A	00002	00007C	0094	0089
IHB0007	00001	000089	0108	0105
IHB0007A	00002	00008A	0109	0104
LADDRESS	00004	00000C	0211	0080
LIST	00001	000000	0207	0067
LISTAREA	00008	0001F0	0156	0066 0085 0221
LISTEND	00008	000240	0161	0066 0221
LISTLOOP	00004	000038	0082	0113
LNAME	00008	000000	0208	0124
LNUMBER	00003	000009	0210	0077
LOOP	00004	0000DA	0123	0128 0131 0157 0180 0185
LSWITCH	00001	000008	0209	0074 0112
MORE	00004	000018	0068	0082
NONE	00001	000080	0116	0069 0112 0120 0132
NOTFOUND	00004	0000FA	0132	0129
NOTRIGHT	00004	00008C	0104	0084 0086
NOTTHERE	00004	0000C0	0112	0070
R0	00001	000000	0193	
R1	00001	000001	0194	0071 0121 0122 0122 0127 0130
R12	00001	00000C	0200	0063 0064
R13	00001	00000D	0201	0096
R14	00001	00000E	0202	0068 0126 0133
R15	00001	00000F	0203	
R2	00001	000002	0195	0128 0131
R3	00001	000003	0196	0121 0123 0127 0130
R5	00001	000005	0197	0066 0067 0082
R6	00001	000006	0198	0082
R7	00001	000007	0199	0066
SAMPLR	00001	000000	0057	0220
SAVE13	00004	0000C8	0114	0065 0096
SEARCH	00004	0000CE	0120	0068
SWITCH	00001	0000CC	0115	0069 0120 0132
TABLAREA	00008	000100	0138	0083 0122
TABLE	00001	000000	0215	0071
TADDRESS	00004	000004	0218	0081
TESTLIST	00008	000340	0184	0085
TESTTABL	00003	000250	0166	0083
TNAME	00008	000008	0219	0124
TNUMBER	00003	000000	0216	0077
TSWITCH	00001	000003	0217	0074

NO STATEMENTS FLAGGED IN THIS ASSEMBLY  
351 PRINTED LINES

APPENDIX D. DYNAMIC INVOCATION OF THE ASSEMBLER

The Assembler can be invoked by a problem program at execution time through the use of the CALL, LINK, XCTL, or ATTACH macro instructions. If the XCTL macro instruction is used to invoke the Assembler, then no user options may be stated. The Assembler will use the standard default, as set during system generation, for each option.

If the Assembler is invoked by CALL, LINK, or ATTACH, the user may supply:

- 1) The Assembler options
- 2) The ddnames of the data sets to be used during processing

Name	Operation	Operand
[symbol]	CALL	IEUASM, (optionlist [,ddnamelist]), VL
	{LINK ATTACH}	EP=IEUASM, PARAM=(optionlist [,ddnamelist]), VL=1

EP - specifies the symbolic name of the Assembler. The entry point at which execution is to begin is determined by the control program (from the library directory entry).

PARAM - specifies, as a sublist, address parameters to be passed from the problem program to the Assembler. The first word in the address parameter list contains the address of the option list. The second word contains the address of the ddname list.

optionlist - specifies the address of a variable length list containing the options. This address must be written even if no option list is provided.

The option list must begin on a half-word boundary. The first two bytes contain a count of the number of bytes in the remainder of the list. If no options are specified, the count must be zero. The option list is free form with each field separated by a comma. No blanks or zeros should appear in the list.

ddnamelist - specifies the address of a variable length list containing alternate ddnames for the data sets used during compiler processing. If standard ddnames are used then this operand may be omitted.

The ddname list must begin on a half-word boundary. The first two bytes contain a count of the number of bytes in the remainder of the list. Each name of less than eight bytes must be left-justified and padded with blanks. If an alternate ddname is omitted, the standard name will be assumed. If the name is omitted within the list, the 8-byte entry must contain binary zeros. Names can be omitted from the end merely by shortening the list. The sequence of the 8-byte entries in the ddname list is as follows:

Entry Alternate Name

- |    |                |
|----|----------------|
| 1  | not applicable |
| 2  | not applicable |
| 3  | not applicable |
| 4  | SYSLIB         |
| 5  | SYSIN          |
| 6  | SYSPRINT       |
| 7  | SYSPUNCH       |
| 8  | SYSUT1         |
| 9  | SYSUT2         |
| 10 | SYSUT3         |
| 11 | SYSGO          |

VL - specifies that the sign bit is to be set to 1 in the last word of the address parameter list.



INDEX

- Access methods 3
  - BPAM (basic partitioned) 3
  - BSAM (basic sequential) 3
  - QSAM (queued sequential) 3
- ASMFC, cataloged procedure for assembly 6
- ASMFCCL, cataloged procedure for assembly and linkage editing 7
- ASMFCCLG, cataloged procedure for assembly, linkage editing, and execution 8
- Assembler cataloged procedures (see cataloged procedures)
- Assembler data sets (see data sets)
- Assembler listing 10
  - cross reference 13
  - diagnostics 14
  - external symbol dictionary 10
  - relocation dictionary 13
  - source and object program 12
  - statistical messages 10
- Assembler options 2
  - default entry 2
- Assembler portion limitations 20
  
- Blocking and buffering information 14
- BPAM (Basic Partitioned Access Method) 3
- BSAM (Basic Sequential Access Method) 3
  
- Cataloged procedures 6
  - for assembling (ASMFC) 6
  - for assembling and linkage editing (ASMFCCL) 7
  - for assembling, linkage editing, and execution (ASMFCCLG) 8
  - overriding 9
- COND= parameter 5, 7-9
- Cross reference listing 13
  
- Data sets 2-5
  - SYSGO 2,3
  - SYSIN 2,3
  - SYSLIB 2,3
  - SYSPRINT 2,3
  - SYSPUNCH 2,3
  - SYSUT1, SYSUT2, SYSUT3 2,3
- DCB macro instruction 3
- DD statements 9
  - ddnames 3
- Default entry 2
- Defining data set characteristics 3
- Device naming conventions (Table 3) 6
- Diagnostics
  - listing 14
  - messages 21
- Dictionaries 17
  - additional requirements 19
  - global 17
  - local 17
- Dictionary size and source statement complexity 16
- Dynamic Invocation of the Assembler (Appendix D) 41
  
- END card format 29
- ESD card format 29
- EXEC statements 9
- External Symbol Dictionary (ESD) listing 10
  
- Global dictionary
  - at collection time 18
  - at generation time 18
  
- IEBUPDAT utility program 16
  
- Job control statements 1
- Job steps 1
  
- Linkage statements (Figure 5) 17
- Listing, assembler (see assembler listing)
- Load module modification - entry point restatement 16
- Local dictionary
  - at collection time 18
  - at generation time 19
  
- Macro-definition library additions 15
- Macro-definition local definition parameter table (Table 9) 19
- Macro generation and conditional assembly limitations 20
- Messages
  - diagnostic 21
  - statistical 10
  
- Object deck output 29
  - END card 29
  - ESD card 29
  - RLD card 29
  - TESTRAN SYM card 30
  - TEXT (TXT) card 29
- Object module linkage 16
- Options, assembler 2
  - default entry 2
- Overriding statements in cataloged procedures 9
  
- PARM field access 15
- PARM= parameter 2,9
- Procedure (definition) 1
- Program listing 31
- Program termination 15
  
- QSAM (Queued Sequential Access Method) 3
  
- Relocation Dictionary listing 13
- Return codes 5
- RLD card format 29
  
- Sample program listing 31
- Saving and restoring general register contents 15

Severity code  
  for diagnostic messages 21-28  
  relation to return code 5  
Source and object program  
  listing 12  
Source statement complexity 19  
SPACE assembler instruction 10  
Statistical messages 10  
SYSGO 3  
SYSIN 2,3

SYSLIB 2, 3  
SYSPRINT 2, 3  
SYSPUNCH 2, 3  
SYSUT1,2,3 2,3  
  
TESTRAN (SYM) card format 30  
TEXT (TXT) card format 29  
Type designators 10  
Types of ESD entries (Table 4) 10  
Utility data sets 2,3





**International Business Machines Corporation**  
**Data Processing Division**  
**112 East Post Road, White Plains, N.Y. 10601**  
**[USA Only]**

**IBM World Trade Corporation**  
**821 United Nations Plaza, New York, New York 10017**  
**[International]**



File Number S360-21

Re: Form No. C26-3756-2

This Newsletter No. N26-0567

Date November 15, 1967

Previous Newsletter Nos. None

IBM System/360 Operating System Assembler (F) Programmer's Guide

The attached pages bring the above publication up to date. Changes are indicated by a vertical line at the left of affected text, a bullet (●) at the left of the title of a changed illustration, and a bullet beside the page number of a page that should be reviewed in its entirety. Pages that contain changes are coded in the upper outside corner.

Replace the following pages:

iii and iv  
1 and 2  
3 and 4  
5 and 6  
7 and 8  
9 and 10  
29 and 30  
41 and 42

Add the following pages:

9.1 and 10  
43 and 44

The changes documented by the attached replacement pages include,

- Change the default entry to specify LINECNT=55 (Release 14).
- Delete a SYSLIB restriction (Release 13).
- Add Dynamic Invocation of the Assembler (Release 14).
- Revise Table 1.
- Add two examples for overriding cataloged procedures.
- Miscellaneous format, editorial and technical corrections.

File this cover letter at the back of the publication. It will then serve as a record of the changes received and incorporated.

