



interface systems inc.

# MODEL 2240

PLUG COMPATIBLE PRINTER FOR 3270 SYSTEM



**The model 2240 is plug compatible with your IBM 3270 communications system. It will replace the 328x without software changes. Just plug it in and run your application.**

## LOW COST

Compact and portable, the model 2240 printer is a low cost replacement for the IBM 328x printer. The 2240 prints at 120 cps and is ideally suited for the office environment.

## ELECTRONICS

All interfacing and Large Scale Integration control logic is housed in the printer chassis. This means the printer may be placed on a table top and can be easily moved.

## ADJUSTABLE FORMS TRACTOR

Use standard pin feed forms of varying sizes from 4" to 14 $\frac{7}{8}$ ". This printer has adjustable sprockets which means that you don't have to change platens (there aren't any) when changing paper widths.

## SPECIAL FEATURES

Take advantage of the special features offered such as: skip to top of form, vertical tab to a predetermined spot, or elongation of characters for highlighting, which adds special emphasis. These features are particularly advantageous when using pre-printed forms, or in large volume applications — and they are yours at no extra cost.

## READABILITY

The Model 2240 uses 9 x 7 dot matrix for easy readability. Characters are distinct and well defined.

## SERVICE

Service is available nationwide. For a detailed map of coverage, contact our office.

## SPECIFICATIONS

<b>Printing Rate</b>	120 characters per second bi-directional
<b>Character Structure</b>	9 x 7 dot matrix, 10 point type equivalent
<b>Code</b>	EBCDIC - 64 characters printed
<b>Switch Controls</b>	ON/OFF, SELECT, FORMS OVERRIDE, LINE FEED, TOP OF FORM
<b>Indicators</b>	PAPER OUT, SELECT
<b>Manual Controls</b>	Form Thickness, Paper Advance Knob
<b>Format</b>	132 characters maximum per line, 6 lines per inch
<b>Paper Feed</b>	Sprocket feed, adjustable to 14 $\frac{7}{8}$ " width
<b>Number of Copies</b>	Original and up to four carbon copies
<b>Dimensions</b>	7" high, 18" deep, 24.5" wide
<b>Weight</b>	60 pounds
<b>Electrical Requirements</b>	115 VAC $\pm$ 10%, 60 Hz.
<b>Temperature</b>	—Operating 40° to 100° F —Storage -40° to 160° F
<b>Humidity</b>	—Operating 5% to 90% (no condensation) —Storage 0% to 95%

Specifications subject to change without notice.

## ADDITIONAL MODELS

### Model 2360

The Model 2360 is identical in appearance and other specifications to the 2240, but prints at a rate of 180 cps bi-directional or 135 lpm for 80 character lines.

### Model 4100SC

Those special label applications you would like to run on your IBM 3270 system are now possible with the ISI 4100SC printer. Large letters, forms graphics, and bar codes can all be printed under program control on the 4100SC.

Select the model to fit your requirements and give us a call.



## FEATURES

- High throughput rates
- Outstanding reliability
- Usable either as a table top model or with optional printer stand
- Vertical forms control with paper tape or program loading
- Elongated character printing
- Simple operator control panel
- Manual top of form control
- Large 9 x 7 dot matrix
- Bottom or rear feed option
- Multiple part forms capability
- Prints forms 4" to 14 $\frac{7}{8}$ " wide
- Based on the rugged Centronics 700 series printers



**interface systems inc.**

462 Jackson Plaza Ann Arbor, Mi. 48103  
Telephone (313) 769-5900 TWX 8102236058