lip

MASSACHUSETTS INSTITUTE OF TECHNOLOGY PROJECT MAC

Artificial Intelligence Project
Programs Nemo No. 108

Manogandum MAC-M-329 October 1966

A Printing Control P Posture

Donald E. Restlake III

A program, some TECO macros, and some small modifications to existing systems software have been written, called PRO, whose purpose is to reduce the large number of control languages and system programs it has been neccessary to know about and the large amount of redundant typing it has been necessary to do to effectively use the MAC PDP-6 system. PRO allows a user knowing the command languages on only TECO, DDT, and PRO to effectively edit and debug small absolute programs with a minimum of command typing overhead (systems of this sort are called control P features for historic reasons). The remainder of this memo, which describes PRO and its use in detail, assumes some knowledge of TECO, DDT, and the MAC PDP-6 system. (In this memo the symbol \$ always stands for the character ALT MOD).

PRO may be initially entered from MACDMP when it is looking at the MACDMP system tape by light penning the word "PRO" on the display screen or by typing "PRO" followed by a carriage return. If one is in TECO one may type "lERPRO2\$YHXJMJ\$\$". Note that entering PRO this way will destroy TECO's buffer and various of its Q registers (see Appendix B). When control is transfered to the TECO macro in Q register P, which is the heart of PRO, it will type a carriage return and a line feed. PRO is then ready for commands.

Commands in PRO are in the form of one line terminating with a carriage return and beginning with a command word. The effect of the command word is determined solely by its first letter and it may be followed by one argument (always a tape number) or two arguments (always a tape number and file name, in that order) which are separated from it and from each other by spaces.

(no commas, periods or other punctuation should appear other than as part of a file name). The part of the current command typed in at any time is always visible on the display and until a carriage return is typed a command may be cancelled by typing a RUB OUT.

The structure of PRO is sufficiently simple that the bulk of it explanation can be in the form of explanations of the individual PRO commands. One may escape from PRO by typing a letter which is not the start of any command word (such as Z) followed by a carriage return, by typing repeat RUB OUT, or because of a TECO error. PRO is re-entered by typing "MP\$\$". PRO assumes that the system tape is on microtape drive one.

Usually the first command typed is:

TEMP.

This is a command of one argument which tells PRO that the tape drive whose number is the command's argument has on it the scratch tape which PRO is to use as a temporary tape.

Commands which use the temporary tape are not safe until PRO is informed which tape is temporary unless tape two is being used as that is PRO's initial assumption. At this point, in order to examine the contents of one's tapes to find the exact names of the file to be edited and debugged with PRO, one uses the command:

This command takes a tape number as an argument and displays the names of the files on that tape until another character is typed. In order to first introduce one's program to the PRO system, one uses the command:

LISTF.

READ.

which takes two arguments. The second argument is the name of a file on the tape whose drive number is the first argument. This file is transferred to the temporary tape with the name PRO 1. To edit this file which has been introduced, one naturally enough uses the command:

EDIT.

This command exits to the top level of TECO after appropriately setting IO switches so one may proceed to edit one's current symbolic. It also modified the macro in Q register P so that when one returns to PRO by typing ["MP \$\$"] it will P through any remaining pages, rename PRO 1 as PRO 2 and file the output of the edit as PRO 1. If one wishes a listing one uses the PRO command:

which lists one's current symbolic on the line printer. One may

PRINT

then enter a machine language debugging phase with the command:
This command causes one's current symbolic to be assembled and
loaded along with DDT. Quite a bit of tape spinning may be
involved and one can tell that one is in DDT when three X's are
typed out. In case of an assembly or loading error, simply
return to MACDMP, load the dump "TECO" on the temporary tape,
then type["MP \$\$"]. If one reaches DDT, a dump of one's program
with DDT has been created on the temporary tape as a file called
"PROD". After some debugging one may return to PRO with one's

file status preserved by the ["\$\$U"] command in DDT. If one

START

wishes to return to a particularly correct symbolic, as when one's last edit did more harm than good, the command:

BACKUP which destroys the current symbolic and replaces it with the immediately previous version. This is only effective to one level. One may exit from PRO directly to MACDMP by means of the command:

MACDMP. which does not dump the current TECO status as it goes to

MACDMP. Lastly, PRO will list its commands for you when you

use the command:

APPENDICIES

- \underline{A} . The following files are oriented and maintained on one's temporary tape by PRO.
 - (1) PRO 1 current symbolic file.

(2) PRO 2 - immediately previous symbolic file.

- (3) PRO B binary file of an assembly(usually of PRO 1).
- (4) PRO D dump file of loading of PRO B and DDT.
- (5) TECO dump file of TECO with PRO macros.
- \underline{B} . The following Q registers are used by PRO:

Q8 - temporary tape number.

QA - command word first letter.

QF - file name argument.

QG - used as part of START command.

QJ - used only once when PRO is loaded.

QN - tape number argument.

QP - main PRO macro.

<u>C</u>. At the time this memo is written, an implementation problem exists which may, twice during the execution of PRO's <u>START</u> command, cause a microtape to continue spinning when a second microtape is started. The first time, the temporary tape keeps spinning as the system tape is started. The second time, it is the other way around. In both cases, the REV-AUTO-FOR switch on the drive initially spinning should be momentarily pushed to the reverse (REV) position.

CS-TR Scanning Project Document Control Form

Date: 12/14/95

Report # AIM - 108
Each of the following should be identified by a checkmark: Originating Department:
Artificial Intellegence Laboratory (AI) Laboratory for Computer Science (LCS)
Document Type:
☐ Technical Report (TR) ☐ Technical Memo (TM) ☐ Other:
Document Information Number of pages: 6 (10-1 mages) Not to include DOD forms, printer intstructions, etc original pages only.
Originals are: Intended to be printed as :
Single-sided or
☐ Double-sided ☐ Double-sided
Print type: Typewriter Offset Press Laser Print InkJet Printer Unknown Other: COPY OF TYPEWRITER Check each if included with document:
□ DOD Form □ Funding Agent Form □ Cover Page □ Spine □ Printers Notes □ Photo negatives □ Other: □ Page Data:
Blank Pages(by page number):
Photographs/Tonal Material (by page number):
Other (note description/page number): Description: Page Number: TMAGE MAP! (1-6) WN# YD TITLE PACE, 2-5, WN# YD APPENDICIES (7-10) SCANCONTROL, TRGT'S (3)
Scanning Agent Signoff: Date Received: 12/14/95 Date Scanned: 1/23/96 Date Returned: 1/25/9
Scanning Agent Signature: Michael W. Cook

Scanning Agent Identification Target

Scanning of this document was supported in part by the Corporation for National Research Initiatives, using funds from the Advanced Research Projects Agency of the United states Government under Grant: MDA972-92-J1029.

The scanning agent for this project was the **Document Services** department of the **M.I.T Libraries.** Technical support for this project was also provided by the **M.I.T. Laboratory for Computer Sciences.**

Scanned

Date: 1/23/1996

M.I.T. Libraries
Document Services