

MVME162PA4 DETAILS

Microprocessor Options

The MVME162PA4 provides scalability by allowing several types of MPU options. Features such as clock speed and floating point capability can be selected.

Memory Expansion

The MVME162PA4 is offered with a configurable SDRAM. The size of the memory is determined by switch settings and the memory devices.

VMEbus Interface

The VMEbus interface ASIC includes a local bus to/from the VMEbus DMA controller, VME board support features, as well as a global control and status register (GCSR) for microprocessor communications. The device also supports the VME D64 specification, further enhancing system performance.

Transition Module

An optional MVME712M transition module is available to support the use of standard I/O connections for the MVME162PA4. This module takes the I/O connections for the peripherals on board the MVME162PA4 from the P2 connection of the module to a transition module that has industry-standard connections.

IndustryPack Interface

A key feature of the MVME162PA4 is the IndustryPack logic interface. This interface provides a 32-bit data path from the IndustryPack modules to the local MC68040 bus. IndustryPack modules provide a wide variety of connections to "real-world" applications such as I/O, control, interface, analog and digital functions. Up to four single-wide or two double-wide IndustryPack modules can be installed on the MVME162PA4 and still occupy only one VME slot. As I/O needs change, a new IndustryPack module can be installed thus preserving the customer's overall investment.

Software Support

The MVME162PA4 is supported by a wide range of real-time kernels and embedded operating systems.

Lynx Real-Time Systems, Inc.:	LynxOS
Integrated Systems, Inc.:	pSOS+
Microware Systems Corporation:	OS-9
Microtec:	VRTX32
Wind River Systems, Inc.:	VxWorks

IndustryPack Performance

Bus Frequency		Period and Bandwidth to 32-Bit IP Space		
MC68040	IP	Back-to-Back Examine (Note 1)	Four-Cycle DMA Burst (Note 2)	Single-Cycle DMA (Note 3)
25 MHz	8 MHz	4 IP clocks 8MB/s	10 IP clocks 12.8MB/s	4 IP clocks 8MB/s
32 MHz	8 MHz	3 IP clocks 10.6MB/s	10 IP clocks 12.8MB/s	4 IP clocks 8MB/s
32 MHz	32 MHz (Note 5)	6 IP clocks 21MB/s	12 IP clocks 42MB/s (Note 4)	6 IP clocks 21MB/s
Notes: 1. Back-to-back cycles for a local bus master, which is accessing a memory or I/O space location on an IndustryPack; assumes a zero-wait-state-acknowledge reply from the IndustryPack. 2. DMA burst cycles between a local bus slave and a memory or I/O space location on an IndustryPack; assumes a zero-wait-state-acknowledge reply from the IndustryPack. 3. DMA single cycles between a local bus slave and a memory or I/O space location on an IndustryPack; assumes a zero-wait-state-acknowledge reply from the IndustryPack. 4. Burst modes DMA is not supported when both bus frequencies are 32 MHz. 5. Because the specified bandwidth assumes a zero-wait-state IndustryPack cycle, it would be difficult to achieve the stated bandwidths for an IP bus frequency of 32 MHz.				

SPECIFICATIONS

Processor

Microprocessor: MC68040
Clock Frequency: 33 MHz

Memory

Synchronous Dynamic RAM

Capacity: 16MB
Read/Write Burst Mode: 4-1-1-1/2-1-1-1
Shared: VMEbus and local bus

Static RAM

Capacity: 512KB
Read/Write Burst Mode: 5-3-3-3/5-3-3-3
Shared: VMEbus and local bus
Battery Type: Lithium
Battery Life (approximate): 406 days continuous backup at 25° C, 81 days at 70° C

Flash

Capacity: 1MB
Shared: No

EPROM (32-pin PLCC)

Capacity: One 1M x 8 in socket

VMEbus ANSI/VITA 1-1994 VME64 (IEEE STD 1014)

DTB Master: A16–A32; D08–D64, BLT, UAT + MBLT
DTB Slave: A24–A32; D08–D64, BLT, UAT + MBLT
Arbiter: RR/PRI
Interrupt Handler: IRQ 1–7
Interrupt Generator: Any 1 of 7
System Controller: Yes, jumperable
Location Monitor: Four, LMA32

SCSI Bus

Controller: NCR 53C710
Local Bus DMA: Yes, with local bus burst
Asynchronous/Synchronous: 5.0MB/s/10.0MB/s
Connector: 50-pin, available on P2

Ethernet

Controller: 82596CA
Local Bus DMA: Yes
Connector: DB-15, available on P2

IndustryPack Logic Interface

Data Width: 16/32-bit
Interrupts: Two levels
DMA: Four channels
Clock Speed: 8 or 32 MHz
Module Types: Four single-high, two double-high
Connectors: Access via four 50-pin planar connectors

Serial Ports

Controller: 85230
Console: EIA-232-D DCE
Second Port: User configurable, EIA-232 or EIA-530 DTE/DCE, or EIA-485
Baud Rate, bps max.: 38.4K sync/async
Connectors: Available on the front panel through two DB-25 female connectors and P2

Hardware Support

Multiprocessing Support: Four mailbox interrupts, RMW, shared RAM
Debug/Monitor: 162Bug, boot and diagnostics
Transition Module (optional): MVME712M

Power Requirements (no IP Modules)

	Typical	Maximum
+5V ±5%	2.0 A	2.5 A
+12V ±5%	—	100 mA (max., with off-board LAN transceiver)
–12V ±5%	100 mA	—

Board Size

Height: 233.4 mm (9.2 in.)
Depth: 160.0 mm (6.3 in.)
Front Panel Height: 261.8 mm (10.3 in.)
Width: 19.8 mm (0.8 in.)

Demonstrated MTBF

(based on a sample of eight boards in accelerated stress environment)
Mean: 190,509 hours
95% Confidence: 107,681 hours

Safety

All printed wiring boards (PWBs) are manufactured with a flammability rating of 94V-0 by UL recognized manufacturers.

Environmental

	Operating	Nonoperating
Temperature:	0° C to 55° C, forced air cooling	-40° C to +85° C
Humidity (NC):	5% to 90%	5% to 90%
Vibration:	2 Gs RMS, 20–2000 Hz random	6 Gs RMS, 20–2000 Hz random

Electromagnetic Compatibility (EMC)

Intended for use in systems meeting the following regulations:

U.S.: FCC Part 15, Subpart B, Class A (non-residential)

Canada: ICES-003, Class A (non-residential)

This product was tested in a representative system to the following standards:

CE Mark per European EMC Directive 89/336/EEC with Amendments; Emissions: EN55022 Class B; Immunity: EN55024

ORDERING INFORMATION

Part Number	Description
MVME162PA-344SE	33 MHz MC68040, SCSI, Ethernet
Related Products	
MVME712M	Four DB-25 female serial port connectors, Centronics parallel port connector, DB-15 Ethernet connector, SCSI connector, P2 adaptor
MVME712P2	P2 adaptor module from VME backplane to cabling for transition modules
SIMM05	EIA-232 DTE module (option)
SIMM06	EIA-232 DCE module (default configuration)
SIMM07	EIA-530 DTE module (option)
SIMM08	EIA-530 DCE module (option)
SIMM09	EIA-485 module (option)
Documentation	
V162P4A/IH	MVME162P4 Installation and Use manual
V1X2P4A/PG	MVME162P4/172P4 Programmer's Reference Guide
VME712MA/IH2	MVME712 Transition Module Installation and Use
V162DIAA/UM	162Bug Diagnostics User's Manual
68KBUG1/D	68K Debugging Package User's Manual Part 1
68KBUG2/D	68K Debugging Package User's Manual Part 2
Documentation is available for online viewing and ordering at http://www.motorola.com/computer/literature	

Motorola Computer Group Regional Offices

NORTH AMERICA: Tempe, AZ 1 800 759 1107 or +1 602 438 5720

EUROPE: Loughborough, UK +44 1509 634300

EAST MEDITERRANEAN: Tel Aviv, Israel +972 3 568 4388

ASIA: Shanghai, China +86 21 5292 5693

PACIFIC RIM: Tokyo, Japan +81 3 5424 3101

ASIA/PACIFIC: Hong Kong +852 2966 3210



www.motorola.com/computer

MOTOROLA and the Stylized M Logo are registered in the U.S. Patent and Trademark Office. All other product or service names are the property of their respective owners.

This datasheet identifies products, their specifications, and their characteristics, which may be suitable for certain applications. It does not constitute an offer to sell or a commitment of present or future availability, and should not be relied upon to state the terms and conditions, including warranties and disclaimers thereof, on which Motorola may sell products. A prospective buyer should exercise its own independent judgement to confirm the suitability of the products for particular applications. Motorola reserves the right to make changes, without notice, to any products or information herein which will, in its sole discretion, improve reliability, function, or design. Motorola does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent or other intellectual property rights or under others. This disclaimer extends to any prospective buyer, and it includes Motorola's licensee, licensee's transferees, and licensee's customers and users. Availability of some of the products and services described herein may be restricted in some locations.