



Customer Service

- ▶ Overview
- ▶ Ask Wyse Knowledge Base
- ▶ Downloads
- ▶ Product Service
- ▶ Product Registration
- ▶ Documentation Index

Home > Customer Service > Discontinued General Purpose Terminals (WY-60)

WY®-60



* WY-60 with adjustable arm not included

Powerful, Versatile General Purpose Terminal

The WY-60 represents most powerful, versatile, and user-friendly Wyse terminal designed to meet the needs of the ASCII/ANSI/PCTerm markets.

- Best selling general purpose terminal
- ASCII/ANSI/PCTerm terminal
- Choice of keyboards ASCII/Enhanced PC keyboard
- High-resolution character mode with 44/132 display format
- Ergonomic Design
- WyseWorks desktop accessories package

ERGONOMICS

- Colors: Paper-white (P-192), amber (P-134), or green (P-31) phosphors
- Monitor: 14-inch diagonal, flat screen, non-glare CRT
- Refresh: 60 Hz refresh
- Adjustments: Tilt -7 to +34 degrees and 360 degree swivel

ALPHANUMERIC FEATURES

- Personalities: ASCII: Wyse WY-60, WY-50, WY-50+; ADDS Viewpoint A2/60; TeleVideo TVI-910 +/920/925/950/955; Hazeltine 1500; Lear Siegler ADM 3A/5/31; IBM 3101 1X/2X, IBM 3161. ANSI: Wyse WY-57 mode; DEC VT-100, VT52; Data General D200/210; PC Terminal
- Format: 26 lines by 80/132 columns, 44 lines by 80/132 columns
- Memory: Up to seven pages of 26 lines by 80 columns (nonhidden-attributes mode); four pages of 26 lines by 132 columns (nonhidden-attributes mode); three pages of

Exceptional Design

Users will appreciate the WY-60's high-resolution character cell for exceptionally crisp characters. The WY-60 has the same superior keyboard touch and layout that users have come to expect from Wyse. Also standard is a tilt-and-swivel base for easy screen positioning. Plus, a choice of green, amber and paper-white phosphors is available.

Sets The Standard

Systems integrators and VARs will value the powerful features available for emerging markets. The WY-60's high-quality, dynamic-focus display is extremely sharp, plus it offers 44-line capability to display more of a spreadsheet or document. Users have a choice of WY-60 ASCII, and IBM Enhanced PC keyboards. Other key features include WyseWorks, a built-in clock/alarm, calender, calculator, and ASCII table combination; selectable hidden or non-hidden attributes; double-high/wide capability for maximum screen display impact; up to seven pages of screen memory for more local editing capability; soft font to create any character set; an enhanced set-up menu; and user-programmable label line, function, and edit keys. The list goes on and on.

COMMUNICATIONS

- Modes: Full/half duplex, block, and monitor (debug)
- Main: RS-232 serial, DB-25 connector; up to 38.4 Kbaud
- Printer: RS-232 serial, DB-25 connector, up to 19.2 Kbaud

PHYSICAL CHARACTERISTICS

- Terminal
- Height: 12.75 in (324 mm)
- Width: 12.5 in (318 mm)
- Depth: 13.0 in (330 mm)
- Keyboards
- WY-60 ASCII and WY-60 ANSI: 2.25 in (H) x 17.25 in (W) x 7.6 in (D) [57 mm(H) x 439 mm (W) x 193 mm (D)]
- IBM Enhanced PC-style: 2.25 in (H) x 18.7 in (W) x 6.9 in (D) [57 mm (H) x 475 mm (W) x 176 mm (D)]
- Finish: Two-tone gray
- Shipping Weight
- Terminal and Keyboard: 20 lbs (9.8 kgs)

26 lines by 80 columns (hidden-attributes mode); two pages of 26 lines by 132 columns (hidden-attributes mode); two pages of 44 lines by 80 columns (nonhidden-attributes mode); one page of 44 lines by 132 columns (hidden-attributes mode); one page of 44 lines by 80 columns (hidden-attributes mode); one page of 44 lines by 132 columns (nonhidden-attributes mode)

- Character Cell: 7 x 12 matrix 10x16 cell with 3-dot descenders: 800 dots by 416-line resolution in 80-column mode; 7 x 12 matrix in 9x16 cell with 3-dot descenders: 1188 dots by 416-line resolution in 132-column mode; four separate programmable (soft) character fonts of 128 characters each; total font display capability of 512 characters
- Character Attributes: Normal, blink, blank, reverse, dim, underscore and combinations. Hidden or nonhidden. Row attributes, double-wide and/or double-high and combinations dim, reverse
- Cursors: Block or underline, blink, steady, or off

KEYBOARD

- All keyboards: Full-travel mechanical key switches. Detachable keyboard with 4-wire coiled cable, 6-feet extended length. Two-position tilt. DIN compliant. Full-touch keys. Approximately 350 nonvolatile bytes available, 64 non-volatile bytes maximum per key.
- Layout: Choice of Enhanced PC (102 keys), International Enhanced PC (103 keys), Wyse ASCII (101 keys).
- Languages: Danish, French, German, Norwegian, Spanish, Swedish, Swiss, U.K. English, and U.S. English

[Back to Top](#) ▲

ENVIRONMENTAL

Temperature Range

- Powered on: 50° to 104°F (10° to 40°C)

- Powered off: -14° to 140°F (-10° to 60°C)

Humidity

- 20% to 80% non-condensing

Altitude Operating Range

- 0 to 10,000 feet (0 to 3,048 meters)

POWER

- 120 VAC+- 10%, 47-63 Hz

REGULATORY COMPLIANCE

Safety

- UL 478 - CSA 220 approved

Radio Frequency Interference

- FCC Class A Power Consumption

- Complies with EPA Energy Star guidelines

WARRANTY

- One year limited warranty

MODELS NUMBERS

- WY-60 120V, green: 900109-01

- WY-60 120V, white: 900109-04

- WY-60 120V, amber: 900109-07

* The Energy Star emblem does not represent EPA endorsement of any product or service

Note: The keyboard is not included with the terminal and must be ordered separately