Shugart Drive options required for Xebec 1200.

A. Pluggable options dependent on unit number selection.

Pluggable Jumper	As Shipped from Shugart		Required for Drive 0		Required for Drive 1		Required for Drive 2	
	Open	Plugged	Open	Plugged	Open	Plugged	Open	Plugged
T1,T3,T4,T5,T6		X		X	X		X	
DS1		X		X	X		X	
DS2	X		X			X	X	
DS3	X		X		X			X

B. Pluggable option, all drive regardless of unit number.

Pluggable Jumper	As shipped from Shugart		Required for all Drives		
	Open	Plugged	Open	Plugged	
T2,DS,C,Y	X			X	Change required
HL,X,Z		X	X		Change required
DS4,D,DC	X		X		No change
A,B		X		X	No change

C. Cut and jumper options. no change

Cut & Jump Options	As shipped from Shugart	
	Open	Short
NP,8,16,D1,D2,D4,DDS	X	
RR,RI,R,I,S,WP,32,I/O Pins 2,4,6,8,10,12,14,16,18		X

For use in the Xebec 1200, the following Shugart drive part number is required. For other configurations, consult Xebec.

85 - X - X - O - X

Model 800-2
with 5V Opt.

X = 0 = 115V 60 Hz
X = 1 = 230V 60 Hz*
X = 2 = 115V 50 Hz
X = 3 = 230V 50 Hz*

*Requires Xebec
 1200 Power supply
 modification

Normal mounting with:
X = 0 = activity led
X = 2 = no led

Standard face plate

X = 0 = write protect & no dust cover
X = 1 = write protect and dust cover
X = 2 = no write protect and no dust cover
X = 3 = no write protect and dust cover