



COMPUTER  
CENTRE  
**BULLETIN**

Vol 5 No 7  
3 July 1972

Editor:  
Mrs Sarah Barry



WARNING ON BASIC

[WN-89]

In some cases the diagnostic message  
'INPUT DATA NOT IN CORRECT FORM - - RETYPE LINE'  
is incorrectly given when only the last portion on the input line  
is incorrect and only that portion of the line need be retyped.

For example, if the input statement

```
20 INPUT A$,B
```

is used and no numeric data is given, by a typein of the form  
TEST?

the above warning message will be given. The input to A\$ of the  
character string 'TEST' has been satisfied. The message implies  
that the whole line should be retyped. In fact only the numeric  
data for variable B is required and that element only should be  
retyped.

EQUIPMENT INSTALLATION - DATA CHANNEL

[WN-93]

On Monday 5 June a second data channel was installed on the  
University's computer system.

Prior to this, a single data channel was utilized to connect the  
RD10 fixed head swapping disks, and the RP02 removable disk pack  
drives through a single channel to the core memory system.  
Considerable data traffic interference occurred between the two  
disk systems resulting in a large proportion of lost time, which  
is time lost while the processor is waiting for disk input/output  
to be completed. The most noticeable effect was poor response  
time on terminals and poor batch throughput.

With the installation of the second data channel, the RD10 fixed  
head disk system was connected to the second channel. This will  
result in a reduction of the data traffic interference between  
the two disk systems, and result in better performance. Initial  
observations of the system's performance have shown that this is  
the case.



batch)  
READ(25,10) N,(A(I)=1,N) searches as many records as need to find all the required fields.

(ii) CALL ENFRED(35,10)  
CALL IFILE(10,'FNAME')  
READ(35,10) N,(A(I),I=1,N)

Since numeric (decimal and octal), logical, and alphanumeric (ASCII) fields may be read, certain assumptions as to the type of field are made from the first character of that field. Fields are separated by spaces or commas.

Briefly, fields starting with a numeric character (digit 0-9 '.' '+' or '-') are considered numeric (see later for logical or octal fields). Other fields (even if they contain numeric characters) are considered alphanumeric fields.

Numeric fields may be in any of the standard formats acceptable to FORTRAN.

#### DETAILS OF FIELD TYPES

##### NUMERIC FIELDS

###### Decimal (Integer or Real)

A signed or unsigned number in standard E format.

examples:

25  
-17  
+25E1  
1E1  
-5.932E-07 etc.

The result is returned in integer or real format depending on the type of variable in the READ statement.

###### Octal

A signed or unsigned number preceded by a " symbol is decoded as an octal number. The number may contain up to 12 digits.

examples:

"52715  
"-593  
"-1

B5-7  
5Jul72

The number may contain a 'decimal' point or an E, in which case it is converted to real format IF the variable TYPE is REAL.

example:

"1E2 is read as 100, and if the variable is REAL is converted to real format.

Numeric fields are ended by any illegal character (including excess signs and E's, and blank or comma).

### LOGICAL FIELDS

A field starting with a decimal point and followed by a non numeric character (i.e. not digits 0-9 or . + or -) is assumed a logical variable. If the second character is a 'T', the variable is set to TRUE, otherwise it is set to FALSE.

examples:

- (i) .T .TRUE. .TOM are read as TRUE
- (ii) .F .FALSE. .XXX are read as FALSE

A logical field is ended by a space or a comma.

### ALPHANUMERIC FIELDS

A string of characters, starting with a non numeric character (except " or ') and containing no spaces or commas is regarded as an ASCII field. This string is read into the variables of the READ statement in sequence (5 characters per variable for integer, real, or complex variables, and 10 characters per variable for double precision variables).

Where there are insufficient characters to fill a variable, blanks are added. Strings containing blanks or commas or starting with a numeric character can be input as ASCII by delimiting the field with apostrophes ('). Two adjacent apostrophes, insert an apostrophe (') into the text.

The following fields are read as:

ABCDEFGH as ABCDE FGHbb  
'52179362' 52179 362bb  
ABC'EFG' ABC'E FG'bb  
(where b represents a space).

Complex Variables

These are handled as two separate variables for numeric or for ASCII type fields (two 5 character fields for ASCII).

Double Precision Variables

These are always handled as one field (the low part is zeroed on numeric fields). Up to 10 ASCII characters can be read into a single variable (blank filled if fewer than 10 characters)

OTHER FACILITIES IN FRED

Repeated fields

An integer field followed by an asterisk (\*) indicates that the following field is to be repeated.

examples:

(i) 5\*21E7

(ii) 5\*ABCDEF repeats ABCDEFbbbb 5 times

(iii) 5\*'THIS WHOLE FIELD IS REPEATED 5 TIMES'

Skipped Variables

Adjacent commas cause variables to be skipped over without change.

example:

READ(25,10) A,B,C,D,E

when reading

7.1,5.9,,,3.1

leaves C and D unchanged (i.e. they retain the values they had before the READ).

when reading

5\*

leaves all variables unchanged.

Continued Records

In the ONE RECORD mode, more than one record can be read by terminating the record with a '-', provided that character is not part of an ASCII field.

B5-7  
5Jul72

examples:

- (i) 5, 7, 21, 15 - causes two records to be input
- (ii) 71, 562.5
- (iii) 5, 7, 21, ABC- the - sign is part of the field ABC-

#### Termination of Reading

In any mode an <altmode> character will cause the unsatisfied input variables to be null (or blank) filled, thus terminating the READ statement.

#### Use with Decode

If a call is made to the subroutine ENFDEC the NEXT DECODE statement is handled by the free field routine. The number of characters to be scanned should not exceed 140 (only 140 will be scanned if this is exceeded).

example:

```
CALL ENFDEC      enables ONE free read DECODE  
DECODE (80,10,A) X,Y,Z
```

#### Limitations

1. Records must not exceed 140 characters in length.
2. Double precision numeric fields are handle in single precision only.

#### Use of FRED

FRED can be loaded from file 525.FRED as:  
.RUN MAIN, SUB1, 525.FRED