

Compaq StorageWorks

64-bit PCI to Fibre Channel Host Bus Adapter Windows 2000 and NT 4.0 Release Notes

These release notes contain the most recent supplemental information for the Compaq StorageWorks 64-Bit PCI to Fibre Channel Host Bus Adapter (HBA).

Be sure to read these notes before installing the HBA module into your server. This information is periodically updated and available on the World Wide Web at www.compaq.com/products/storageworks/adapters.html.

Introduction

The 64-Bit PCI to Fibre Channel Host Bus Adapter is a high-performance PCI option module that connects to devices attached through either a hub-based optical Fibre Channel arbitrated loop or a switch based optical Fibre Channel fabric. The HBA supports only short wave multi-mode connections. These release notes include all known issues or restrictions for using the HBA within a system configuration. This document is organized into sections as follows:

- Parts List for the adapter (Table 1)
- Supported systems
- Supported Storage and Interconnect Devices
- Configuration Information
- Restrictions
- Registry Settings

Table 1
Parts List

Part Number	Revision	Description
Digital Classic		
DS-KGPSA-CB	A	64-Bit PCI to Fibre Channel Host Bus Adapter
AA-RKPEC-TE (173940-003)	C	Release notes for the KGPSA-CB (this document)
AA-RKPDB-TE (173941-002)	B	<i>Compaq StorageWorks 64-Bit PCI to Fibre Channel Adapter User Guide</i>
AK-RKPHB-CA	B	Windows NT 4.0. mini-port driver kit and readme files
AA-RNXMA-CA	A	Windows 2000. mini-port driver kit and readme files
AA-RNXLA-CA	A	64-Bit PCI to Fibre Channel Host Bus Adapter BIOS Enable Utility and readme files for NT4 and Windows 2000.
AK-RNXKA-CA (Disk 1 of 2)	A	Driver upgrade utility for Windows 2000 and NT 4.0
AK-RNXNA-CA (Disk 2 of 2)		
3R-Q411A-AA	B01	Compaq Directory
AV-RKU9B-TE		Software License
3R-Q409A-AA	C01	Warranty Terms and Conditions

Supported Systems

The Compaq StorageWorks 64-Bit PCI to Fibre Channel Host Bus Adapter (HBA) is supported on the Proliant family of servers, a maximum of 4 adapters per server.

The HBA is also supported in other x86 platforms. See the Restrictions section in these release notes for known device restrictions. Refer to the Compaq Computer Storage Works web site <http://www.compaq.com/products> for other supported servers.

Supported Storage and Interconnecting Devices

Table 2 describes the associated components and their revisions that are qualified with the HBA.

Table 2
Supported Storage and Interconnect Devices

COMPONENT	FW/Driver	P/N and Comments
	Version	
DS-KGPSA-CY	Firmware ddb381a1.awc	Resides on the HBA
Windows NT 4.0 mini-port driver	4-4.52a8	
Windows 2000 mini-port driver for Advanced Server	5-4.52a8	For Data Center installations the mini-port driver is on the Data Center Platform Kit.

continued

Table 2
Supported Storage and Interconnect Devices *continued*

COMPONENT	FW/Driver Version	P/N and Comments
8-Port Switch	1.6D	DS-DSGGA-AA 380591-B21
16-Port Switch		DS-DSGGA-AB 380578-B21
SAN Switch 8	2.1.9a1	DS-DSGGB-AA 158222-B21
SAN Switch 16		DS-DSGGB-AB 158223-B21
SAN Switch 8-EL	2.1.9a1	DS-DSGGC-AA 176219-B21
SAN Switch 16-EL		DS-DSGGC-AB 212776-B21
RA8000/ESA12000	ACS 8.5	Windows NT 4.0 and Advanced Server Platform Kit, 380551-001
MA8000/EMA12000	ACS 8.5	Windows NT 4.0 and Advanced Server Platform Kit, 380551-001
MA6000	ACS 8.5	Windows NT 4.0 and Advanced Server Platform Kit ,192214-B21
FW Upgrade Util I386DNLD.exe	8.5a6	This utility is also used to enable the HBA BIOS.

continued

Table 2
Supported Storage and Interconnect Devices *continued*

COMPONENT	FW/Driver Version	P/N and Comments
12-Port Hub	N/A	DS-HDGGB-AA 295573-B22
7-Port Hub	N/A	DS-SWXHB-X7 234453-xxx
SWL GBIC	N/A	30-56040-01
Optical Cables (connection from HBA to Hub or Switch)	N/A	BNGBX-xx (02,05,15,30,50) 234457-B2x (xx = length in meters)

Configuration Information

- Supports mixed HBAs (380574-001 and 176479-B21) in the same host,
- Maximum number of cascaded (serial) switches is 8,
- Maximum number of hops is 7,
- Maximum cable length between switches is 500m for SWL, 10K LWL, 100K VLD,
- Supports a mix of SAN switches in the same configuration.

Restrictions

64-Bit PCI to Fibre Channel Host Bus Adapter Restrictions

Adapter restrictions include:

- The minimum Revision of NT 4.0 mini-port driver code is 4-4.52a8.
- The minimum Revision of Windows 2000 mini-port driver code is 5-4.52a8.
- The minimum Revision of HBA firmware for is ddb381a1.awc.
- The minimum Revision of the HBA hardware is FC1020016-02 Rev B.
- Maximum length of the OPTICAL cable from the HBA to a hub or switch is 500 meters short wave multi mode 50/125 micron Fibre Channel Cable.

Windows NT Restrictions

Windows NT restrictions include:

- The HBA is not supported on Alpha Windows NT 4.0 platforms.
- The minimum Windows NT 4.0 revision that supports the HBA adapter is Revision 4.0 with Service Pack 6.0 installed.
- The minimum Windows 2000 Advanced Server revision that supports the HBA is Build 2195 with Service Pack 1 installed.
- The HBA supports boot functionality for both Hub and Switch Topologies. Refer to your platform kit for configuration information and application notes specific to your configuration. Also consult <http://www.compaq.com> for information.
- HBAs 380574-001 and 176479-B21 are not supported in the same Secure Path pair of HBAs. A Secure Path pair of HBAs is defined as two HBAs that have access to the same storage devices through completely independent paths.
- Hot plug functionality is supported on this HBA. Please consult the application notes at <http://www.compaq.com> for updates.

Registry Settings

Table 3 contains the Windows NT 4.0 and Windows 2000 registry settings, from the OEMSetup.ini file that is shipped with the HBA kit. Additional

registry settings are required as a function of the configuration the HBA is installed into. The additional registry parameter settings are automatically added, when the Fibre Channel Setup Kit is installed and also when your specific application (Secure Path, DRM, EVM; etc) is installed. Consult your Fibre Channel Setup Kit for this information.

Table 3
Registry Parameters

Parameter	Setting	Comment
Number of Requests	Dec. Value = 50	
Maximum SG List	Dec. Value = 33	
RetryIOtimeOut	1	
RetryInterval	52	
EnableDPC	1	
QueueTarget	1	
ElsRetryCount	6	
NodeTimeout	60	Standard for transparent failover mode
Topology	0	Default value for Arbitrated Loop Configurations
ScanDown	1	Valid for Arbitrated Loop Configurations

NOTICE

© 2001 Compaq Computer Corporation.

Compaq, the Compaq logo, and StorageWorks Registered in U. S. Patent and Trademark Office.

Motif, OSF/1, Tru64 UNIX, and OpenVMS are trademarks of Compaq Information Technologies Group, L.P. in the United States and other countries.

Microsoft, MS-DOS, Windows, Windows NT are trademarks of Microsoft Corporation in the United States and other countries.

Intel, Pentium, Intel Inside, and Celeron are trademarks of Intel Corporation in the United States and other countries.

All other product names mentioned herein may be trademarks of their respective companies.

Confidential computer software. Valid license from Compaq required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

Compaq shall not be liable for technical or editorial errors or omissions contained herein. The information in this document is provided "as is" without warranty of any kind and is subject to change without notice. The warranties for Compaq products are set forth in the express limited warranty statements accompanying such products. Nothing herein should be construed as constituting an additional warranty.

Compaq service tool software, including associated documentation, is the property of and contains confidential technology of Compaq Computer Corporation. Service customer is hereby licensed to use the software only for activities directly relating to the delivery of, and only during the term of, the applicable services delivered by Compaq or its authorized service provider. Customer may not modify or reverse engineer, remove, or transfer the software or make the software or any resultant diagnosis or system management data available to other parties without Compaq's or its authorized service provider's consent. Upon termination of the services, customer will, at Compaq's or its service provider's option, destroy or return the software and associated documentation in its possession.