



White Paper  
Intel® Xeon® Processor  
7400-based Server

# Consolidation of a Performance-Sensitive Application: Virtualizing Electronic Sports League's Gaming Infrastructure



## Abstract

An end-user case study with Electronic Sports League (ESL) using VMware ESX 3.5U1\* with NetQueue feature running on Intel® Xeon® processor 7400 series-based servers with Intel® NICs supporting VMDq feature. Game servers are mission-critical, single-threaded, processor-intensive, and network-latency sensitive. They were previously believed to be “non-virtualizeable” due to the overhead of virtualization. In this case, we will show that game QoS can be preserved on virtualized game servers when using the latest technologies noted above. We'll also show that large server consolidation ratios and cost savings can be achieved at the same time.

**Authors:** Bob Albers, I/O Usage Architect, and Sreeram Sammeta,  
Sr. Systems Engineer, Intel Digital Enterprise Group



# Table of Contents

- Introduction - Can We Virtualize Everything? ..... 3**
  - “Non-virtualizable” applications.....3
  - Sidebar: ESL* .....3
  - Problem statement .....4
- New Technologies Allow Us to Virtualize More. .... 4**
  - ESL Proof of Concept (PoC) overview .....4
  - Server hardware.....5
  - Network I/O .....5
  - Software stack .....7
- Question the Assumptions. .... 7**
  - Key performance metrics .....7
  - Gaming protocol .....8
  - Round-trip network latency tests.....8
  - ESL game testing ..... 10
- ROI Delivered ..... 11**
  - Server consolidation ..... 11
  - Power savings ..... 12
  - Other savings..... 12
- Conclusions ..... 13**
- Resources ..... 14**

## Introduction — Can We Virtualize Everything?

Virtualization of enterprise data center applications using hypervisors or VMMs is taking a predictable path. It started with the consolidation of the simplest, least performance-sensitive, and least mission-critical applications, many of which had hardware utilization figures in the 10 percent or less range. These applications were the “low-hanging fruit” of the first wave of application virtualization, and consolidation ratios were quite high while still delivering adequate performance. This consolidation wave delivered a significantly positive ROI to the organizations. IT organizations would like to have the benefits of virtualization across the entire spectrum of applications, but there are challenges to delivering on this potential.

### “Non-virtualizable” applications

Not all enterprise applications fit the description above, of course. There are more complex, high-performance, and mission-critical applications, too. Many of these applications are very demanding of the hardware resources in state-of-the-art servers; therefore we expect that it would be more difficult to virtualize them while retaining adequate performance. Examples of some of the generic types of applications that don’t fit the “low-hanging fruit” description are those characterized by the following characteristics:


- Mission critical
- Transaction latency sensitive
- CPU intensive: single thread vs. multi-thread
- Memory intensive: size/throughput/latency
- I/O intensive: disk/network; throughput/latency

From our experiences with virtualization we know there are certain overheads involved with delivering the value that a VMM/hypervisor provides. These overheads can impact all the characteristics noted above. This leads to the perception that these types of applications “can’t be virtualized” because the tradeoffs would be too severe. Is this a perception or reality?

### ESL

Electronic Sports League (ESL) is the largest online gaming community in Europe, with more than 844,000 active users as of August 12, 2008.

ESL has deployed thousands of game servers to provide services to its members. Obviously, for a game services company, the game servers are mission critical. The key performance criterion measured by gamers is the in-game transaction latency, which determines the responsiveness of the game and is a key component in the competitive edge for the players, many of whom are actually professionals and quite demanding of the performance of this key criterion. In addition, most game server code is single-threaded and very CPU intensive, with CPU utilization typically in the 60-80 percent range.



**Figure 1.** ESL game server high-level architecture.

## Problem statement

ESL's perception, along with that of many of its peers in the gaming industry, was that gaming servers "can't be virtualized" due to their mission-critical nature, high CPU utilization, and the critical focus of their user base on the in-game transaction latency. However, ESL was very motivated to try to break through this "perception barrier" because it has been experiencing exponential growth for the past eight years, which caused substantial problems for its IT team in managing game server sprawl, costs, power, and operational expenses. The fundamental question was: could we deliver the benefits of virtualization for the gaming server infrastructure while maintaining high quality of service (QoS) levels as perceived by the ESL members? The virtualized game servers must deliver smooth game play and measurably competitive in-game transaction latencies to be acceptable to ESL's customers.

## New Technologies Allow Us to Virtualize More

Our perceptions are shaped by our experiences and our knowledge of the experiences of others. These perceptions often become embedded in our thinking and need to be periodically challenged to be sure that they still represent reality. As technology marches on, we have seen many IT perceptions change. With this in mind, and with consideration of the latest technology innovations that may be relevant to the problem at hand, ESL and Intel proceeded to examine our perceptions about the virtualization of gaming servers.

### ESL Proof of Concept (PoC) overview

We know that servers grow more powerful with each new generation, which improves the performance of any application running on them, including virtualized ones. However, we also know that virtualization overheads are especially severe for I/O performance-sensitive applications such as this one, where in-game transaction latency (which includes the round-trip network latency) is so critical.





Figure 2. Intel® Xeon® processor 7300 platform high-level architecture.

Our hypothesis was that virtualization of gaming servers may be possible if we use the latest technologies:

- Intel Xeon processor 7400-based servers with 24 processing cores to address the need for higher performance overall. This should allow us to deliver QoS headroom to counteract the overheads of virtualization. This platform was also chosen due to the desire for high consolidation ratios to address ESL challenges with server sprawl, cost, power, and operational expenses.
- Intel NICs with the VMDq feature, which allow the virtualized network overheads to be minimized and the network load to be spread across multiple platform cores for higher performance and more headroom to maintain QoS.
- VMware ESX 3.5\* to support the platform chosen. ESX 3.5 also delivers substantial networking performance improvements compared to earlier versions.
- VMware NetQueue feature, which provides the software environment to take advantage of the VMDq feature in the latest NICs.

We could not find any industry data on the latency impact of virtualization that was relevant to typical gaming server protocols, so we decided to first test the network-latency impact




**Figure 3.** Network data flow for virtualization without the use of VMDq and NetQueue technologies.

of virtualization in the Intel lab using common network micro-benchmarks before attempting the virtualization of the gaming server environment. This would allow us to quantify the latency added by virtualization to see if it would be significant. When we were sure that the latency added should not be a concern, we proceeded to test the gaming server virtualization with private testing in the ESL lab and ultimately onto public testing on the Internet with real ESL members.

### Server hardware

The PoC targeted the Intel Xeon processor 7300 platform with four processor sockets with the six-core Intel Xeon processor 7400 series (Dunnington). These new processors became available in September 2008 and are hardware and software compatible with Intel Xeon processor 7300-based platforms that have been in production for more than a year. The Intel Xeon processor 7400 series delivers a performance boost from using six rather than four cores per socket and by the addition of a new 16 MB L3 cache. It also delivers an energy-efficiency boost derived from our 45nm high-k process technology. In addition, the Intel Xeon processor 7400 series has added some



**Figure 4.** Impact of virtualization on a 10 GB Ethernet NIC without the use of VMDq and NetQueue.


enhanced hardware-assist features for virtualization. The platform supports 32 memory slots for up to 256 GB capacity. In this PoC we used 32 GB.

### Network I/O

But virtualization is not just about CPU and memory resources. It's important to have I/O tuned for virtualization, too.

In a typical virtualization scenario (Figure 3), the network I/O for all the VMs is delivered to the hypervisor. The hypervisor then performs the necessary Ethernet switching functions in software to forward each network flow to the destination VM. This software function, called a virtual switch, is much slower than a typical hardware-based Ethernet switch and causes CPU loading that detracts from application VM performance. Also, the hypervisor virtual switch has to process all the interrupts sent by the network I/O device on a single CPU core. This can be a bottleneck too, especially for faster networks like 10 GbE.

As shown in Figure 4, the Intel® 10 GbE NIC runs into this single-core interrupt processing load bottleneck. In this case, the 10 GbE NIC can only receive 4 GB of traffic due to the saturation of the single CPU core processing all the receive interrupts at 10 GB line rate.




**Figure 5.** Network data flow for virtualization with VMDq and NetQueue.

**VMM overhead**

- Switching load
- Interrupt bottleneck

We can optimize the network I/O solution to solve both of the issues above.

In Figure 5, we show the effect of using the new Intel® VMDq hardware in our latest NICs along with the new VMware NetQueue software in ESX 3.5. In this case, the network flows destined for each of the VMs are switched in hardware on the NIC itself and put into separate hardware queues. This greatly simplifies the work that the virtualization software layer has to do to forward packets to the destination VMs and delivers improved CPU headroom for application VMs. Each of the queues noted above is equipped with a dedicated interrupt signal that



**Figure 6.** Tests measure wire speed Receive (Rx) side performance with VMDq on Intel® 82598 10 Gigabit Ethernet Controllers.

can be directly routed to the destination VM for handling. This allows us to spread the load of a 10 G pipe across the processor cores running those VMs. In this way we can break through the single-core interrupt processing bottleneck to deliver near line-rate performance even at 10 GbE speeds.

In Figure 6, we can see that the receive performance with VMDq + NetQueue is 9.2 Gbps with standard 1518-byte packet size and 9.5 Gbps with jumbo frames. This is more than double the throughput without these new technologies enabled and very close to maximum theoretical line rate.

**VMDq and NetQueue**

- Optimize switching
- Load-balance interrupts




Figure 7. Software stack.

### Software stack

Figure 7 shows the software stack used in the PoC. We started with VMware ESX 3.5U1, which was the latest production version at the time the PoC began. We also used Virtual Center 2.5.\* The VMs were configured with 1 vCPU and 2 GB of memory each, which emulates the physical server infrastructure used by ESL. In each VM we loaded Windows Server 2003\* 32-bit and the Counter-Strike 1.6\* game server. Counter-Strike is a very popular game and a good example of the types of games hosted by ESL. Each VM hosts three game server processes, and each game server process can host up to 12 game users. Again, this corresponds with the typical deployment processes used by ESL for its physical game servers.

Now that we’ve described the technologies used in the PoC, we’ll move on to detailing the engineering and testing phase.




Figure 8. In-game latency.

## Question the Assumptions

### Key performance metrics

The key performance metric for ESL—or for any online gaming application—is the “in-game transaction latency.” This can be defined as the sum of round-trip network latency and game server processing time.

Figure 8 represents the typical in-game transaction latency numbers that ESL observed in its current native environment.

When players are connected to the game servers through a local area network, the best case in-game latency is ~5 ms. For players connected to game servers via the Internet, the in-game latency is greater or equal to 20 ms; and for the players having high-speed Internet connections, it’s about ~10ms, which is the Internet best-case scenario.




Figure 9. Game network protocol overview.

### Gaming protocol

How does this gaming protocol work? A player sends a UDP packet of 40–200 bytes in size to the game server. The game server receives the packets, does its own processing, and then updates all the players by sending a 2,000-byte UDP packet (as represented in Figure 9).

We know that the virtualization will increase the round-trip network latency, but we are not sure by how much. In theory we also know that enabling VMDq and NetQueue will improve the network latency. We searched both internally and externally for data related to the impact of virtualization on latency sensitive applications, but we were not successful. Therefore, we decided to do our own tests in Intel labs.



Figure 10. Native lab test setup.

### Round-trip network latency tests

In order to run the round-trip network latency test, we used the micro-benchmark Netperf 2.4.4, the UDP latency test and the ESL workload, which consists of UDP packets. The following three scenarios are being compared here:

1. Native
2. Virtualized with VMDq/NetQueue
3. Virtualized with no VMDq/NetQueue

#### Scenario 1: Native

The setup and configuration, as shown in Figure 10, includes eight clients connected to eight 1-GbE ports of a 1G/10G link aggregation switch (Force 10 S50\*) and the Intel Xeon processor 7300 server connected to 10G port of the switch via Intel® 82598 10GbE CX4 NIC. SLES10 SP1 is the operating system installed on all the clients and servers, and there are eight parallel streams of UDP latency tests being run from the clients to the server.



Figure 11. Virtualized lab test setup.

**Scenarios 2 and 3: Virtualized with and without VMDq/NetQueue**

In these scenarios, the setup shown in Figure 11, consists of eight clients connected to eight 1-GbE ports of a 1G/10G link aggregation switch (Force 10 S50) and the Intel Xeon processor 7300 server connected to 10G port of the switch via Intel 82598 10GbE CX4 NIC. On the server, ESX 3.5 is installed and there are eight virtual machines created. The virtual machines are configured with 1vCPU; 1 GB RAM and SLES 10 SP1 is the guest operating system. VMDq with 16 queues along with NetQueue is enabled on the ESX server, and we are letting the VMM handle the VMDq assignments, core assignments, and interrupt affinity. On the clients, SLES 10 SP1 is the operating system. There are eight parallel streams of UDP latency tests being run from eight clients to eight virtual machines.

As mentioned earlier, in all the scenarios we used Netperf 2.4.4 UDP latency test and we ran the tests for UDP packet sizes of 64 bytes, 256 bytes, and 1024 bytes. The ESL workload used UDP packets of sizes varying from 40 to 200 bytes.




Figure 12. Netperf 2.4.4 UDP latency test with eight parallel streams.

The results from these tests are summarized in Figure 12. In the graph, we are comparing native, virtualized with VMDq, and virtualized with no VMDq (represented by the blue, light blue, and gray bars, respectively). The horizontal axis represents various UDP packet sizes in bytes, and the vertical axis represents the average latency in milliseconds.

From Figure 12 it can be concluded that virtualization increases the latency. In fact, the latency is doubled (for 64-byte packets, the latency in the native scenario is 0.12 ms, whereas in the virtualized scenario with no VMDq it is 0.24 ms). By enabling VMDq and NetQueue, the latency in the virtualized case is near native (~0.13 ms). The increase in latency by virtualizing has a negligible impact when compared to in-game latency of 5 ms best case.




Figure 13. Live Internet test setup.




Figure 14. Test software stack.


## ESL game testing

At ESL labs, we ran a series of tests cases that included private and public Internet testing. All these tests revealed that there is no impact on in-game latency, and as a result there is no impact on the gaming experience.

As part of this testing, we used an Intel Xeon processor 7400 server code-named "Dunnington." This is an MP server with four sockets and six cores per socket, with a total of 24 cores. This server is connected to a 10 GbE port of a 1G/10G aggregation switch by using a 10 GbE CX4 NIC. ESX 3.5 U1 was installed on the server, and each virtual machine is configured with 1vCPU,

2 GB memory, Windows 2003 server (32 bit) and Counter-Strike 1.6 (three game servers running per VM). We are not using any kind of CPU affinity or memory reservations. Also, on the ESX server we enabled the "NetQueue" feature and by default a maximum of 16 queues per 10 GbE port are created.

As a part of load generation we used real players who connected to the game servers on the local LAN and through the Internet, and "bots," which are an emulation of a player playing a game. These bots run on the game server as a plug-in and generate CPU load. The setup and configuration are shown in Figures 13 and 14.



**Figure 15.** ESL virtual game servers on Intel® Xeon® processor 7400 Series-based platforms.

## ROI Delivered

### Server consolidation

Figure 15 represents the CPU utilization and power utilized by the server at various numbers of virtual machines under a full load. The bar graph represents CPU utilization, and the line graph represents power utilized by the server. The horizontal axis represents the number of virtual machines, and the left vertical axis and right vertical axis represent the scale for CPU utilization and power utilization, respectively.

Since the server has 24 cores, we started with 24 virtual machines, all of them configured identically as mentioned earlier. As we can see from the graph, for identical 24 virtual machines the total average CPU utilization was a little more than 40 percent, and power utilized was about 665 watts. As the server is not fully utilized, the number of virtual machines was scaled up to 40. At 40 virtual machines the CPU utilization was about 90 percent, and power utilized was about 725 watts. Even at 90 percent utilization there was no impact on the in-game

latency or gaming experience. But in ESL’s current native environment, ESL tries to limit the CPU utilization per server around 60–80 percent. ESL needs this head room as there can be situations where some game servers need more resources. Therefore, it was decided that 36 virtual machines is the optimal number as the CPU utilization and power utilization are 75 percent and 710 watts, respectively.

Below is the quote from “Kapio,” a professional gamer who actually played Counter-Strike on the virtual machines. He did not see any difference as compared to native.

**“Playing on virtualized game servers running on Intel and VMware technologies gives professional gamers no disadvantages compared with playing on a non-virtualized server. Everything ran smoothly, and I did not notice anything unusual. A perfect setup for professional gaming.”**

– Navid Javadi, aka mousesports|Kapio

**Table 1.** ESL standard native hardware deployment metrics (“Before”) vs. virtualized deployment Proof-of-Concept metrics as described in this paper (“After”).

	Before	After
Server	1P Intel® Core™2 Duo processor	4P Intel® Xeon® processor 7400
Cores	2	24
Game server processes	3 per CPU core	3 per VM; 4.5 per CPU core
VMs per box	N/A	36
Game server per box	6	108
Total users per box	72	1,296
CPU utilization	60-80%	75%
Power utilized per server	350 W	710 W
Consolidation ratio	18	1
Annual direct power cost	\$731,000 per 1,000 servers	\$83,000 per 56 servers

### Power savings

Using the optimal number of virtual machines, which is 36, a simple calculation of direct power costs was done comparing the before (native) and after (virtualized).

Table 1 shows that with 36 virtual machines, with each virtual machine having three game servers and each game server supporting 12 players, we can see a consolidation ration of 18:1. This means we can consolidate 18 of ESL’s existing Intel® Core™2 Duo processor-based native servers onto one Intel Xeon processor 7400 server by using virtualization in combination with VMDq and NetQueue technologies without impacting the gaming

latency and gaming experience. This translates to direct power-cost savings of \$648,000 annually for every 1,000 Intel Core 2 Duo processor-based servers that will be converted. In these calculations we are taking into consideration that these game servers are running 24x7, 365 days per year, and we used the actual power rate ESL is paying (0.16 euros/kWh).

### Other savings

The above savings are only direct power savings. We did not take into account other savings like cooling, datacenter space, network hardware, and manageability.

## Conclusions

We have shown that ESL's mission-critical, processor-intensive, network latency-sensitive game servers can be very effectively virtualized using the latest technologies. We achieved 18:1 consolidation ratios and saved almost 90 percent on power consumption compared to the ESL physical servers, while preserving game QoS and customer satisfaction.

This one data point does not prove that we can virtualize every server application. Some demanding applications are still beyond the reach of current technology. However, we do show that the latest technologies can allow us to virtualize more workloads, even those once thought "non-virtualizable" like the ESL game servers.

To gain the benefits that virtualization brings, we will have to question our assumptions and evaluate the latest technologies to see if we can virtualize these demanding applications. This is the only way to deliver the ROI to our organizations.

At some point in the relatively near future, with the ongoing march of hardware and software technologies, we do expect that practically all server applications will be virtualizable. So when you take a look at your server application inventory, you may have applications that seem to be "non-virtualizable." Perhaps there are some new technologies you could evaluate to prove or disprove this perception. It may be time to capture the ROI of virtualizing these demanding applications for your corporation, too.

**"The new Six-Core Intel Xeon 7400 processor series ("Dunnington") was completely overwhelming in all terms. The Intel Xeon MP servers with Intel VMDq technology enable us to efficiently run our servers with reduced costs and without any negative impacts."**

*– Bjoern Metzdorf, Director of Information Technology,  
Electronic Sports League*

## Resources

### Additional sources of information on this topic

Intel Virtualization Developer Community:

[www.microsoft.com/windowsserver/compare/compare-windows-to-unix.msp](http://www.microsoft.com/windowsserver/compare/compare-windows-to-unix.msp)

Intel Virtualization Developer Community:

[softwarecommunity.intel.com/articles/eng/1424.htm](http://softwarecommunity.intel.com/articles/eng/1424.htm)

Intel Virtualization Technology:

[www.intel.com/technology/virtualization/index.htm](http://www.intel.com/technology/virtualization/index.htm)

Intel Xeon processor 7400 series:

[www.intel.com/performance/server/xeon\\_mp/virtualization.htm?iid=SEARCH](http://www.intel.com/performance/server/xeon_mp/virtualization.htm?iid=SEARCH)

More information on Intel® Virtualization Technology for Connectivity:

[www.intel.com/go/vtc](http://www.intel.com/go/vtc)

More information on Intel Networking Solutions:

[www.intel.com/network](http://www.intel.com/network)

Intel Virtualization Technology for Connectivity Tech Brief:

[softwarecommunity.intel.com/isn/downloads/virtualization/pdfs/20137\\_LAD\\_VTc\\_Tech\\_Brief\\_r04.pdf](http://softwarecommunity.intel.com/isn/downloads/virtualization/pdfs/20137_LAD_VTc_Tech_Brief_r04.pdf)

Virtual Machine Device Queues White Paper:

[www.intel.com/technology/platform-technology/virtualization/VMDq\\_whitepaper.pdf](http://www.intel.com/technology/platform-technology/virtualization/VMDq_whitepaper.pdf)

VMware ESX Server 3 Configuration Guide – Update 2 for ESX 3.5:

[www.vmware.com/pdf/vi3\\_35/esx\\_3r35u2/vi3\\_35\\_25\\_u2\\_3\\_server\\_config.pdf](http://www.vmware.com/pdf/vi3_35/esx_3r35u2/vi3_35_25_u2_3_server_config.pdf)

*(Search for NetQueue/VMDq configuration info)*

Intelligent Queueing Technologies for Virtualization: Intel-VMware white paper:

[http://download.intel.com/network/connectivity/products/s10727\\_Intel\\_LAD\\_VMDq\\_WP\\_103008.pdf](http://download.intel.com/network/connectivity/products/s10727_Intel_LAD_VMDq_WP_103008.pdf)

Intel 4-Processor Server System S7000FC4UR:

<http://www.intel.com/products/server/systems/s7000fc4ur/s7000fc4ur-overview.htm>



## We want to hear from you

### Join the conversation on Intel's Open Port: **The Server Room**

- Bring your questions to the "Ask an Expert" discussion forum
- Share best practices with IT influencers
- Engage with Intel on your Datacenter challenges

Performance tests and ratings are measured using specific computer systems and/or components and reflect the approximate performance of Intel products as measured by those tests. Any difference in system hardware or software design or configuration may affect actual performance. Buyers should consult other sources of information to evaluate the performance of systems or components they are considering purchasing. For more information on performance tests and on the performance of Intel products, visit Intel Performance Benchmark Limitations

INFORMATION IN THIS DOCUMENT IS PROVIDED IN CONNECTION WITH INTEL® PRODUCTS. NO LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, TO ANY INTELLECTUAL PROPERTY RIGHTS IS GRANTED BY THIS DOCUMENT. EXCEPT AS PROVIDED IN INTEL'S TERMS AND CONDITIONS OF SALE FOR SUCH PRODUCTS, INTEL ASSUMES NO LIABILITY WHATSOEVER, AND INTEL DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY, RELATING TO SALE AND/OR USE OF INTEL PRODUCTS INCLUDING LIABILITY OR WARRANTIES RELATING TO FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT. UNLESS OTHERWISE AGREED IN WRITING BY INTEL, THE INTEL PRODUCTS ARE NOT DESIGNED NOR INTENDED FOR ANY APPLICATION IN WHICH THE FAILURE OF THE INTEL PRODUCT COULD CREATE A SITUATION WHERE PERSONAL INJURY OR DEATH MAY OCCUR.

Intel may make changes to specifications and product descriptions at any time, without notice. Designers must not rely on the absence or characteristics of any features or instructions marked "reserved" or "undefined." Intel reserves these for future definition and shall have no responsibility whatsoever for conflicts or incompatibilities arising from future changes to them. The information here is subject to change without notice. Do not finalize a design with this information.

The products described in this document may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request. Contact your local Intel sales office or your distributor to obtain the latest specifications and before placing your product order. Copies of documents which have an order number and are referenced in this document, or other Intel literature, may be obtained by calling 1-800-548-4725, or by visiting Intel's Web site at [www.intel.com](http://www.intel.com).

Copyright © 2009 Intel Corporation. All rights reserved. Intel, the Intel logo, Xeon, and Core are trademarks of Intel Corporation in the U.S. and other countries.

\*Other names and brands may be claimed as the property of others.

Printed in USA

0109/RS/OCG/XX/PDF

 Please Recycle

321250-001US

