

## **Product Information**

Model#: RS 2100

Size (LxWxH in/mm): 24X17X3.468 in / 610x432x88 mm

5.25" Bays: 1

3.50" Bays: 5 (includes 4X Hot Swap SCSI Ultra 3 drive

bays)

Fans: 4 x 80mm ( 2 x 80mm standard & 2 x 80mm

optional)

**Power Supply: CI Design, CA-300ATX** 

Other Information:

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

## **Additional Information**

Associated Model #s: N/A

Options: Fans, hot swap redundant power supply, Color (Black or Platinum), IDE HDD Removable Tray, Rack Mount Slide Rail Kit, 3PCI Back Panel

## Ci Design RS 2100 Rack Server Enclosure www.cidesign.com

Chassis Configuration (as tested with Intel's L440GX+ Server

Board)

Model tested: RS 2100

Fans (qty/size): 4 x 80mm (2 x Standard, 2 x Optional)

Hard drives: 3 x Seagate\* ST39102LC Cheetah\*

Processor: 2 x 850MHz Pentium® III

Memory: 512 MB

**Power Supply: CI Design CA-300ATX** 

**RAID: Intel, BOXSRCU21** 

**Additional Information: Tested With optional fans.** 

\* Third Party names and brands are the property of the respective owner.

Note: Modifications to the tested configuration may cause variations in actual performance.

## **List of Intel**

**Real Server Boxed Boards** 

**Mechanically Compatible with:** 

L440GX+ (850 MHz)

Thermally Compatible with:

L440GX+ (850 MHz)

**CE Testing Performed with:**