

#### **Product Information**

Model# KI-P20

Size (LxWxH inches/mm) 19.5x19x7"/508x445x177mm

5.25" Bays x 2

3.50" Bays x 3

Fans x 1(12cm ball bearing fan)

Power Supply PS-II 250W/300W

Other Information: Lockable front door, Easily removable dust filter, card guide for ISA/PCI

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

### **Additional Information**

Associated Model #s:KI-P22 (AT 12 slots), KI-P24 (AT 14 slots)

Options: 1-8 cm fan,redundant P/S (EPR-2250M), Hot

**Swap drives** 

# MACASE Industrial Corp. KI-020WP

www.macase.com.tw

Chassis Configuration (as tested with Intel's L440GX+

server board)

Model tested: KI-020WP

Fans (size, qty): 8 cm, 3 and 12 cm, 2

Hard drives: 1-Seagate\* ST39102LW Cheetah\*

Processor: 2 x 450MHz Pentium® II

Memory: 256 MB

Power Supply: Seven Team\* ST-301HR

**Additional Information:** 

\* Third Party names and brands are the property of the respective owner.

Note: Modifications to the tested configuration may cause

variations in actual performance.

## **List of Intel**

## **Real Server Boxed Boards**

**Mechanical Validation** 

L440GX+, N440BX, T440BX

**Thermal Validation** 

L440GX+, N440BX, T440BX

**EMI (CISPR) Validation** 

**N440BX**