



# Chenbro SR101 (Ultra)

[www.chenbro.com.tw/](http://www.chenbro.com.tw/)

## Product Information

**Model#: SR101 (Ultra)**

**Size (LxWxH in/mm): 22.8x14.6x26.8in/583x370x680mm**

**5.25" Bays: 12**

**3.50" Bays: 1 exposed, 8 internal**

**Fans: 4 x 9cm (12 x 9 cm, 2 x 8 cm, 1 x 6 cm optional)**

**Power Supply: Dual or Trio Redundant PSU**

**3 x PS/2 standard PSU**

**Other Information: SCA HDD Raid module is optional**

**Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.**

## Additional Information

**Associated Model #s:**

**Options: Hot Swap Drives.  
Redundant PSU**

**Chassis Configuration:** (Server Board SDS2 Tested Chassis List Based On Mechanical and Thermal Regression Testing of Chassis Posted on Server Board STL2 Reference List)

**Model tested: SR101 (Ultra)**

**Fans (qty x size): 5 x 90 mm, 1 x 60 mm**

**Hard drives: 3 x Seagate\* ST328451 LW Cheetah\***

**Processor: 2 x 1 Ghz Pentium® III FC-PGA**

**Memory: 256 MB SDRAM**

**Power Supply:** (Contact Chassis Supplier for information on Compatible Power Supplies for Server Board SDS2)

**RAID: Intel, BOXSRCU31L**

**Additional Information:**

\* Third party names and brands are the property of their respective owners.

**Note: Modifications to the tested configuration may cause variations in actual performance.**

## List of Intel

### Real Server Boxed Boards

**Mechanically Compatible with:**

**STL2, SAI2, SDS2**

**Thermally Compatible with:**

**STL2, SAI2, SDS2**

**CE Testing Performed with:**