



CI Design RS 4100 Rack Server Enclosure

www.cidesign.com

Product Information

Model#: RS 4100

Size (LxWxH in/mm): 17X24X6.968 in / 432x610x177 mm

5.25" Bays: 5

3.50" Bays: 5 Hot Swap SCSI

Fans: 4 x 80mm (4 x 80mm standard & 2 x 80mm optional)

Power Supply: Seasonic, SR-300FS

Other Information:

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

Chassis Configuration: (Server Board SDS2 Tested Chassis List Based On Mechanical and Thermal Regression Testing of Chassis Posted on Server Board STL2 Reference List)

Model tested: RS 4100

Fans (qty/size): 4 x 80mm Standard

Hard drives: 3 x Seagate* ST328451LC Cheetah*

Processor: 2 x 1 GHz Pentium® III FC-PGA

Memory: 256 MB

Power Supply: ([Contact Chassis Supplier for information on Compatible Power Supplies for Server Board SDS2](#))

RAID: Intel, BOXSRCU31L

Additional Information:

* Third Party names and brands are the property of the respective owner.

Note: Modifications to the tested configuration may cause variations in actual performance.

Additional Information

Associated Model #s: 09-1702-XXX; 09-1706-XXX

Options: Fans, hot swap redundant power supply, Color (Black or Platinum), IDE HDD Removable Tray, Rack Mount Slide Rail Kit, 3PCI Back Panel

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

[STL2](#), [SAI2](#), [SDS2](#)

Thermally Compatible with:

[STL2](#), [SAI2](#), [SDS2](#)

CE Testing Performed with: