



Chenbro A9791

www.chenbro.com.tw/

Additional Information

Associated Model #s: A9741, A9751, A9781, A9791
Options: Hot Swap Drives.
Redundant PSU

Chassis Configuration (as tested with Intel's Server Board STL2)

Model tested: A9791
Fans (qty x size): 5 x 90 mm
Hard drives: 3 x Seagate* ST328451 LW Cheetah*
Processor: 2 x 1 GHz Pentium® III FC-PGA
Memory: 256 MB SDRAM
Power Supply: EMACS AP2-5400F-RV2
RAID: Intel, BOXSRCU31L
Additional Information:

* Third party names and brands are the property of their respective owners.

Note: Modifications to the tested configuration may cause variations in actual performance.

Product Information

Model#: A9791
Size (LxWxH in/mm): 22.8x14.8x22.8in/583x376x580mm
5.25" Bays: 11
3.50" Bays: 2 exposed, 4 internal
Fans: 3 x 9cm (9 x 9 cm, 1 x 8 cm, 1 x 6 cm optional)
Power Supply: Dual or Trio Redundant PSU
3 x PS/2 standard PSU
Other Information: SCA HDD Raid module is optional

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

L440GX+ (850 MHz), T440BX, STL2

Thermally Compatible with:

L440GX+ (850 MHz), T440BX, STL2

CE Testing Performed with:

L440GX+ (450 MHz)