

# Chenbro A9891

[www.chenbro.com.tw/](http://www.chenbro.com.tw/)



## Product Information

**Model#:** A9891

**Size (LxWxH in/mm):** 20.4x14.8x18.4 in/518x376x467mm

**5.25" Bays:** 8

**3.50" Bays:** 2 exposed, 4 internal

**Fans:** 2 x 9cm (1 x 12 cm, 3 x 9 cm, 1 x 6 cm optional)

**Power Supply:** Dual Redundant PSU

2 x PS/2 standard PSU

**Other Information:** SCA HDD Raid module is optional

**Note:** The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

## Additional Information

**Associated Model #s:** A9841, A9851, A9881, A9891, A9881-1, A9891-1, A9881-7, A9891-7

**Options:** Hot Swap Drives.  
Redundant PSU

## Chassis Configuration (as tested with Intel's Server Board STL2)

**Model tested:** A9891

**Fans (qty x size):** 3 x 92 mm

**Hard drives:** 3 x Seagate\* ST328451 LW Cheetah\*

**Processor:** 2 x 1 GHz Pentium® III FC-PGA

**Memory:** 256 MB SDRAM

**Power Supply:** EMACS RPD-5300F-RV2S

**RAID:** Intel, BOXSRCU31L

**Additional Information:**

\* Third party names and brands are the property of their respective owners.

**Note:** Modifications to the tested configuration may cause variations in actual performance.

## List of Intel

### Real Server Boxed Boards

**Mechanically Compatible with:**

**L440GX+ (850 MHz), N440BX, T440BX, STL2**

**Thermally Compatible with:**

**L440GX+ (850 MHz), N440BX, T440BX, STL2**

**CE Testing Performed with:**

**L440GX+ (450 MHz), N440BX, T440BX**