

Signum Data Futurecase 600E

<http://www.signumdata.de>



Product Information

Model#: FutureCase 600E

Size (LxWxH in/mm): 29x17x10in / 736x430x255mm

5.25" Bays: 10

3.50" Bays: 1 external

Fans: 3 120mm

Power Supply: Unipower/ETNF 2933-232/450W

Other Information: Hotswap PS, optional redundant

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

Additional Information

Associated Model #s: 600E

Options:

Chassis Configuration (as tested with Intel's Server Board STL2)

Model tested: 600E

Fans (qty x size): 6 x 40mm (HDA Fans), 3 x 120mm

Hard drives: 3 x Seagate* ST318451 LC Cheetah X15*

Processor: 2 x 1 GHz Pentium® III FC-PGA

Memory: 256 MB

Power Supply: Unipower/ETNF 2933-232

RAID: Intel, BOXSRCU31L

Additional Information:

* Third party names and brands are the property of their respective owners.

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

STL2

Thermally Compatible with:

STL2

CE Testing Performed with: