



[www.aicipc.com](http://www.aicipc.com)

### Product Information

**Model# RMC2M**

**Size (LxWxH inches/mm) 25.6x19x3.5 / 650x483x89**

**5.25" Bays: 1**

**3.50" Bays: 1 external**

**Hot-swap Bays: 4x1.6" Ultra 160 SCSI**

**Fans: 4 x 80mm**

**Power Supply: Emac P2U-6300P 300W ATX w/PFC**

**Other Information: 3x32-bit PCI or 2x64-bit PCI offset riser cards and 400W single power supply w/PFC are available for this chassis.**

**Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any changes.**

# Advanced Industrial Computer RMC2M

**Chassis Configuration** (as tested with Intel's Server Board STL2)

**Model tested: RMC2M**

**Fans (size, qty): 80mm - 4**

**Hard drives: 3 Seagate ST318451 LC**

**Processor: 2 - Intel® Pentium III (FC-PGA)**

**Memory: 256 MB**

**Power Supply: EMACS 300W P2U-6300P**

**RAID: Intel, BOXSTCU31L**

**Additional Information:**

**Note: Modifications to the tested configuration may cause variations in actual performance.**

### List of Intel

#### Real Server Boxed Boards

**Mechanical Validation**

**STL2**

**Thermal Validation**

**STL2**

**EMI (CISPR) Validation**

**STL2**