



<http://www.siliconrax-sliger.com/>

Siliconrax-Sliger SR-CX246

Chassis Configuration (as tested with Intel's Server Board STL2)

Model tested: SR-CX246

Fans (size, qty): 80mm - 3

Hard drives: 3 Seagate ST318451 LC

Processor: 2 - Intel® Pentium III (FC-PGA)

Memory: 256 MB

Power Supply: 2 - Elan Vital 300W EVR-3006

RAID: Intel, BOXSTCU31L

Additional Information:

Note: Modifications to the tested configuration may cause variations in actual performance.

Product Information

Model# SR-CX246

Size (LxWxH inches/mm) 24x19x3.5 / 608x483x89

5.25" Bays: None

3.50" Bays: 4 x SCA, 1 x slim size FDD, 1 x slim size CD

Fans: 3 intake fans, 2 exhaust fans

Power Supply: ElanVital/EVR-3006/300W

Other Information: Four hot swap SCSI drives and front access redundant hot swap 300W power supply makes this chassis fault resilient and easily serviceable.

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any changes.

List of Intel

Real Server Boxed Boards

Mechanical Validation

STL2

Thermal Validation

STL2

EMI (CISPR) Validation

STL2